

Bio-stabilized modular rammed earth blocks for sustainable and aesthetic construction

Ahmed Abdelaal, Jiaming Ma, Hongru Zhang and Vahid Shobeiri
*Centre for Innovative Structures and Materials, School of Engineering,
RMIT University, Melbourne, Australia, and*

Yi Min Xie

*Centre for Innovative Structures and Materials, School of Engineering,
RMIT University, Melbourne, Australia, and College of Future Technologies,
Hohai University, Changzhou, China*

Received 15 May 2025
Revised 22 August 2025
Accepted 14 September 2025

Abstract

Purpose – This study aims to address critical limitations in rammed earth (RE) construction through a novel modular block system integrating computational design, modular construction and bio-stabilization techniques. The research quantifies environmental benefits and structural performance, establishing empirical foundations for commercial implementation of prefabricated earthen construction technologies.

Design/methodology/approach – The methodology used non-uniform rational B-splines (NURBS)-based parametric design for customized free-form blocks with five distinct types facilitating staggered assembly. Bio-stabilization was evaluated using animal glue and xanthan gum versus unstabilized variants. Life cycle assessment was conducted following ISO 14040 protocols. Full-scale prototyping validated manufacturing through CNC-milled formwork, while experimental validation included 28-day compressive strength testing and environmental impact quantification.

Findings – Full-scale prototyping confirmed technical feasibility of the modular free-form RE block system, achieving consistent production through precision CNC-milled formwork. Staggered assembly methodology enhanced structural stability via embedded reinforcement channels. Animal glue bio-stabilization demonstrated superior performance metrics (6.86 MPa strength, 38.61 kg CO_{2-eq}/m³ emissions) compared to xanthan gum (5.58 MPa, 60.12 kg CO_{2-eq}/m³) and unstabilized variants (1.74 MPa, 12.32 kg CO_{2-eq}/m³).

Originality/value – This research pioneers computational design integration with traditional RE construction, establishing novel methodological frameworks for sustainable building. The synthesis of NURBS parametric geometry, prefabrication protocols and bio-stabilization represents significant advancement in earthen architecture, providing construction professionals with validated methodologies for achieving architectural sophistication while maintaining environmental sustainability.

Keywords Sustainability, Sustainability and green buildings, Open manufacturing/offsite construction, Computer aided design, Life-cycle analysis

Paper type Research paper

© Ahmed Abdelaal, Jiaming Ma, Hongru Zhang, Vahid Shobeiri and Yi Min Xie. Published by Emerald Publishing Limited. This article is published under the Creative Commons Attribution (CC BY 4.0) licence. Anyone may reproduce, distribute, translate and create derivative works of this article (for both commercial and non-commercial purposes), subject to full attribution to the original publication and authors. The full terms of this licence may be seen at <http://creativecommons.org/licenses/by/4.0/>

Declaration of competing interest: The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.



Construction Innovation
Vol. 26 No. 9, 2026
pp. 1-20
Emerald Publishing Limited
1471-4175
DOI 10.1108/CI-05-2025-0224

1. Introduction

Rammed earth (RE) construction spans 10,000 years (Jaquin *et al.*, 2008; Xie *et al.*, 2021), historically using simple tools and manual labor (Houben and Guillaud, 1994; Woolley, 2006) while offering low embodied energy and superior thermal mass properties (Allinson and Hall, 2010; Cabeza *et al.*, 2013). Traditional RE buildings faced stability, durability and labor limitations (Gomes *et al.*, 2014; Jaquin *et al.*, 2007; Walker *et al.*, 2005). To address these issues, contemporary RE construction incorporates advanced materials, digital fabrication and sustainable innovations (Arrigoni *et al.*, 2017; Ma *et al.*, 2025, 2024b, 2024a). These advancements extend to bio-stabilization (Blok *et al.*, 2019; Fatehi *et al.*, 2021), prefabrication (Abdelaal *et al.*, 2025; Niroumand *et al.*, 2021) and robotic construction (Gomaa *et al.*, 2023, 2022). While modern RE enables complex geometries and enhanced mechanical performance (Ciancio and Beckett, 2015; Paio, 2013), challenges persist, including labor intensity, height limitations and formwork complexity (Dabaieh, 2014; Maniatidis and Walker, 2008; Preciado and Santos, 2020). To address the above issues, automated systems have been developed aiming to achieve programmable formwork positioning and pneumatic compaction (Willmann *et al.*, 2012).

Earthen construction used diverse stabilization methodologies spanning millennia (Losini *et al.*, 2021). Bitumen was used in Mesopotamian construction from 3000 BCE for waterproofing and structural adhesion (Connan, 1999), concurrent with lime-based stabilization documented from Neolithic sites dating to 5000 BCE (Lu *et al.*, 2023; Xie *et al.*, 2021). Biopolymeric stabilizers, including proteins (casein), polysaccharides (starch) and polyphenols (tannins), also demonstrated effectiveness through both archaeological evidence and contemporary characterization studies (Losini *et al.*, 2022, 2021; Lu *et al.*, 2023). The 19th-century's transition to Portland cement for stabilization – patented by Joseph Aspdin in 1824 and achieving widespread adoption by the 1850s – has revived RE in modern construction (Bennett, 2005; Chen *et al.*, 2025; Gillard, 2018; Scrivener *et al.*, 2018). Natural fiber reinforcement – incorporating straw, animal hair and vegetal materials – enhanced tensile properties while extending durability to more than 20 years (Bui *et al.*, 2009; Gomes *et al.*, 2014). To further enhance tensile and seismic performance for RE, mechanical reinforcement is incorporated in modern RE construction. Bamboo reinforcement is widely used across Asia, Latin America and Africa – demonstrating 139%–167% flexural strength improvements (Tripura *et al.*, 2020; Zhang *et al.*, 2024). Steel reinforcement is adopted in earthquake-prone regions. Meanwhile, hybrid bamboo-steel configurations occur to balance structural performance and sustainability metrics (Beckett *et al.*, 2024; Tripura *et al.*, 2020; Tripura and Singh, 2019). However, the incorporation of reinforcement complicated the construction process and resulted in higher costs and carbon footprints. More importantly, the reliance on cement for stabilization creates notable environmental impacts through CO₂ emissions (Losini *et al.*, 2022; Morel *et al.*, 2007), water consumption and waste (Andrew, 2018; Dams *et al.*, 2021; Galluccio *et al.*, 2019; Madlool *et al.*, 2011; Zhang *et al.*, 2012), necessitating contemporary reassessment of bio-based alternatives within sustainability frameworks. Bio-binders from agricultural and animal by-products offer sustainable alternatives (Abdelaal *et al.*, 2025; Fatehi *et al.*, 2021; Losini *et al.*, 2021) requiring further large-scale research. Earth processing demands only 1% of energy compared to fired bricks or concrete (Minke, 2006) due to minimal processing and local sourcing (Dams *et al.*, 2021). Bio-stabilizers such as xanthan gum and animal glue maintain performance, while reducing impacts through lower processing temperatures (60°C–65°C) versus conventional stabilizers (Abdelaal *et al.*, 2025; Idris *et al.*, 2010). These align with circular economy principles through waste reuse (Xie *et al.*, 2024), reducing embodied energy and emissions (Scrivener *et al.*, 2018; Worrell *et al.*, 2008).

Modular construction presents an opportunity to address traditional RE implementation challenges while maintaining RE's sustainability benefits. This methodology represents a shift from traditional on-site to off-site manufacturing (Bertram *et al.*, 2019). Analysis demonstrated that modular implementation could reduce total construction duration by 33% (18–24 to 13–16 months) and on-site construction time by 83% (2–12 months), while achieving 10%–25% savings in on-site labor costs (Bertram *et al.*, 2019). This evolution, driven by advanced material technologies, digital integration and increased emphasis on sustainability (Ferdous *et al.*, 2019), faces challenges in RE implementation including material optimization, modular design strategies and complex integration of design, manufacturing and assembly processes (Subramanya *et al.*, 2020).

Modern RE production methods include prefabrication in controlled environments – improving quality control and material properties (Giuffrida *et al.*, 2019; Pan, 2012). However, prefabrication for RE construction faces several challenges. These include logistical complexities, transportation constraints due to module dimensions and weight, susceptibility to edge damage during transport (Lee *et al.*, 2022) and interoperability between construction phases (Giuffrida *et al.*, 2019). These considerations necessitate the development of optimized block sizes that balance structural performance with manufacturing efficiency, requiring careful attention to load-bearing capacity, stability and inter-module connections (Hendry, 1998; Niroumand *et al.*, 2021). To address these challenges, this research proposed a novel modular RE block system combining advanced computational design, modular integrated construction and sustainable bio-binder stabilization. The system featured free-form blocks with smooth geometry transitions, staggered block arrangement and interconnection, validated through full-scale prototyping and a wall construction.

2. Methodology

2.1 Modular design principles

The design used a two-step geometric approach. First, an inner boundary was created through uniform offset, with distance determined by continuity requirements for smooth module transitions and desired curvature profiles. Second, shared symmetric boundaries defined surface continuity conditions, with tangency guides and height parameters controlling variation.

Identical edge geometry enabled four rotational positions per block. This flexibility, multiplied by assembly blocks, created design possibilities while preserving structural integrity and continuity. Prototype dimensions (50 cm × 50 cm × 25 cm) balanced structural requirements with practical handling.

The block geometry was defined by a parametric non-uniform rational B-splines (NURBS) surface with boundary conditions and tangency constraints, where u-v directional isocurves form a curvilinear mesh network. Within this variable domain, non-uniform geometric deformation maintained geometric continuity while allowing for design variation. This continuity was validated through zebra striping visualization analysis, which demonstrated surface coherence across adjacent blocks, with vertical red contours revealing the topographic characteristics of the surface geometry (see Figure 1).

The system enabled designers to manipulate UV curves through control points, generating diverse surface geometries while maintaining inter-module continuity. The underlying geometry (see Figure 2) was defined by a parametric NURBS surface with boundary conditions and tangency constraints, where u-v directional isocurves form a curvilinear mesh network. Within this variable domain, non-uniform geometric deformation maintained geometric continuity, characterized by its control mesh and spline-based interpolation.



(a)



(b)

Figure 1. Block geometry: (a) rendered image of modular rammed earth block with free-form surfaces and (b) zebra striping visualization demonstrating surface continuity with vertical red contours revealing topographic characteristics

Source: Author's own work




Figure 2. NURBS surface geometry illustrating the variable domain, tangency domain and isocurve directions (u and v) that define the parametric block geometry with controlled deformation parameters

Source: Author's own work

The modular assembly configuration (see [Figure 3](#)) used parametrically defined surface components with symmetrical edges. NURBS-based geometry-maintained curvature continuity across blocks while allowing for controlled deformation within variable domains. UV isocurves formed the curvilinear mesh network for defining topology, enabling customisation while preserving continuity across the system geometry.




Figure 3. Modular assembly configuration showing block staggering possibilities with block A and block B, demonstrating how the symmetric boundary design facilitates geometry continuity and structural integrity

Source: Author’s own work

The system used five block types (see Figure 4) designed for different structural roles to build an architectural four-wall enclosure. Primary blocks (A–B) functioned as main load-bearing elements, while secondary blocks (C–E) served as connection components and space-forming elements. Each block type included variations with strategically positioned reinforcement channels that enhanced structural performance without requiring additional manufacturing time or materials. The standardized dimensions facilitated field measurements, manual handling and planning efficiency (Kamali and Hewage, 2016). This modular system allowed flexible configurations (Huang *et al.*, 2023), while the earth-based composition delivered reduced embodied energy and environmental benefits (Greer and Horvath, 2023; Wu *et al.*, 2024).

2.2 RE block fabrication

CNC-milled bases defined surface geometry, while removable side panels established boundaries, and positioned holes provided reinforcement channels (Figure 5). Production proceeded through formwork setting, soil filling, then layered compaction (Figure 6). This approach enabled consistent production with geometric precision across block types. The modular system facilitated efficient assembly/disassembly, reducing time while ensuring quality control. Released blocks maintained geometric properties fulfilling structural and architectural requirements (Figure 7).




Figure 4. Five modular rammed earth block types: Block A and B serve as primary structural blocks, while blocks C, D and E function as secondary connection elements

Source: Author’s own work




Figure 5. Formwork system components showing: CNC-milled base with tube alignment holes on the left, and the resulting block with curved surface geometry and integrated sling notches on the right after formwork removal

Source: Author’s own work




Figure 6. Block production: (a) the formwork assembled, (b) filling soil and ramming the initial layers, (c) concentrating the ramming force to create a gap for the PVC tubes and assembly of the clamps, (d) assembly the tubes in position and (e) filling soil and ramming remaining layers and completing the final ramming sequence

Source: Author’s own work




Figure 7. Formwork system and resulting blocks: (a) initial block setting after 24-h with side panels removed showing the CNC-milled base with sling notches, (b) flipped block setting after 48-h initial curing period with the base removed and (c) finished rammed earth blocks arranged for the remaining three-week moisture stabilization

Source: Author's own work

2.3 Assembly process

Following 28-day curing, blocks were assembled on-site. Positioning used bottom-surface slings (Figure 8), avoiding top lifting. Assembly followed predetermined sequences: foundation placement, then vertical stacking considering load distribution. Reinforcement bars inserted through embedded channels ensured alignment while enhancing structural integrity. The staggered configuration, with half-length overlap, eliminated continuous vertical joints and enhanced stability through geometrical interlocking.

Upon completion of the primary assembly, post-processing was conducted to fill the lifting notches with soil and smooth the surface through sanding. This final step ensured geometric continuity throughout the structure while preserved the aesthetic qualities inherent in the natural textures of RE material.

2.4 Environmental impact assessment

This study examined the environmental benefits of using bio-binders (Abdelaal *et al.*, 2025), with a functional unit of one cubic meter. The life cycle assessment followed ISO 14040 guidelines, focusing on the material preparation phase, while excluding transport emissions and the fabrication processes described in Section 3.2 due to their prototype-scale variability. The base mixture comprised three equal portions of soil with varying grain sizes 0–2.36 mm, 2.36–13.2 mm and 13.2–20 mm, totaling 2,862 g for each sample, combined with 10% water 286.2 g and 1% binder 28.62 g. All soil materials were sieved to obtain the required particle size distribution prior to mixing. Three configurations were evaluated using different binding agents: un-stabilized rammed earth (URE), stabilized with animal glue (AG) and stabilized with xanthan gum (XG). Emissions calculations were based on material embodied carbon values and process energy requirements for preparing the mixtures. Mechanical performance was assessed through 28-day compressive strength tests conducted on 100 mm cube specimens for all three mixture types (URE, AG and XG). The production process for the AG mixture involved an energy-intensive boiling step requiring 2.2 kWh/m³ (Abdelaal *et al.*, 2025), contributing 1.5026 kg CO_{2-eq}/m³, while all mixtures underwent a mixing process consuming 1.2 kWh/m³ (based on product manufacturing details), adding 0.8196 kg CO_{2-eq}/m³. The energy-related emissions were calculated based on Australian electricity mix using an electricity carbon intensity factor of 0.683 kg CO₂/kWh (Stuart, 2017), while material embodied carbon values were obtained from multiple sources: 0.004 kg CO_{2-eq}/kg for soil (Avila *et al.*, 2021), 0.866 kg CO_{2-eq}/kg for animal glue (technical data from Gelita Australia), 1.67 kg CO_{2-eq}/kg for xanthan gum (Kumar *et al.*, 2023) and 0.0002 kg CO_{2-eq}/kg for water (Shobeiri *et al.*, 2023). In terms of performance as shown in (see Figure 9), plain URE demonstrated the lowest CO₂ emissions at




Figure 8. Assembly procedure for the rammed earth blocks showing: (a) reinforced steel bars and slings for lifting, (b) foundation block placement, (c) vertical stacking considering load distribution, (d) half-sized block integration with the assembly and (e) the final assembled wall

Source: Author's own work

12.32 kg CO_{2-eq}/m³ but achieved only 1.74 MPa strength, indicating limited structural capacity. The AG-stabilized mixture produced moderate emissions at 38.61 kg CO_{2-eq}/m³ while achieving the highest strength of 6.86 MPa, resulting in the most efficient kg CO_{2-eq}/m³·MPa ratio of 5.63. In contrast, the XG mixture generated the highest emissions at 60.12 kg CO_{2-eq}/m³ with 5.58 MPa strength, yielding the least favorable kg CO_{2-eq}/m³·MPa ratio of 10.77. The analysis concluded that the AG-stabilized mixture represents the optimal balance between environmental impact and structural performance, while XG, despite its good strength, proves least sustainable due to its high environmental impact. These findings underscored the importance of considering both environmental and structural factors in sustainable construction material selection, with AG emerged as a promising binder for RE applications.

3. Prototyping

3.1 Mixture, preparation and production

The modular RE blocks incorporated a soil mixture of 50% 5 mm minus cream crusher dust and 50% 10 mm minus cream crushed rocks from Hastings region quarries in Victoria,




Figure 9. Environmental impact assessment comparing three rammed earth mixtures: (a) efficiency ratios and (b) emissions

Source: Author's own work

Australia, with edible bovine gelatine 200 bloom grade serving as a sustainable bio-binder at 1% by soil weight and 10% water content. Compaction was performed in seven successive layers using two different rammers. The initial two layers were compacted with a Trax KPT-1L Kawasaki sand rammer operating at 1,800 blows per minute with 18 mm butt diameter. For the remaining five layers, an Ingersoll Rand 241A1M floor sand rammer was used, operating at 1,590 blows per minute with 102 mm stroke length and 33 mm bore. Each layer underwent 30–40 s of compaction to minimize voids and optimize compression. Following compaction, specimens underwent curing in a semi-controlled outdoor environment representative of Melbourne ambient conditions.

3.2 Off-site fabrication process

The modular RE block fabrication used precision manufacturing techniques to create the complex geometries required for the block system. The formwork system consisted of a CNC-milled obomodulan® 710 terra polyurethane base (700 kg/m^3 density, 25–30 MPa compressive strength) to achieve precise free-form geometries (see Figure 10). The process involved assembling removable plywood formwork sides with sufficient rigidity (see Figure 11). The formwork walls were constructed with a 36 mm thickness to ensure adequate stiffness and minimize deformation during the high-pressure ramming process. This formwork system accommodated the positioning of PVC tubes, creating channels for reinforcement bars that facilitate structural connectivity between blocks during final assembly (see Figure 12).

The fabrication process followed a systematic procedure for integrating reinforcement channels in the RE blocks. Initially, the formwork base and boundaries were assembled without the reinforcement tubes, as illustrated in Figure 13. The soil mixture was then compacted in sequential layers following the methodology detailed in Section 2.3. Upon reaching the designated height for tube placement (approximately mid-height of the block), the ramming process was temporarily halted. At this stage, PVC tubes were precisely




Figure 10. Formwork base components: front and back views of the CNC-milled timber base, showing integrated sling notches for lifting
Source: Author's own work




Figure 11. Formwork component assembly showing the main structural elements and tube positioning system
Source: Author's own work

positioned according to the predetermined layout (see [Figure 14](#)), creating channels that will later accommodate steel reinforcement bars. After securing the tubes in position, the ramming process continued until the block reaches its final thickness of 25 cm. This integrated channel system provided critical structural benefits: it ensured precise alignment during wall assembly, enhanced load distribution across the wall system and significantly increased the composite structure's resistance to lateral forces. The strategic positioning of these channels – following the block's geometry contours – maintained the structural integrity while facilitating the reinforcement connectivity that is essential for creating a cohesive wall assembly.

The completed RE blocks required precise dimensional control to ensure both aesthetic quality and proper assembly fit. The bottom surface featured consistent lifting notches specifically designed to accommodate slings for handling. Following compaction, the RE blocks followed a systematic desiccation procedure: 24 h within the formwork, followed by side panel removal. Then, a 48-h initial curing period was implemented to ensure the structural integrity of the blocks during flipping and handling. Following this phase, blocks were transferred to the designated curing location for the remaining three-week moisture stabilization period (see [Figures 15](#) and [16](#)).




Figure 12. Complete formwork assembly showing all setting and the tubes that will be placed after ramming to its level, including plywood formwork side, sling notches, PVC tubes, CNC-milled obomodulan® 710 terra polyurethane base and side fastener

Source: Author's own work

4. Results and discussion

4.1 Assembly of prefabricated rammed earth wall

Upon completion of a 28-day curing period, the RE blocks attained sufficient compressive strength for transportation to the construction site. The assembly protocol (see Figure 17) used sling mechanisms for block placement and implemented a staggered configuration for optimal structural stability. The assembly proceeded in two sequential steps: first, establishing a triangular wall configuration using the full-sized primary blocks; second, completing the wall formation by installing the remaining blocks. Due to laboratory constraints during the prototype testing phase, timber spacers were temporarily used in place of the half-sized blocks.

The wall assembly was constructed using eight blocks in a staggered configuration, yielding overall dimensions of 1.5×1.5 m [Figure 18(a)]. The experimental protocol excluded notch filling and surface finishing procedures to examine raw interface characteristics. This approach revealed interface discontinuities, particularly at notch locations. Surface damage from transport was identified in areas requiring refinement: notch design modifications and edge reinforcement. Block curing and assembly were carried out during Melbourne's winter period (July 2024, rainfall: 96.8 mm, 67% above average). Despite variable environmental exposure, the RE blocks achieved adequate strength for assembly, enabling completion of the 1.5×1.5 m prototyping.

The anticipated low-rise structure, upon completion, was expected to resemble the visualization [as shown in Figure 18(b)–(c)]. These rendered images illustrated the potential integration of the modular RE wall system in a single-story residential application.




Figure 13. Formwork assembly sequence: (a) CNC-milled lower base of the formwork with surface curvature positioned on the flat layer with channels for sling placement, (b) side panels attached to the base, (c) slings positioning guides installed, (d) completed formwork assembly before soil compaction and (e) PVC tubes installed in position for creating reinforcement channels
Source: Author's own work




Figure 14. Block production: (a) the formwork assembled, (b) ramming the initial two layers, (c) concentrating the ramming force to create a gap for the tubes, (d) the tubes assembled in place, (e) ramming last layers and (f) flattening the last layer manually
Source: Author's own work




Figure 15. Block handling and stockage preparation: (a) sliding slings into grooves at the bottom of the CNC milled base, (b) fastening slings, (c) flipping the block onto slings, (d) removing the CNC milled base, (e) sling slot detail allowing removal and (f) stacking blocks for the drying period
Source: Author's own work



Figure 16. Finished rammed earth block showing curved surface geometry after being released from the CNC milled base for drying, with visible notches at the bottom surface for handling
Source: Author's own work




Figure 17. RE wall assembly process using mechanical lifting equipment: (a) first stage assembly showing bottom rows of blocks arranged in a triangular formation, (b) continued assembly with additional top block and (c) second stage assembly showing slings for safe handling

Source: Author's own work

4.2 Limitation and future work

This research explores the feasibility of freeform modular RE blocks integrating advanced parametric design with bio-stabilization techniques. While the current study focuses on the geometry modeling and construction workflow, systematic assessments on the mechanical and durability performance of the proposed system will be critical for the next steps. These include axial compression and tensile tests, as well as flexural, seismic, hygrothermal and fire resistance evaluations. Durability testing through wet–dry cycling and freeze–thaw protocols will further validate the practical applicability. Development of automated modular construction systems will also be necessary to improve efficiency while ensuring consistent quality.



(a)



(b)



(c)

Figure 18. Modular rammed earth implementation and conceptualized applications: (a) physical prototype showing completed wall with free-form surface blocks, (b) and (c) computer-generated visualizations of potential applications with (b) a free-standing wall structure using modular blocks and (c) conceptual rendering of a complete building incorporating the rammed earth block system

Source: Author's own work

5. Conclusion

This study proposed a novel modular RE block system that integrates computational design, modular construction and bio-stabilization techniques. The system introduced customized free-form blocks with smooth geometry transitions and a systematic assembly method that enables staggered block arrangements with integrated steel reinforcement for enhanced structural stability. Comparative analysis of stabilization methods demonstrated that animal glue bio-binder provided an optimal balance between mechanical performance and environmental impact (6.86 MPa compressive strength with 38.61 kg CO_{2-eq}/m³ emissions) when compared to both unstabilized RE (1.74 MPa, 12.32 kg CO_{2-eq}/m³) and xanthan gum-stabilized RE (5.58 MPa, 60.12 kg CO_{2-eq}/m³). The precision manufacturing process, using CNC-milled formwork and strategically embedded reinforcement channels, facilitated consistent production and reliable assembly. Full-scale prototyping confirmed the technical feasibility of the system and demonstrated its potential for architectural implementation. The research contributed to advancing sustainable construction methods that addressed traditional design and building limitations while maintaining the inherent environmental advantages of earth-based building materials.

Data availability

Data will be made available on request.

Funding

The funding source had no involvement in the study design, data collection, analysis, interpretation, writing of the report or the decision to submit the article for publication, Australian Research Council: FL190100014.

References

- Abdelaal, A., Ma, J., Gomaa, M., Giustozzi, F. and Xie, Y.M. (2025), "Stabilizing rammed earth using xanthan gum or animal glue as bio-binder", *Front. Built Environ.*, Vol. 11, p. 1535947.
- Allinson, D. and Hall, M. (2010), "Hygrothermal analysis of a stabilised rammed earth test building in the UK", *Energy and Buildings*, Vol. 42 No. 6, pp. 845–852.
- Andrew, R.M. (2018), "Global CO₂ emissions from cement production", *Earth System Science Data*, Vol. 10 No. 1, pp. 195–217.
- Arrigoni, A., Pelosato, R., Dotelli, G., Beckett, C.T.S. and Ciancio, D. (2017), "Weathering's beneficial effect on waste-stabilised rammed earth: a chemical and microstructural investigation", *Construction and Building Materials*, Vol. 140, pp. 157–166.
- Avila, F., Puertas, E. and Gallego, R. (2021), "Characterization of the mechanical and physical properties of unstabilized rammed earth: a review", *Construction and Building Materials*, Vol. 270, p. 121435.
- Beckett, C.T.S., Rimniceanu, A., Lin, B.Y.X. and Reynolds, T.P. (2024), *Bonding Behaviour of Bamboo Reinforcement in Rammed Earth*, RILEM Book. Springer, Cham. 52, pp. 475–484.
- Bennett, B. (2005), "The development of Portland cement", *Building Conservation*, Wiltshire, available at: www.buildingconservation.com/articles/prtlndcmnt/prtlndcmnt.htm (accessed 10 August 2025).
- Bertram, S., Fuchs, J., Mischke, R., Palter, G., Strube, J. and Woetzel, J. (2019), *Modular Construction: From Projects to Products*, McKinsey and Company, New York, NY, available at: <https://www.mckinsey.com/capabilities/operations/our-insights/modular-construction-from-projects-to-products> (accessed 10 August 2025).
- Blok, R., Kuit, B., Schröder, T. and Teuffel, P. (2019), "Bio-based construction materials for a sustainable future", *Proceedings of the 20th Congress of IABSE, 2019: The evolving metropolis —Report*, 860–866, New York, NY, available at: <https://research.tue.nl/en/publications/bio-based-construction-materials-for-a-sustainable-future> (accessed 10 August 2025).

- Bui, Q.B., Morel, J.C., Reddy, B.V.V. and Ghayad, W. (2009), "Durability of rammed earth walls exposed for 20 years to natural weathering", *Building and Environment*, Vol. 44 No. 5, pp. 912-919.
- Cabeza, L.F., Barreneche, C., Miró, L., Morera, J.M., Bartolí, E. and Inés Fernández, A. (2013), "Low carbon and low embodied energy materials in buildings: a review", *Renewable and Sustainable Energy Reviews*, Vol. 23, pp. 536-542.
- Chen, H., Li, N., Unluer, C., Chen, P. and Zhang, Z. (2025), "200 Years of Portland cement: Technological advancements and sustainability challenges", *Journal of Cleaner Production*, Vol. 486, p. 144500.
- Ciancio, D. and Beckett, C. (2015), *Rammed Earth Construction: Cutting-Edge Research on Traditional and Modern Rammed Earth*, CRC Press, Boca Raton.
- Connan, J. (1999), "Use and trade of bitumen in antiquity and prehistory: Molecular archaeology reveals secrets of past civilizations", *Philos. Trans. R. Soc.*, Vol. 354, pp. 33-50.
- Dabaieh, M. (2014), "Building with rammed earth – a practical experience with Martin Rauch", available at: <https://portal.research.lu.se/en/publications/building-with-rammed-earth-a-practical-experience-with-martin-rau> (accessed 1 October 2024).
- Dams, B., Maskell, D., Shea, A., Allen, S., Cascione, V., Walker, P. and Emmitt, S. (2021), "Upscaling non-residential bio-based circular construction in the United Kingdom", *IOP Conf. Ser.: Earth Environ. Sci.*, Vol. 855 No. 1, p. 012015.
- Fatehi, H., Ong, D.E.L., Yu, J. and Chang, I. (2021), "Biopolymers as green binders for soil improvement in geotechnical applications: a review", *Geosciences*, Vol. 11 No. 7, p. 291.
- Ferdous, W., Bai, Y., Ngo, T.D., Manalo, A. and Mendis, P. (2019), "New advancements, challenges and opportunities of multi-storey modular buildings – a state-of-the-art review", *Engineering Structures*, Vol. 183, pp. 883-893.
- Galluccio, S., Beirau, T. and Pöhlmann, H. (2019), "Cement as a climate killer: using industrial residues to produce carbon neutral alternatives", available at: https://pressemittelungen.pr.uni-halle.de/index.php?modus=pmanzeige&pm_id=3083 (accessed 1 October 2024).
- Gillard, L. (2018), "History of cement and lime mortars", The Yorkshire Lime Company, available at: www.theyorkshirelime.com/a-basic-history-of-cement-and-lime-mortars-and-their-use-in-construction/ (accessed 10 August 2025).
- Giuffrida, G., Caponetto, R. and Cuomo, M. (2019), "An overview on contemporary rammed earth buildings: Technological advances in production, construction and material characterization", *IOP Conf. Ser.: Earth Environ. Sci.*, Vol. 296 No. 1, p. 012018.
- Gomaa, M., Jabi, W., Soebarto, V. and Xie, Y.M. (2022), "Digital manufacturing for earth construction: a critical review", *Journal of Cleaner Production*, Vol. 338, p. 130630.
- Gomaa, M., Schade, S., Bao, D.W. and Xie, Y.M. (2023), "Automation in rammed earth construction for industry 4.0: precedent work, current progress and future prospect", *Journal of Cleaner Production*, Vol. 398, p. 136569.
- Gomes, M.I., Gonçalves, T.D. and Faria, P. (2014), "Unstabilized rammed earth: characterization of material collected from old constructions in South Portugal and comparison to normative requirements", *International Journal of Architectural Heritage*, Vol. 8 No. 2, pp. 185-212.
- Greer, F. and Horvath, A. (2023), "Modular construction's capacity to reduce embodied carbon emissions in California's housing sector", *Building and Environment*, Vol. 240, p. 110432.
- Hendry, A.W. (1998), "Structural design of masonry buildings", in Hendry, A.W. (Ed.), *Structural Masonry*, Macmillan Education, pp. 1-15.
- Houben, H. and Guillaud, H. (1994), *Earth Construction: A Comprehensive Guide*, Intermediate Technology Publications, London.
- Huang, M.Q., Chen, X.L., Ninić, J., Bai, Y. and Zhang, Q.B. (2023), "A framework for integrating embodied carbon assessment and construction feasibility in prefabricated stations", *Tunnelling and Underground Space Technology*, Vol. 132, p. 104920.

- Idris, A., Saed, K. and Hung, Y.T. (2010), "Animal glue production from skin wastes", in Wang, L.K., Tay, J.H., Tay, S.T.L., Hung, Y.T. (Eds), *Environmental Bioengineering: Volume 11*, Humana Press, Totowa, pp. 685-697.
- Jaquin, P.A., Augarde, C.E. and Gerrard, C.M. (2007), "Historic rammed earth structures in Spain: Construction techniques and a preliminary classification", *Int. J. Archit. Herit*, Vol. 1, pp. 311-326.
- Jaquin, P.A., Augarde, C.E. and Gerrard, C.M. (2008), "Chronological description of the spatial development of rammed earth techniques", *International Journal of Architectural Heritage*, Vol. 2 No. 4, pp. 377-400.
- Kamali, M. and Hewage, K. (2016), "Life cycle performance of modular buildings: a critical review", *Renewable and Sustainable Energy Reviews*, Vol. 62, pp. 1171-1183.
- Kumar, M.A., Moghal, A.A.B., Vydehi, K.V. and Almajed, A. (2023), "Embodied energy in the production of guar and xanthan biopolymers and their cross-linking effect in enhancing the geotechnical properties of cohesive soil", *Buildings*, Vol. 13 No. 9, p. 2304.
- Lee, Y., Kim, J.I., Flager, F. and Fischer, M. (2022), "Methodology to estimate logistics costs for vertically transported prefabricated wall panels", *Journal of Computational Design and Engineering*, Vol. 9 No. 4, pp. 1348-1368.
- Losini, A.E., Grillet, A.C., Bellotto, M., Woloszyn, M. and Dotelli, G. (2021), "Natural additives and biopolymers for raw earth construction stabilization – a review", *Construction and Building Materials*, Vol. 304, p. 124507.
- Losini, A.E., Grillet, A.C., Woloszyn, M., Lavrik, L., Moletti, C., Dotelli, G. and Caruso, M. (2022), "Mechanical and microstructural characterization of rammed earth stabilized with five biopolymers", *Materials*, Vol. 15 No. 9, p. 3136.
- Lu, H., Kang, N., Zhang, B., Ma, M. and Hu, Y. (2023), "Organic additives to Neolithic white lime surfaces in Yulin, Shaanxi, China", *Journal of Archaeological Science*, Vol. 158, p. 105841.
- Ma, J., Zhang, H., San Ha, N. and Xie, Y.M. (2024b), "Exploiting auxetic confinement for enhancing structural performance of earth-based construction", *Proceedings of International Association for Shell and Spatial Structures Annual Symposium, Zurich*, Vol. 2024, .
- Ma, J., Abdelaal, A., Zhang, H., Zhou, A., Fu, Y. and Xie, Y.M. (2024a), "Ultra-compressed earth block stabilized by bio-binder for sustainable building construction", *Case Studies in Construction Materials*, Vol. 21, p. e03523.
- Ma, J., Zhang, H., Shobeiri, V., Zhong, Y., Zhang, J., Bai, Y., Robert, D. and Xie, Y.M. (2025), "CFRP-confined rammed earth towards high-performance earth construction", *Composite Structures*, Vol. 371, p. 119512.
- Madlool, N.A., Saidur, R., Hossain, M.S. and Rahim, N.A. (2011), "A critical review on energy use and savings in the cement industries", *Renewable and Sustainable Energy Reviews*, Vol. 15 No. 4, pp. 2042-2060.
- Maniatis, V. and Walker, P. (2008), "Structural capacity of rammed earth in compression", *J. Mater. Civ. Eng.*, Vol. 20 No. 3, pp. 230-238.
- Minke, G. (2006), *Building with Earth: Design and Technology of a Sustainable Architecture*, Birkhäuser, Basel.
- Morel, J.C., Pkla, A. and Walker, P. (2007), "Compressive strength testing of compressed earth blocks", *Constr. Build. Mater.*, Vol. 21 No. 2, pp. 303-309.
- Niroumand, H., Akbari, R., Khanlari, K., Gültekin, A.B. and Barcelo, J.A. (2021), "A systematic literature review of rammed earth walls", *Soil Mechanics and Foundation Engineering*, Vol. 58 No. 4, pp. 295-301.
- Paio, A. (2013), "Digital tectonic: rethinking the building with earth in architecture", *Archit. Res.*, Vol. 3 No. 2, pp. 33-44.
- Pan, W. (2012), "Prefabrication and automation in rammed earth building construction", *Proceedings of the CIB IAARC W119*, 57-61, Munich, available at: www.irbnet.de/daten/iconda/CIB_DC25191.pdf (accessed 10 August 2025).

- Preciado, A. and Santos, J.C. (2020), "Rammed earth sustainability and durability in seismic areas as a building material", *IOP Conf. Ser.: Earth Environ. Sci.*, Vol. 410 No. 1, p. 012108.
- Scrivener, K.L., John, V.M. and Gartner, E.M. (2018), "Eco-efficient cements: Potential economically viable solutions for a low-CO₂ cement-based materials industry", *Cement and Concrete Research*, Vol. 114, pp. 2-26.
- Shobeiri, V., Bennett, B., Xie, T. and Visintin, P. (2023), "Mix design optimization of concrete containing fly ash and slag for global warming potential and cost reduction", *Case Studies in Construction Materials*, Vol. 18, pp. e01832.
- Stuart, M. (2017), *The Future of Australian Energy Generation*, Institution of Engineers Australia, Australian Capital Territory, Australia.
- Subramanya, K., Kermanshachi, S. and Rouhanizadeh, B. (2020), "Modular construction vs. traditional construction: advantages and limitations: a comparative study", *Creative Construction e-Conference 2020 12*.
- Tripura, D.D. and Singh, K.D. (2019), "Axial load-capacity of bamboo-steel reinforced cement stabilised rammed earth columns", *Structural Engineering International*, Vol. 29 No. 1, pp. 133-143.
- Tripura, D.D., Gupta, S., Debbarma, B. and Deep, R.S.S. (2020), "Flexural strength and failure trend of bamboo and coir reinforced cement stabilized rammed earth wallettes", *Construction and Building Materials*, Vol. 242, p. 117986.
- Walker, P., Keable, R., Martin, J. and Maniatidis, V. (2005), *Rammed Earth: Design and Construction Guidelines*, BRE Bookshop.
- Willmann, J., Augugliaro, F., Cadalbert, T., D'Andrea, R., Gramazio, F. and Kohler, M. (2012), "Aerial robotic construction towards a new field of architectural research", *International Journal of Architectural Computing*, Vol. 10 No. 3, pp. 439-459.
- Woolley, T. (2006), *Natural Building: A Guide to Materials and Techniques*, Crowood Press, Ramsbury.
- Worrell, E., Galitsky, C. and Price, L. (2008), "Energy efficiency improvement and cost saving opportunities for cement making", LBNL-54036-Revision. *Ernest Orlando Lawrence Berkeley National Laboratory, University of CA, Berkeley*, available at: www.energystar.gov/sites/default/files/buildings/tools/LBNL-54036.pdf (accessed 10 August 2025).
- Wu, X., Yue, T., Geoffrey Qiping, S., Zhang, Z. and Qiong, W. (2024), "Measuring and reducing the embodied carbon in high-rise buildings through innovative modular construction", *Proceedings of the International Conference on Construction Engineering and Project Management*, 41-48. *Korea Institute of Construction Engineering and Management, Sapporo*.
- Xie, L., Wang, D., Zhao, H., Gao, J. and Gallo, T. (2021), "Architectural energetics for rammed-earth compaction in the context of Neolithic to early bronze age urban sites in middle yellow river valley, China", *Journal of Archaeological Science*, Vol. 126, p. 105303.
- Xie, Y., Wang, H., Guo, Y., Wang, C., Cui, H. and Xue, J. (2024), "Mechanical performance and water resistance of biochar admixture lightweight magnesium oxychloride cement", *Science of The Total Environment*, Vol. 912, p. 168773.
- Zhang, L., Zhou, T., Hu, K., Tan, W. and Liang, Z. (2024), "Seismic performance of rammed earth walls with embedded steel wire mesh or bamboo reinforcement mesh", *Structures*, Vol. 65, p. 106667.
- Zhang, C., Tian, H., Chen, G., Chappelka, A., Xu, X., Ren, W., Hui, D., Liu, M., Lu, C. and Pan, S. (2012), "Impacts of urbanization on carbon balance in terrestrial ecosystems of the Southern United States", *Environmental Pollution*, Vol. 164, pp. 89-101.

Further reading

- Amaral Rocha, R. and Melo de Oliveira, P.H. (2019), "The stabilized rammed earth building technique and its use in Australia", in Reddy, B.V.V., Mani, M., Walker, P. (Eds) *Proceedings of the International Conference on Construction Engineering and Project Management* *Proceedings of the International Conference on Construction Engineering and Project Management* *Proceedings of the International Conference on Construction Engineering and Project Management*

of the International Conference on Construction Engineering and Project Management Proceedings of the International Conference on Construction Engineering and Project Management), *Earthen Dwellings and Structures: Current Status in Their Adoption*, Springer, Singapore, pp. 81-92.

AS 3700-2018 (2018), *Masonry Structures*, Standards Australia, Sydney.

ASTM C1585-20 (2013), *Standard Test Method for Measurement of Rate of Absorption of Water by Hydraulic-Cement Concretes*, ASTM International, West Conshohocken.

Hall, M. and Djerbib, Y. (2004), "Rammed earth sample production: context, recommendations and consistency", *Construction and Building Materials*, Vol. 18 No. 4, pp. 281-286.

Hall, M. and Djerbib, Y. (2006), "Moisture ingress in rammed earth: part 2 – the effect of soil particle-size distribution on the absorption of static pressure-driven water", *Construction and Building Materials*, Vol. 20 No. 6, pp. 374-383.

Miccoli, L., Müller, U. and Fontana, P. (2014), "Mechanical behaviour of earthen materials: a comparison between earth block masonry, rammed earth and cob", *Construction and Building Materials*, Vol. 61, pp. 327-339.

Morel, J.C., Charef, R., Hamard, E., Fabbri, A., Beckett, C. and Bui, Q.B. (2021), "Earth as construction material in the circular economy context: practitioner perspectives on barriers to overcome", *Philos. Trans. R. Soc. B*, Vol. 376 No. 1834, p. 20200182.

Corresponding author

Yi Min Xie can be contacted at: mike.xie@rmit.edu.au