

Correspondence from G. M. Peck

p. 76, line 21: should read $\frac{S_1 - S_0}{S_0} \simeq 0.10 \log_{10} \left(\frac{\text{strain rate}}{\text{standard strain rate}} \right)$

p. 77, line 5: '0.030 in./min.' should read '0.30 in./min.'

line 6: should read $\log_{10} \left(\frac{\text{pen. rate}}{\text{slowest pen. rate}} \right) |0|0.699|1.398|$

2nd line after table should read $\frac{S_1 - S_0}{S_0} \simeq 0.157 \log_{10} \left(\frac{\text{pen. rate}}{\text{slowest pen. rate}} \right)$

4th line after table should read $\simeq 0.157 \times \log_{10} 394 = 40.7\%$

5th line after table should read $N_c = 18/1.407 = 12.8$

7th line after table should read $\frac{S_1 - S_0}{S_0} \simeq 0.0966 \times \log_{10} \left(\frac{\text{pen. rate}}{\text{slowest pen. rate}} \right)$

8th line after table should read $N_c \text{ corrected} = 14.4$

September 1966

A note on the constant head test to measure soil permeability in situ. R. E. Gibson

p. 258: second sentence of 'Conclusions' should read, 'Consequently for $k_1/k_3=0.1, 1, 10$ the corresponding values of λ are 0.05, 0.5, 5, the first . . .'