

# INDEX TO GÉOTECHNIQUE VOLUME LI

February, March, April, May, June, August, September, October, November, December 2001  
 No. 1, 1–93; No. 2, 95–193, No. 3, 195–291; No. 4, 293–387; No. 5, 389–482; No. 6, 483–576; No. 7, 577–654; No. 8, 655–732;  
 No. 9, 733–826; No. 10, 827–920

## AUTHOR INDEX

- Abbiss C. P.**  
 Deformation of landfill from measurements of shear wave velocity and damping, 483–492
- Akagi H., Jafari M. R., Bolton M. D., Komiya K. & Soga K.**  
 Soil consolidation associated with grouting during shield tunnelling in soft clayey ground, 835–846
- Algin H. M.**  
 Technical note: Vertical stress formula for pressure over rectangular areas, 719–722
- Alonso E. E. & Navarro V.**  
 Secondary compression of clays as a local dehydration process, 859–869
- Alonso E. E. & Oldecop L. A.**  
 A model for rockfill compressibility, 127–139
- Alonso E. E., Gens A. & Lloret A.**  
 Discussion: Precompression design for secondary settlement reduction, 822–826
- Ashmawy A. K. & Sukumaran B.**  
 Quantitative characterisation of the geometry of discrete particles, 619–627
- Bardet J. P. & Iai S.**  
 Plane strain instability of saturated elasto-plastic soils, 389–398
- Berrill J. B., Christensen S. A., Keenan R. P., Okada W. & Pettinga J. R.**  
 Case study of lateral spreading forces on a piled foundation, 501–517
- Blewett J., McCarter W. J., Chrisp T. M. & Starrs G.**  
 Technical note: Monitoring sedimentation of a clay slurry, 723–728
- Boardman D. I., Glendinning S. & Rogers C. D. F.**  
 Development of stabilisation and solidification in lime–clay mixes, 533–543
- Bolton M. D., Komiya K., Soga K., Akagi H. & Jafari M. R.**  
 Soil consolidation associated with grouting during shield tunnelling in soft clayey ground, 835–846
- Bowman E. T., Soga K. & Drummond W.**  
 Particle shape characterisation using Fourier descriptor analysis, 545–554
- Brucy F., Chow F. C., Jardine R. J. & Nauroy J. F.**  
 Discussion: Time-related increases in the shaft capacities of driven piles in sand, 475–476
- Burland J. B. & Georgiannou V. N.**  
 A laboratory study of post-rupture strength, 665–675
- Burton C. L., Waltham A. C. & McLaren S. J.**  
 Technical note: Strength variation in young reef limestones, 887–889
- Butterfield R.**  
 Discussion: Dimensional analysis for geotechnical engineers, 91–93
- Byrne B. W. & Houlsby G. T.**  
 Technical note: Observations of footing behaviour on loose carbonate sands, 463–466
- Cafaro F. & Cotecchia F.**  
 Structure degradation and changes in the mechanical behaviour of a stiff clay due to weathering, 441–453
- Cao L. F., Chang M. F. & Teh C. I.**  
 Undrained cavity expansion in modified Cam clay II: Application to the interpretation of the piezocone test, 335–350
- Cao L. F., Teh C. I. & Chang M. F.**  
 Undrained cavity expansion in modified Cam clay I: Theoretical analysis, 323–334
- Cardosa A. S. & Fernandes M. M.**  
 Characteristic values of ground parameters and probability of failure in design according to Eurocode 7, 519–531
- Carrara L., Velde B., Dudoignon P. & Pantet A.**  
 Macro–micro measurement of particle arrangement in sheared kaolinitic matrices, 493–499
- Cerasi P. & Soga K.**  
 Failure models of drilling fluid filter cake, 777–785
- Chang M. F., Cao L. F. & Teh C. I.**  
 Undrained cavity expansion in modified Cam clay I: Theoretical analysis, 323–334
- Chang M. F., Teh C. I. & Cao L. F.**  
 Undrained cavity expansion in modified Cam clay II: Application to the interpretation of the piezocone test, 335–350
- Chow F. C., Jardine R. J., Nauroy J. F. & Brucy F.**  
 Discussion: Time-related increases in the shaft capacities of driven piles in sand, 475–476
- Chrisp T. M., Starrs G., Blewett J. & McCarter W. J.**  
 Technical note: Monitoring sedimentation of a clay slurry, 723–728
- Christensen S. A., Keenan R. P., Okada W., Pettinga J. R. & Berrill J. B.**  
 Case study of lateral spreading forces on a piled foundation, 501–517
- Christopher R. A., Juang C. H. & Jiang T.**  
 Three-dimensional site characteristics: neural network approach, 799–809
- Chu J. & Leong W. K.**  
 Pre-failure strain softening and pre-failure instability of sand: a comparative study, 311–321
- Clayton C. R. I. & Heymann G.**  
 Stiffness of geomaterials at very small strains, 245–255
- Coop M. R. & Klotz E. U.**  
 An investigation of the effect of soil state on the capacity of driven piles in sands, 733–751
- Cotecchia F. & Cafaro F.**  
 Structure degradation and changes in the mechanical behaviour of a stiff clay due to weathering, 441–453
- Cousens T. W., Stewart D. I. & Tay Y. Y.**  
 The strength of unsaturated bentonite-enhanced sand, 767–775
- Cravero S., Harrison J. P. & Ferrero A. M.**  
 Fuzzy partitioning algorithms applied to the interpretation of distinct element modelling results, 677–686
- Crespellani T., Madiati C. & Vannuchi G.**  
 Discussion: Earthquake destructiveness potential factor and slope stability, 281–284
- Cresswell A.**  
 Technical note: Block sampling and test sample preparation of locked sands, 567–570
- Croce P. & Flora A.**  
 Analysis of single-fluid jet grouting, 905–906
- Cuéllar V. & Olalla C.**  
 Failure mechanism of the Aznalcóllar Dam, Seville, Spain, 399–406
- Dafalias Y. F. & Li X. S.**  
 Discussion: Dilatancy for cohesionless soils, 729–730
- Daniell C. M. & McDowell G. R.**  
 Technical note: Fractal compression of soil, 173–176
- Day R. A.**  
 Discussion: Net pressure analysis of cantilever sheet pile walls, 185–187
- Dean E. T. R.**  
 New descriptions of plane strain, 15–36
- de Boer R.**  
 Technical note: Uplift, friction, capillarity and effective stress: revisited via the porous media theory, 811–814
- Doran I. G., Sivakumar V., Graham J. & Johnson A.**  
 Discussion: Estimation of *in situ* stresses using anisotropic elasticity and suction measurements, 383–384
- Drummond W., Bowman E. T. & Soga K.**  
 Particle shape characterisation using Fourier descriptor analysis, 545–554
- Dudoignon P., Pantet A., Carrara L. & Velde B.**  
 Macro–micro measurement of particle arrangement in sheared kaolinitic matrices, 493–499
- Ellis E. A. & Springman S. M.**  
 Full-height piled bridge abutments constructed on soft clay, 3–14
- Fakher A., Jones C. J. F. P. & Shahgholi M.**  
 Technical note: Horizontal slice method of analysis, 881–885
- Feng T. W.**  
 Discussion: Fall-cone penetration and water content relationships of clays, 819–821
- Fenton G. A. & Griffiths D. V.**  
 Bearing capacity of spatially random soil: the undrained clay Prandtl problem revisited, 351–359
- Fernandes M. M. & Cardosa A. S.**  
 Characteristic values of ground parameters and probability of failure in design according to Eurocode 7, 519–531

- Ferrero A. M., Cravero S. & Harrison J. P.**  
Fuzzy partitioning algorithms applied to the interpretation of distinct element modelling results, 677–686
- Flora A. & Croce P.**  
Analysis of single-fluid jet grouting, 905–906
- Fourie A. B., Hofmann B. A., Mikula R. J., Lord E. R. F. & Robertson P. K.**  
Partially saturated tailings sand below the phreatic surface, 577–585
- Fredlund D. G., Pufahl D. E. & Vanapalli S. K.**  
Discussion: Influence of soil structure and stress history on the soil—water characteristics of a compacted till, 573–576
- Gazetas G., Tazoh T., Nikolaou S. & Mylonakis G.**  
Kinematic pile bending during earthquakes: analysis and field measurements, 425–440
- Gens A., Lloret A. & Alonso E. E.**  
Discussion: Precompression design for secondary settlement reduction, 822–826
- Georgiannou V. N. & Burland J. B.**  
A laboratory study of post-rupture strength, 665–675
- Germaine J. T., Varney A., Whittle A. J. & Sutabutr T.**  
Prediction and interpretation of pore pressure dissipation for a tapered piezoprobe, 601–617
- Glendinning S., Rogers C. D. F. & Boardman D. I.**  
Development of stabilisation and solidification in lime—clay mixes, 533–543
- Gonzalez R. & Sills G. C.**  
Consolidation of naturally gassy soft soil, 629–639
- Graham J., Johnson A., Doran I. G. & Sivakumar V.**  
Discussion: Estimation of *in situ* stresses using anisotropic elasticity and suction measurements, 383–384
- Greening P. D. & Lings M. L.**  
Technical note: A novel bender/extender element for soil testing, 713–717
- Griffiths D. V. & Fenton G. A.**  
Bearing capacity of spatially random soil: the undrained clay Prandtl problem revisited, 351–359
- Griffiths D. V. & Lane P. A.**  
Slope stability analysis by finite elements, 653–654
- Hansbo S.**  
Consolidation equation valid for both Darcian and non-Darcian flow, 51–54
- Harrison J. P., Ferrero A. M. & Cravero S.**  
Fuzzy partitioning algorithms applied to the interpretation of distinct element modelling results, 677–686
- Heymann G. & Clayton C. R. I.**  
Stiffness of geomaterials at very small strains, 245–255
- Hofmann B. A., Mikula R. J., Lord E. R. F., Robertson P. K. & Fourie A. B.**  
Partially saturated tailings sand below the phreatic surface, 577–585
- Holzöhner U.**  
Strip loads on a non-linear heterogeneous half-space, 655–664
- Houlsby G. T. & Byrne B. W.**  
Technical note: Observations of footing behaviour on loose carbonate sands, 463–466
- Houlsby G. T. & Koumoto T.**  
Theory and practice of the fall cone test, 701–712
- Houlsby G. T. & Martin C. M.**  
Combined loading of spudcan foundations on clay: numerical modelling, 677–686
- Houlsby G. T. & Puzrin A. M.**  
Technical note: On the non-intersection dilemma in multiple surface plasticity, 369–372
- Houlsby G. T. & Puzrin A. M.**  
Technical note: Strain-based plasticity models for soils and the BRICK model as an example of the hyperplasticity approach, 169–172
- Hu W., Nash D. F. T. & Muir-Wood D.**  
Discussion: Group effects in stone column foundations: model tests, 649
- Hyde A. F. L., Hyodo M., Murata H. & Nakata Y.**  
Discussion: A probabilistic approach to sand particle crushing in the triaxial test, 285–287
- Hyodo M., Murata H., Nakata Y. & Hyde A. F. L.**  
Discussion: A probabilistic approach to sand particle crushing in the triaxial test, 285–287
- Iai S. & Bardet J. P.**  
Plane strain instability of saturated elasto-plastic soils, 389–398
- Jafari M. R., Bolton M. D., Komiya K., Soga K. & Akagi H.**  
Soil consolidation associated with grouting during shield tunnelling in soft clayey ground, 835–846
- Jardine R. J. & Zdravković L.**  
The effect on anisotropy of rotating the principal stress axes during consolidation, 69–83
- Jardine R. J., Nauroy J. F., Brucy F. & Chow F. C.**  
Discussion: Time-related increases in the shaft capacities of driven piles in sand, 475–476
- Jardine R. J., Zdravković L. & Potts D. M.**  
A parametric study of the pull-out capacity of bucket foundations in soft clay, 55–67
- Jiang T., Christopher R. A. & Juang C. H.**  
Three-dimensional site characteristics: neural network approach, 799–809
- Johnson A., Doran I. G., Sivakumar V. & Graham J.**  
Discussion: Estimation of *in situ* stresses using anisotropic elasticity and suction measurements, 383–384
- Jones C. J. F. P., Shahgholi M. & Fakher A.**  
Technical note: Horizontal slice method of analysis, 881–885
- Juang C. H., Jiang T. & Christopher R. A.**  
Three-dimensional site characteristics: neural network approach, 799–809
- Kabbaz M. H. & Khalili N.**  
Discussion: A unique relationship for  $\chi$  for the determination of the shear strength of unsaturated soils, 477–478
- Keenan R. P., Okada W., Pettinga J. R., Berrill J. B. & Christensen S. A.**  
Case study of lateral spreading forces on a piled foundation, 501–517
- Khalili N. & Kabbaz M. H.**  
Discussion: A unique relationship for  $\chi$  for the determination of the shear strength of unsaturated soils, 477–478
- Klotz E. U. & Coop M. R.**  
An investigation of the effect of soil state on the capacity of driven piles in sands, 733–751
- Komiya K., Soga K., Akagi H., Jafari M. R. & Bolton M. D.**  
Soil consolidation associated with grouting during shield tunnelling in soft clayey ground, 835–846
- Konrad J.-M.**  
Discussion: Sand state from cone penetrometer tests: a framework considering grain crushing stress, 651–652
- Koumoto T. & Houlsby G. T.**  
Theory and practice of the fall cone test, 701–712
- Kumar J.**  
Technical note: Seismic vertical uplift capacity of strip anchors, 275–279
- Lane P. A. & Griffiths D. V.**  
Slope stability analysis by finite elements, 653–654
- Latham J.-P., Lu Y. & Munjiza A.**  
A random method for simulating loose packs of angular particles using tetrahedra, 871–879
- Lee C. F., Zhu D.-Y. & Qian Q.-H.**  
Active and passive critical slip fields for cohesionless soils and calculation of lateral earth pressures, 407–423
- Leelaratanam V. & Wesley L. D.**  
Technical note: Shear strength parameters from back-analysis of single slips, 373–374
- Leong W. K. & Chu J.**  
Pre-failure strain softening and pre-failure instability of sand: a comparative study, 311–321
- Leroueil S.**  
39th Rankin Lecture: Natural slopes and cuts: movement and failure mechanisms, 195–243
- Li X. S. & Dafalias Y. F.**  
Discussion: Dilatancy for cohesionless soils, 729–730
- Lings M. L.**  
Drained and undrained anisotropic elastic stiffness parameters, 555–565
- Lings M. L. & Greening P. D.**  
Technical note: A novel bender/extender element for soil testing, 713–717
- Lloret A., Alonso E. E. & Gens A.**  
Discussion: Precompression design for secondary settlement reduction, 822–826
- Long M. M. & O’Riordan N. J.**  
Field behaviour of very soft clays at the Athlone embankments, 293–309
- Lord E. R. F., Robertson P. K., Fourie A. B., Hofmann B. A. & Mikula R. J.**  
Partially saturated tailings sand below the phreatic surface, 577–585

- Lu Y., Munjiza A. & Latham J.-P.**  
A random method for simulating loose packs of angular particles using tetrahedra, 871–879
- Lukkunaprasit P., Teachavorasinskun S. & Thongchim P.**  
Technical note: Shear modulus and damping ratio of a clay during undrained cyclic loading, 467–470
- Madiari C., Vannuchi G. & Crespellani T.**  
Discussion: Earthquake destructiveness potential factor and slope stability, 281–284
- Maranha J. R., Maranhã das Neves E., Viega Pinto A. A. & Naylor D. J.**  
Discussion: A back-analysis of Beliche Dam, 377–381
- Maranhã das Neves E., Viega Pinto A. A., Naylor D. J. & Maranhã J. R.**  
Discussion: A back-analysis of Beliche Dam, 377–381
- Martin C. M. & Houlsby G. T.**  
Combined loading of spudcan foundations on clay: numerical modelling, 677–686
- McCarter W. J., Chrisp T. M., Starrs G. & Blewett J.**  
Technical note: Monitoring sedimentation of a clay slurry, 723–728
- McDowell G. R.**  
Technical note: Statistics of soil particle strength, 897–900
- McDowell G. R. & Daniell C. M.**  
Technical note: Fractal compression of soil, 173–176
- McLaren S. J., Burton C. L. & Waltham A. C.**  
Technical note: Strength variation in young reef limestones, 887–889
- Merifield R. S., Sloan S. W. & Yu H. S.**  
Discussion: Rigorous plasticity solutions for the bearing capacity of two-layered clays, 179–183
- Merifield R. S., Sloan S. W. & Yu H. S.**  
Stability of plate anchors in undrained clay, 141–153
- Mesri G.**  
Technical note: Undrained shear strength of soft clays from push cone penetration test, 167–168
- Michalowski R. L.**  
Upper-bound load estimates on square and rectangular footings, 787–798
- Mikula R. J., Lord E. R. F., Robertson P. K., Fourie A. B. & Hofmann B. A.**  
Partially saturated tailings sand below the phreatic surface, 577–585
- Mitchell J. K., Nakagawa K. & Soga K.**  
Discussion: Observation of Biot compressional wave of the second kind in granular soils, 85–89
- Miyamoto J., Sassa S. & Sekiguchi H.**  
Analysis of progressive liquefaction as a moving-boundary problem, 847–857
- Molenkamp F.**  
Evaluation of axial shear test using plane strain simulations, 37–49
- Muir-Wood D., Hu W. & Nash D. F. T.**  
Discussion: Group effects in stone column foundations: model tests, 649
- Munjiza A., Latham J.-P. & Lu Y.**  
A random method for simulating loose packs of angular particles using tetrahedra, 871–879
- Murata H., Nakata Y., Hyde A. F. L. & Hyodo M.**  
Discussion: A probabilistic approach to sand particle crushing in the triaxial test, 285–287
- Mylonakis G.**  
Winkler modulus for axially loaded piles, 455–461
- Mylonakis G., Gazetas G., Tazoh T. & Nikolaou S.**  
Kinematic pile bending during earthquakes: analysis and field measurements, 425–440
- Nakagawa K., Soga K. & Mitchell J. K.**  
Discussion: Observation of Biot compressional wave of the second kind in granular soils, 85–89
- Nakata Y., Hyde A. F. L., Hyodo M. & Murata H.**  
Discussion: A probabilistic approach to sand particle crushing in the triaxial test, 285–287
- Nash D. F. T. & Ryde S. J.**  
Modelling consolidation accelerated by vertical drains in soils subject to creep, 257–273
- Nash D. F. T., Muir-Wood D. & Hu W.**  
Discussion: Group effects in stone column foundations: model tests, 649
- Nauroy J. F., Bruy F., Chow F. C. & Jardine R. J.**  
Discussion: Time-related increases in the shaft capacities of driven piles in sand, 475–476
- Navarro V. & Alonso E. E.**  
Secondary compression of clays as a local dehydration process, 859–869
- Naylor D. J., Maranhã J. R., Maranhã das Neves E. & Viega Pinto A. A.**  
Discussion: A back-analysis of Beliche Dam, 377–381
- Nemat-Nasser S. & Okada N.**  
Radiographic and microscopic observation of shear bands in granular materials, 753–765
- Nikolaou S., Mylonakis G., Gazetas G. & Tazoh T.**  
Kinematic pile bending during earthquakes: analysis and field measurements, 425–440
- Okada N. & Nemat-Nasser S.**  
Radiographic and microscopic observation of shear bands in granular materials, 753–765
- Okada W., Pettinga J. R., Berrill J. B., Christensen S. A. & Keenan R. P.**  
Case study of lateral spreading forces on a piled foundation, 501–517
- Olalla C. & Cuéllar V.**  
Failure mechanism of the Aznalcóllar Dam, Seville, Spain, 399–406
- Oldecop L. A. & Alonso E. E.**  
A model for rockfill compressibility, 127–139
- O’Riordan N. J. & Long M. M.**  
Field behaviour of very soft clays at the Athlone embankments, 293–309
- Pan Y.-W. & Wen B.-H.**  
Technical note: Constitutive model for the continuous drainage of brittle rock, 155–159
- Pane V. & Schiffman R. L.**  
Discussion: The permeability of clay suspensions, 375–376
- Pantelidou H., Stallebrass S. E. & Powrie W.**  
Discussion: Soil stiffness in stress paths relevant to diaphragm walls in clay, 177–178
- Pantet A., Carrara L., Velde B. & Dudoignon P.**  
Macro—micro measurement of particle arrangement in sheared kaolinitic matrices, 493–499
- Pettinga J. R., Berrill J. B., Christensen S. A., Keenan R. P. & Okada W.**  
Case study of lateral spreading forces on a piled foundation, 501–517
- Potts D. M., Jardine R. J. & Zdravković L.**  
A parametric study of the pull-out capacity of bucket foundations in soft clay, 55–67
- Poulos H. G.**  
Piled raft foundations: design and applications, 95–113
- Powrie W., Pantelidou H. & Stallebrass S. E.**  
Discussion: Soil stiffness in stress paths relevant to diaphragm walls in clay, 177–178
- Pufahl D. E., Vanapalli S. K. & Fredlund D. G.**  
Discussion: Influence of soil structure and stress history on the soil—water characteristics of a compacted till, 573–576
- Puzrin A. M. & Houlsby G. T.**  
Technical note: On the non-intersection dilemma in multiple surface plasticity, 369–372
- Puzrin A. M. & Houlsby G. T.**  
Technical note: Strain-based plasticity models for soils and the BRICK model as an example of the hyperplasticity approach, 169–172
- Qian Q.-H., Lee C. F. & Zhu D.-Y.**  
Active and passive critical slip fields for cohesionless soils and calculation of lateral earth pressures, 407–423
- Ranzini S. M. T.**  
Technical note: Stabilisation of leaning structures: the Tower of Pisa case, 647–648
- Ratnam S., Soga K. & Whittle R. W.**  
Technical note: Revisiting Hvorslev’s intake factors using the finite element method, 641–645
- Robertson P. K., Fourie A. B., Hofmann B. A., Mikula R. J. & Lord E. R. F.**  
Partially saturated tailings sand below the phreatic surface, 577–585
- Rogers C. D. F., Boardman D. I. & Glendinning S.**  
Development of stabilisation and solidification in lime—clay mixes, 533–543
- Ryde S. J. & Nash D. F. T.**  
Modelling consolidation accelerated by vertical drains in soils subject to creep, 257–273
- Sassa K. & Wang G.**  
Factors affecting rainfall-induced flowslides in laboratory flume tests, 587–599
- Sassa S. & Sekiguchi H.**  
Analysis of wave-induced liquefaction of sand beds, 115–126
- Sassa S., Sekiguchi H. & Miyamoto J.**  
Analysis of progressive liquefaction as a moving-boundary problem, 847–857

- Sato T. & Yang J.**  
Technical note: Analytical study of saturation effects on seismic vertical amplification of a soil layer, 161–165
- Sawicki A.**  
Discussion: Theoretical analysis of centrifugal model tests on reinforced earth structures, 571–572
- Schiffman R. L. & Pane V.**  
Discussion: The permeability of clay suspensions., 375–376
- Sekiguchi H. & Sassa S.**  
Analysis of wave-induced liquefaction of sand beds, 115–126
- Sekiguchi H., Miyamoto J. & Sassa S.**  
Analysis of progressive liquefaction as a moving-boundary problem, 847–857
- Shahgholi M., Fagher A. & Jones C. J. F. P.**  
Technical note: Horizontal slice method of analysis, 881–885
- Sills G. C. & Gonzalez R.**  
Consolidation of naturally gassy soft soil, 629–639
- Simpson B.**  
Editorial, 1
- Simpson B. & Thomas H.**  
Editorial, 827
- Sivakumar V., Graham J., Johnson A. & Doran I. G.**  
Discussion: Estimation of *in situ* stresses using anisotropic elasticity and suction measurements, 383–384
- Sloan S. W., Yu H. S. & Merifield R. S.**  
Discussion: Rigorous plasticity solutions for the bearing capacity of two-layered clays, 179–183
- Sloan S. W., Yu H. S. & Merifield R. S.**  
Stability of plate anchors in undrained clay, 141–153
- Soga K. & Cerasi P.**  
Failure models of drilling fluid filter cake, 777–785
- Soga K., Akagi H., Jafari M. R., Bolton M. D. & Komiya K.**  
Soil consolidation associated with grouting during shield tunnelling in soft clayey ground, 835–846
- Soga K., Drummond W. & Bowman E. T.**  
Particle shape characterisation using Fourier descriptor analysis, 545–554
- Soga K., Mitchell J. K. & Nakagawa K.**  
Discussion: Observation of Biot compressional wave of the second kind in granular soils, 85–89
- Soga K., Whittle R. W. & Ratnam S.**  
Technical note: Revisiting Hvorslev's intake factors using the finite element method, 641–645
- Springman S. M. & Ellis E. A.**  
Full-height piled bridge abutments constructed on soft clay, 3–14
- Stallebrass S. E., Powrie W. & Pantelidou H.**  
Discussion: Soil stiffness in stress paths relevant to diaphragm walls in clay, 177–178
- Starrs G., Blewett J., McCarter W. J. & Chrisp T. M.**  
Technical note: Monitoring sedimentation of a clay slurry, 723–728
- Stewart D. I., Tay Y. Y. & Cousens T. W.**  
The strength of unsaturated bentonite-enhanced sand, 767–775
- Sukumaran B. & Ashmawy A. K.**  
Quantitative characterisation of the geometry of discrete particles, 619–627
- Sutabutr T., Germaine J. T., Varney A. & Whittle A. J.**  
Prediction and interpretation of pore pressure dissipation for a tapered piezoprobe, 601–617
- Tay Y. Y., Cousens T. W. & Stewart D. I.**  
The strength of unsaturated bentonite-enhanced sand, 767–775
- Tazoh T., Nikolaou S., Mylonakis G. & Gazetas G.**  
Kinematic pile bending during earthquakes: analysis and field measurements, 425–440
- Teachavorasinskun S., Thongchim P. & Lukkunaprasit P.**  
Technical note: Shear modulus and damping ratio of a clay during undrained cyclic loading, 467–470
- Teh C. I., Cao L. F. & Chang M. F.**  
Undrained cavity expansion in modified Cam clay II: Application to the interpretation of the piezocone test, 335–350
- Teh C. I., Chang M. F. & Cao L. F.**  
Undrained cavity expansion in modified Cam clay I: Theoretical analysis, 323–334
- Thomas H. & Simpson B.**  
Editorial, 827
- Thongchim P., Lukkunaprasit P. & Teachavorasinskun S.**  
Technical note: Shear modulus and damping ratio of a clay during undrained cyclic loading, 467–470
- Trenter N. A. & Warren C. D.**  
Discussion: Further investigations at the Folkestone Warren landslide, 189–192
- Triantafyllidis T.**  
Technical note: On the application of the Hiley formula in driving long piles, 891–895
- Vanapalli S. K., Fredlund D. G. & Pufahl D. E.**  
Discussion: Influence of soil structure and stress history on the soil–water characteristics of a compacted till, 573–576
- Vannuchi G., Crespellani T. & Madiati C.**  
Discussion: Earthquake destructiveness potential factor and slope stability, 281–284
- Varney A., Whittle A. J., Sutabutr T. & Germaine J. T.**  
Prediction and interpretation of pore pressure dissipation for a tapered piezoprobe, 601–617
- Velde B., Dudoignon P., Pantet A. & Carrara L.**  
Macro–micro measurement of particle arrangement in sheared kaolinitic matrices, 493–499
- Viega Pinto A. A., Naylor D. J., Maranha J. R. & Maranha das Neves E.**  
Discussion: A back-analysis of Beliche Dam, 377–381
- Waltham A. C., McLaren S. J. & Burton C. L.**  
Technical note: Strength variation in young reef limestones, 887–889
- Wang G. & Sassa K.**  
Factors affecting rainfall-induced flowslides in laboratory flume tests, 587–599
- Wang S. & Wu F.**  
Technical note: Strength theory of homogeneous jointed rock mass, 815–818
- Warren C. D. & Trenter N. A.**  
Discussion: Further investigations at the Folkestone Warren landslide, 189–192
- Wen B.-H. & Pan Y.-W.**  
Technical note: Constitutive model for the continuous drainage of brittle rock, 155–159
- Wesley L. D.**  
Technical note: Consolidation behaviour of allophone clays, 901–904
- Wesley L. D. & Leelaratanam V.**  
Technical note: Shear strength parameters from back-analysis of single slips, 373–374
- Whittle A. J., Sutabutr T., Germaine J. T. & Varney A.**  
Prediction and interpretation of pore pressure dissipation for a tapered piezoprobe, 601–617
- Whittle R. W., Ratnam S. & Soga K.**  
Technical note: Revisiting Hvorslev's intake factors using the finite element method, 641–645
- Wu F. & Wang S.**  
Technical note: Strength theory of homogeneous jointed rock mass, 815–818
- Yang J. & Sato T.**  
Technical note: Analytical study of saturation effects on seismic vertical amplification of a soil layer, 161–165
- Yin J.-H. & Zhu G.**  
Technical note: Consolidation of soil with vertical and horizontal drainage under ramp load, 361–367
- Yin J. H. & Zhu J.-G.**  
Technical note: Drained creep behaviour of soft Hong Kong marine deposits, 471–474
- Yu H. S., Merifield R. S. & Sloan S. W.**  
Discussion: Rigorous plasticity solutions for the bearing capacity of two-layered clays, 179–183
- Yu H. S., Merifield R. S. & Sloan S. W.**  
Stability of plate anchors in undrained clay, 141–153
- Zdravković L. & Jardine R. J.**  
The effect on anisotropy of rotating the principal stress axes during consolidation, 69–83
- Zdravković L., Potts D. M. & Jardine R. J.**  
A parametric study of the pull-out capacity of bucket foundations in soft clay, 55–67
- Zhu D.-Y., Qian Q.-H. & Lee C. F.**  
Active and passive critical slip fields for cohesionless soils and calculation of lateral earth pressures, 407–423
- Zhu G. & Yin J.-H.**  
Technical note: Consolidation of soil with vertical and horizontal drainage under ramp load, 361–367
- Zhu J.-G. & Yin J. H.**  
Technical note: Drained creep behaviour of soft Hong Kong marine deposits, 471–474

## SUBJECT INDEX

**Anchors**

Stability of plate anchors in undrained clay. Merifield R. S., Sloan S. W. & Yu H. S., 141–153

Technical note: Seismic vertical uplift capacity of strip anchors. Kumar J., 275–279

**Anisotropy**

Drained and undrained anisotropic elastic stiffness parameters. Lings M. L., 555–565

Evaluation of axial shear test using plane strain simulations. Molenkamp F., 37–49

New descriptions of plane strain. Dean E. T. R., 15–36

Technical note: Constitutive model for the continuous damage of brittle rock. Pan Y.-W. & Wen B.-H., 155–159

The effect on anisotropy of rotating the principal stress axes during consolidation. Zdravković L. & Jardine R. J., 69–83

**Bearing capacity**

Bearing capacity of spatially random soil: the undrained clay Prandtl problem revisited. Griffiths D. V. & Fenton G. A., 351–359

Characteristic values of ground parameters and probability of failure in design according to Eurocode 7. Cardoso A. S. & Fernandes M. M., 519–531

Combined loading of spudcan foundations on clay: numerical modelling. Martin C. M. & Houlsby G. T., 687–699

Discussion: Group effects in stone column foundations: model tests. Muir-Wood D., Hu W. & Nash D. F. T., 649

Discussion: Rigorous plasticity solutions for the bearing capacity of two-layered clays. Merifield R. S., Sloan S. W. & Yu H. S., 179–183

Discussion: Theoretical analysis of centrifugal model tests on reinforced earth structures. Sawicki A., 571–572

Strip loads on a non-linear heterogeneous half-space. Holzlöhner U., 655–664

Technical note: Observations of footing behaviour in loose carbonate sands. Byrne B. W. & Houlsby G. T., 463–466

Technical note: On the application of the Hiley formula in driving long piles. Triantafyllidis T., 891–895

Technical note: Strength variation in young reef limestones. Burton C. L., Waltham A. C. & McLaren S. J., 887–889

Upper bound load estimates on square and rectangular footings. Michalowski R. L., 787–798

**Calcareous soils**

Technical note: Fractal compression of soil. McDowell G. R. & Daniell C. M., 173–176

Technical note: Observations of footing behaviour in loose carbonate sands. Byrne B. W. & Houlsby G. T., 463–466

Technical note: Strength variation in young reef limestones. Burton C. L., Waltham A. C. & McLaren S. J., 887–889

**Case history**

Case study of lateral spreading forces on a piled foundation. Berrill J. B., Christensen S. A., Keenan R. P., Okada W. & Pettinga J. R., 501–517

Discussion: Precompression design for secondary settlement reduction. Alonso E. E., Gens A. & Lloret A., 822–826

Discussion: Time-related increases in the shaft capacities of driven piles in sand. Chow F. C., Jardine R. J., Nauroy J. F. & Bruzy F., 475–476

Failure mechanism of the Aznalcóllar Dam, Seville, Spain. Olalla C. & Cuéllar V., 399–406

Kinematic pile bending during earthquakes: analysis and field measurements. Nikolaou S., Mylonakis G., Gazetas G. & Tazoh T., 425–440

**Centrifuge modelling**

Analysis of progressive liquefaction as a moving-boundary problem. Sassa S., Sekiguchi H. & Miyamoto J., 847–857

Analysis of wave-induced liquefaction of sand beds. Sassa S. & Sekiguchi H., 115–126

An investigation of the effect of soil state on the capacity of driven piles in sands. Klotz E. U. & Coop M. R., 733–751

Discussion: Theoretical analysis of centrifugal model tests on reinforced earth structures. Sawicki A., 571–572

Full-height piled bridge abutments constructed on soft clay. Ellis E. A. & Springman S. M., 3–14

**Chalk**

Stiffness of geomaterials at very small strains. Clayton C. R. I. & Heymann G., 245–255

**Chemical properties**

Development of stabilisation and solidification on lime–clay mixes. Boardman D. I., Glendinning S. & Rogers C. D. F., 533–543

**Clays**

A laboratory study of post-rupture strength. Georgiannou V. N. & Burland J. B., 665–675

Discussion: Fall-cone penetration and water content relationships of clays. Feng T. W., 819–821

Discussion: Group effects in stone column foundations: model tests. Muir-Wood D., Hu W. & Nash D. F. T., 649

Discussion: Rigorous plasticity solutions for the bearing capacity of two-layered clays. Merifield R. S., Sloan S. W. & Yu H. S., 179–183

Discussion: Soil stiffness in stress paths relevant to diaphragm walls in clay. Powrie W., Pantelidou H. & Stallebrass S. E., 177–178

Discussion: The permeability of clay suspensions. Pane V. & Schiffman R. L., 375–376

Field behaviour of very soft clays at the Athlone embankments. Long M. M. & O’Riordan N. J., 293–309

Macro–micro measurement of particle arrangement in sheared kaolinitic matrices. Dudoignon P., Pantet A., Carrara L. & Velde B., 493–499

Modelling consolidation accelerated by vertical drains in soils subject to creep. Nash D. F. T. & Ryde S. J., 257–273

Prediction and interpretation of pore pressure dissipation for a tapered piezoprobe. Whittle A. J., Sutabutr T., Germaine J. T. & Varney A., 601–617

Secondary compression of clays as a local dehydration process. Navarro V. & Alonso E. E., 859–869

Soil consolidation associated with grouting during shield tunnelling in soft clayey ground. Komiya K., Soga K., Akagi H., Jafari M. R. & Bolton M. D., 835–846

Stability of plate anchors in undrained clay. Merifield R. S., Sloan S. W. & Yu H. S., 141–153

Stiffness of geomaterials at very small strains. Clayton C. R. I. & Heymann G., 245–255

Structure degradation and changes in the mechanical behaviour of a stiff clay due to weathering. Cafaro F. & Cotecchia F., 441–453

Technical note: Consolidation behaviour of allophone clays. Wesley L. D., 901–904

Technical note: Drained creep behaviour of soft Hong Kong marine deposits. Zhu J.-G. & Yin J.-H., 471–474

Technical note: Revisiting Hvorslev’s intake factors using the finite element method. Ratnam S., Soga K. & Whittle R. W., 641–645

Technical note: Shear modulus and damping ratio of a clay during undrained cyclic loading. Teachavorasinskun S., Thongchim P. & Lukkunaprasit P., 467–470

Technical note: Shear strength parameters from back-analysis of single slips. Wesley L. D. & Leelaratnam V., 373–374

Technical note: Undrained shear strength of soft clays from push cone penetration test. Mesri G., 167–168

Theory and practice of the fall cone test. Koumoto T. & Houlsby G. T., 701–712

Undrained cavity expansion in modified Cam clay I: Theoretical analysis. Cao L. F., Teh C. I. & Chang M. F., 323–334

Undrained cavity expansion in modified Cam clay II: Application to the interpretation of the piezocone test. Chang M. F., Teh C. I. & Cao L. F., 335–350

**Compaction**

A model for rockfill compressibility. Oldecop L. A. & Alonso E. E., 127–139

Discussion: Influence of soil structure and stress history on the soil–water characteristics of a compacted till. Vanapalli S. K., Fredlund D. G. & Pufahl D. E., 573–576

**Compressibility**

A model for rockfill compressibility. Oldecop L. A. & Alonso E. E., 127–139

Discussion: A probabilistic approach to sand particle crushing in the triaxial test. Nakata Y., Hyde A. F. L., Hyodo M. & Murata H., 285–287

Discussion: Precompression design for secondary settlement reduction. Alonso E. E., Gens A. & Lloret A., 822–826

Field behaviour of very soft clays at the Athlone embankments. Long M. M. & O’Riordan N. J., 293–309

Technical note: Fractal compression of soil. McDowell G. R. & Daniell C. M., 173–176

**Consolidation**

Consolidation equation valid for both Darcian and non-Darcian flow. Hansbo S., 51–54

Consolidation of naturally gassy soft soil. Silts G. C. & Gonzalez R., 629–639

Discussion: Precompression design for secondary settlement reduction. Alonso E. E., Gens A. & Lloret A., 822–826

Failure modes of drilling fluid filter cake. Cerasi P. & Soga K., 777–785

Macro–micro measurement of particle arrangement in sheared kaolinitic matrices. Dudoignon P., Pantet A., Carrara L. & Velde B., 493–499

- Modelling consolidation accelerated by vertical drains in soils subject to creep. Nash D. F. T. & Ryde S. J., 257–273
- Soil consolidation associated with grouting during shield tunnelling in soft clayey ground. Komiya K., Soga K., Akagi H., Jafari M. R. & Bolton M. D., 835–846
- Technical note: Consolidation behaviour of allophone clays. Wesley L. D., 901–904
- Technical note: Consolidation of soil with vertical and horizontal drainage under ramp load. Zhu G. & Yin J.-H., 361–367
- Constitutive relations**
- A model for rockfill compressibility. Oldecop L. A. & Alonso E. E., 127–139
- Analysis of wave-induced liquefaction of sand beds. Sassa S. & Sekiguchi H., 115–126
- Discussion: Dilatancy for cohesionless soils. Li X. S. & Dafalias Y. F., 729–730
- Evaluation of axial shear test using plane strain simulations. Molenkamp F., 37–49
- New descriptions of plane strain. Dean E. T. R., 15–36
- Plane strain instability of saturated elasto-plastic soils. Iai S. & Bardet J. P., 389–398
- Prediction and interpretation of pore pressure dissipation for a tapered piezoprobe. Whittle A. J., Sutabutr T., Germaine J. T. & Varney A., 601–617
- Strip loads on a non-linear heterogeneous half-space. Holzlöhner U., 655–664
- Technical note: Constitutive model for the continuous damage of brittle rock. Pan Y.-W. & Wen B.-H., 155–159
- Technical note: Uplift, friction, capillarity and effective stress: revisited via the porous media theory. de Boer R., 811–814
- Contaminated land**
- Development of stabilisation and solidification on lime–clay mixes. Boardman D. I., Glendinning S. & Rogers C. D. F., 533–543
- Creep**
- Modelling consolidation accelerated by vertical drains in soils subject to creep. Nash D. F. T. & Ryde S. J., 257–273
- Secondary compression of clays as a local dehydration process. Navarro V. & Alonso E. E., 859–869
- Technical note: Drained creep behaviour of soft Hong Kong marine deposits. Zhu J.-G. & Yin J.-H., 471–474
- Cut-off walls and barriers**
- The strength of unsaturated bentonite-enhanced sand. Stewart D. I., Tay Y. Y. & Cousens T. W., 767–775
- Dams**
- Discussion: A back-analysis of Beliche Dam. Naylor D. J., Maranha J. R., Maranha das Neves E. & Viegas Pinto A. A., 377–381
- Discussion: Further investigations at the Folkstone Warren landslide. Trenter N. A. & Warren C. D., 189–192
- Discussion: Slope stability analysis by finite elements. Griffiths D. V. & Lane P. A., 653–654
- Failure mechanism of the Aznalcóllar Dam, Seville, Spain. Olalla C. & Cuéllar V., 399–406
- Deformation**
- Deformation of landfill from measurements of shear wave velocity and damping. Abbiss C. P., 483–492
- Discussion: Soil stiffness in stress paths relevant to diaphragm walls in clay. Powrie W., Pantelidou H. & Stallebrass S. E., 177–178
- Failure modes of drilling fluid filter cake. Cerasi P. & Soga K., 777–785
- New descriptions of plane strain. Dean E. T. R., 15–36
- Technical note: Consolidation behaviour of allophone clays. Wesley L. D., 901–904
- Design**
- Discussion: Earthquake destructiveness: potential factor and slope stability. Crespellani T., Madiari C. & Vannucchi G., 281–284
- Discussion: Rigorous plasticity solutions for the bearing capacity of two-layered clays. Merifield R. S., Sloan S. W. & Yu H. S., 179–183
- Piled raft foundations: design and applications. Poulos H. G., 95–113
- Technical note: Horizontal slice method of analysis. Shahgholi M., Fakhri A. & Jones C. J. F. P., 881–885
- Diaphragm and in situ walls**
- Discussion: Soil stiffness in stress paths relevant to diaphragm walls in clay. Powrie W., Pantelidou H. & Stallebrass S. E., 177–178
- Drainage**
- Technical note: Consolidation of soil with vertical and horizontal drainage under ramp load. Zhu G. & Yin J.-H., 361–367
- Technical note: Revisiting Hvorslev's intake factors using the finite element method. Zhu G. & Yin J.-H., 361–367
- Technical note: Revisiting Hvorslev's intake factors using the finite element method. Ratnam S., Soga K. & Whittle R. W., 641–645
- Dynamics**
- Discussion: Observation of Biot compressional wave of the second kind in granular soils. Nakagawa K., Soga K. & Mitchell J. K., 85–89
- Kinematic pile bending during earthquakes: analysis and field measurements. Nikolaou S., Mylonakis G., Gazetas G. & Tazoh T., 425–440
- Technical note: Analytical study of saturation effects on seismic vertical amplification of a soil layer. Yang J. & Sato T., 161–165
- Technical note: A novel bender/extender element for soil testing. Lings M. L. & Greening P. D., 713–717
- Technical note: On the application of the Hiley formula in driving long piles. Triantafyllidis T., 891–895
- Winkler modulus for axially loaded piles. Mylonakis G., 455–461
- Earth pressure**
- Active and passive critical slip fields for cohesionless soils and calculation of lateral earth pressures. Zhu D.-Y., Qian Q.-H. & Lee C. F., 407–423
- Discussion: Net pressure analysis of cantilever sheet pile walls. Day R. A., 185–187
- Earthquakes**
- Case study of lateral spreading forces on a piled foundation. Berrill J. B., Christensen S. A., Keenan R. P., Okada W. & Pettinga J. R., 501–517
- Discussion: Earthquake destructiveness: potential factor and slope stability. Crespellani T., Madiari C. & Vannucchi G., 281–284
- Kinematic pile bending during earthquakes: analysis and field measurements. Nikolaou S., Mylonakis G., Gazetas G. & Tazoh T., 425–440
- Technical note: Analytical study of saturation effects on seismic vertical amplification of a soil layer. Yang J. & Sato T., 161–165
- Technical note: Seismic vertical uplift capacity of strip anchors. Kumar J., 275–279
- Elasticity**
- Deformation of landfill from measurements of shear wave velocity and damping. Abbiss C. P., 483–492
- Discussion: Estimation of *in situ* stresses using anisotropic elasticity and suction measurements. Doran I. G., Sivakumar V., Graham J. & Johnson A., 383–384
- Discussion: Observation of Biot compressional wave of the second kind in granular soils. Nakagawa K., Soga K. & Mitchell J. K., 85–89
- Drained and undrained anisotropic elastic stiffness parameters. Lings M. L., 555–565
- Failure modes of drilling fluid filter cake. Cerasi P. & Soga K., 777–785
- Strip loads on a non-linear heterogeneous half-space. Holzlöhner U., 655–664
- Winkler modulus for axially loaded piles. Mylonakis G., 455–461
- Embankments**
- Characteristic values of ground parameters and probability of failure in design according to Eurocode 7. Cardoso A. S. & Fernandes M. M., 519–531
- Discussion: A back-analysis of Beliche Dam. Naylor D. J., Maranha J. R., Maranha das Neves E. & Viegas Pinto A. A., 377–381
- Discussion: Further investigations at the Folkstone Warren landslide. Trenter N. A. & Warren C. D., 189–192
- Full-height piled bridge abutments constructed on soft clay. Ellis E. A. & Springman S. M., 3–14
- Modelling consolidation accelerated by vertical drains in soils subject to creep. Nash D. F. T. & Ryde S. J., 257–273
- The effect on anisotropy of rotating the principal stress axes during consolidation. Zdravković L. & Jardine R. J., 69–83
- Environmental engineering**
- Development of stabilisation and solidification on lime–clay mixes. Boardman D. I., Glendinning S. & Rogers C. D. F., 533–543
- Excavation**
- Natural slopes and cuts: movement and failure mechanisms. Leroueil S., 197–243
- Fabric/structure of soils**
- A laboratory study of post-rupture strength. Georgiannou V. N. & Burland J. B., 665–675
- A random method for simulating loose packs of angular particles using tetrahedra. Latham J.-P., Lu Y. & Munjiza A., 871–879
- Discussion: Influence of soil structure and stress history on the soil–water characteristics of a compacted till. Vanapalli S. K., Fredlund D. G. & Pufahl D. E., 573–576
- Macro–micro measurement of particle arrangement in sheared kaolinitic matrices. Dudoignon P., Pantet A., Carrara L. & Velde B., 493–499
- Particle shape characterisation using Fourier descriptor analysis. Bowman E. T., Soga K. & Drummond W., 545–554
- Secondary compression of clays as a local dehydration process. Navarro V. & Alonso E. E., 859–869
- Structure degradation and changes in the mechanical behaviour of a stiff clay due to weathering. Cafaro F. & Cotecchia F., 441–453

- Technical note: Block sampling and test sample preparation of locked sands. Cresswell A., 567–570
- Technical note: Monitoring sedimentation of a clay slurry. Blewett J., McCarter W. J., Chrisp T. M. & Starrs G., 723–728
- Failure**
- Active and passive critical slip fields for cohesionless soils and calculation of lateral earth pressures. Zhu D.-Y., Qian Q.-H. & Lee C. F., 407–423
- Discussion: Rigorous plasticity solutions for the bearing capacity of two-layered clays. Merifield R. S., Sloan S. W. & Yu H. S., 179–183
- Failure mechanism of the Aznalcóllar Dam, Seville, Spain. Olalla C. & Cuéllar V., 399–406
- Failure modes of drilling fluid filter cake. Cerasi P. & Soga K., 777–785
- Natural slopes and cuts: movement and failure mechanisms. Leroueil S., 197–243
- Pre-failure strain softening and pre-failure instability of sand: a comparative study. Chu J. & Leong W. K., 311–321
- Stability of plate anchors in undrained clay. Merifield R. S., Sloan S. W. & Yu H. S., 141–153
- Technical note: Shear strength parameters from back-analysis of single slips. Wesley L. D. & Leelaratanam V., 373–374
- Technical note: Strength theory of homogeneous jointed rock d clay. Merifield R. S., Sloan S. W. & Yu H. S., 141–153
- Technical note: Shear strength parameters from back-analysis of single slips. Wesley L. D. & Leelaratanam V., 373–374
- Technical note: Strength theory of homogeneous jointed rock mass. Wu F. & Wang S., 815–818
- Undrained cavity expansion in modified Cam clay II: Application to the interpretation of the piezocone test. Chang M. F., Teh C. I. & Cao L. F., 335–350
- Upper bound load estimates on square and rectangular footings. Michalowski R. L., 787–798
- Field instrumentation**
- Discussion: Precompression design for secondary settlement reduction. Alonso E. E., Gens A. & Lloret A., 822–826
- Technical note: Revisiting Hvorslev's intake factors using the finite element method. Ratnam S., Soga K. & Whittle R. W., 641–645
- Footings/foundations**
- A parametric study of the pull-out capacity of bucket foundations in soft clay. Zdravković L., Potts D. M. & Jardine R. J., 55–67
- Case study of lateral spreading forces on a piled foundation. Berrill J. B., Christensen S. A., Keenan R. P., Okada W. & Pettinga J. R., 501–517
- Characteristic values of ground parameters and probability of failure in design according to Eurocode 7. Cardoso A. S. & Fernandes M. M., 519–531
- Combined loading of spudcan foundations on clay: numerical modelling. Martin C. M. & Houlsby G. T., 687–699
- Discussion: Dimensional analysis for geotechnical engineers. Butterfield R., 91–93
- Discussion: Rigorous plasticity solutions for the bearing capacity of two-layered clays. Merifield R. S., Sloan S. W. & Yu H. S., 179–183
- Piled raft foundations: design and applications. Poulos H. G., 95–113
- Strip loads on a non-linear heterogeneous half-space. Holzlöhner U., 655–664
- Technical note: Observations of footing behaviour in loose carbonate sands. Byrne B. W. & Houlsby G. T., 463–466
- Technical note: Seismic vertical uplift capacity of strip anchors. Kumar J., 275–279
- Technical note: Stabilisation of leaning structures: the Tower of Pisa case. Ranzini S. M. T., 647–648
- Technical note: Vertical stress formula for pressure over rectangular areas. Algin H. M., 719–722
- Upper bound load estimates on square and rectangular footings. Michalowski R. L., 787–798
- Friction**
- Discussion: Time-related increases in the shaft capacities of driven piles in sand. Chow F. C., Jardine R. J., Nauroy J. F. & Brucy F., 475–476
- The strength of unsaturated bentonite-enhanced sand. Stewart D. I., Tay Y. Y. & Cousens T. W., 767–775
- Full-scale tests**
- Discussion: Time-related increases in the shaft capacities of driven piles in sand. Chow F. C., Jardine R. J., Nauroy J. F. & Brucy F., 475–476
- Geology**
- Technical note: Strength variation in young reef limestones. Burton C. L., Waltham A. C. & McLaren S. J., 887–889
- Gravels**
- A model for rockfill compressibility. Oldecop L. A. & Alonso E. E., 127–139
- A random method for simulating loose packs of angular particles using tetrahedra. Latham J.-P., Lu Y. & Munjiza A., 871–879
- Ground freezing**
- Partially saturated tailings sand below the phreatic surface. Fourie A. B., Hofmann B. A., Mikula R. J., Lord E. R. F. & Robertson P. K., 577–585
- Ground improvement**
- Development of stabilisation and solidification on lime—clay mixes. Boardman D. I., Glendinning S. & Rogers C. D. F., 533–543
- Discussion: Analysis of single-fluid jet grouting. Croce P. & Flora A., 905–906
- Discussion: Precompression design for secondary settlement reduction. Alonso E. E., Gens A. & Lloret A., 822–826
- Modelling consolidation accelerated by vertical drains in soils subject to creep. Nash D. F. T. & Ryde S. J., 257–273
- Ground movements**
- Case study of lateral spreading forces on a piled foundation. Berrill J. B., Christensen S. A., Keenan R. P., Okada W. & Pettinga J. R., 501–517
- Natural slopes and cuts: movement and failure mechanisms. Leroueil S., 197–243
- Grouting**
- Discussion: Analysis of single-fluid jet grouting. Croce P. & Flora A., 905–906
- Soil consolidation associated with grouting during shield tunnelling in soft clayey ground. Komiya K., Soga K., Akagi H., Jafari M. R. & Bolton M. D., 835–846
- In-situ testing**
- Discussion: Sand state from cone penetrometer tests: a framework considering grain crushing stress. Konrad J.-M., 651–652
- Prediction and interpretation of pore pressure dissipation for a tapered piezoprobe. Whittle A. J., Sutabutr T., Germaine J. T. & Varney A., 601–617
- Technical note: On the application of the Hiley formula in driving long piles. Triantafyllidis T., 891–895
- Technical note: Revisiting Hvorslev's intake factors using the finite element method. Ratnam S., Soga K. & Whittle R. W., 641–645
- Three-dimensional site characterisation: neural network approach. Juang C. H., Jiang T. & Christopher R. A., 799–809
- Undrained cavity expansion in modified Cam clay I: Theoretical analysis. Cao L. F., Teh C. I. & Chang M. F., 323–334
- Undrained cavity expansion in modified Cam clay II: Application to the interpretation of the piezocone test. Chang M. F., Teh C. I. & Cao L. F., 335–350
- Laboratory equipment**
- Technical note: A novel Bender/extender element for soil testing. Lings M. L. & Greening P. D., 713–717
- Laboratory tests**
- A laboratory study of post-rupture strength. Georgiannou V. N. & Burland J. B., 665–675
- A model for rockfill compressibility. Oldecop L. A. & Alonso E. E., 127–139
- Consolidation of naturally gassy soft soil. Sills G. C. & Gonzalez R., 629–639
- Discussion: Fall-cone penetration and water content relationships of clays. Feng T. W., 819–821
- Discussion: Observation of Biot compressional wave of the second kind in granular soils. Nakagawa K., Soga K. & Mitchell J. K., 85–89
- Discussion: Sand state from cone penetrometer tests: a framework considering grain crushing stress. Konrad J.-M., 651–652
- Discussion: The permeability of clay suspensions. Pane V. & Schiffman R. L., 375–376
- Evaluation of axial shear test using plane strain simulations. Molenkamp F., 37–49
- Factors affecting rainfall-induced flowslides in laboratory flume tests. Wang G. & Sassa K., 587–599
- Field behaviour of very soft clays at the Athlone embankments. Long M. M. & O'Riordan N. J., 293–309
- Macro—micro measurement of particle arrangement in sheared kaolinitic matrices. Dudoignon P., Pantet A., Carrara L. & Velde B., 493–499
- Pre-failure strain softening and pre-failure instability of sand: a comparative study. Chu J. & Leong W. K., 311–321
- Quantitative characterisation of the geometry of discrete particles. Sukumaran B. & Ashmawy A. K., 619–627
- Radiographic and microscopic observation of shear bands in granular materials. Nemat-Nasser S. & Okada N., 753–765
- Secondary compression of clays as a local dehydration process. Navarro V. & Alonso E. E., 859–869
- Soil consolidation associated with grouting during shield tunnelling in soft clayey ground. Komiya K., Soga K., Akagi H., Jafari M. R. & Bolton M. D., 835–846
- Technical note: Block sampling and test sample preparation of locked sands. Cresswell A., 567–570

- Technical note: Fractal compression of soil. McDowell G. R. & Daniell C. M., 173–176
- Technical note: Monitoring sedimentation of a clay slurry. Blewett J., McCarter W. J., Chrisp T. M. & Starrs G., 723–728
- Technical note: Shear modulus and damping ratio of a clay during undrained cyclic loading. Teachavorasinskun S., Thongchim P. & Lukkunaprasit P., 467–470
- Technical note: Statistics of soil particle strength. McDowell G. R., 897–900
- The effect on anisotropy of rotating the principal stress axes during consolidation. Zdravković L. & Jardine R. J., 69–83
- Theory and practice of the fall cone test. Koumoto T. & Houlsby G. T., 701–712
- The strength of unsaturated bentonite-enhanced sand. Stewart D. I., Tay Y. Y. & Cousens T. W., 767–775
- Landfills**
- Deformation of landfill from measurements of shear wave velocity and damping. Abbiss C. P., 483–492
- Landslides**
- Discussion: Earthquake destructiveness: potential factor and slope stability. Crespellani T., Madiari C. & Vannucchi G., 281–284
- Factors affecting rainfall-induced flowslides in laboratory flume tests. Wang G. & Sassa K., 587–599
- Natural slopes and cuts: movement and failure mechanisms. Leroueil S., 197–243
- Limit state design/analysis**
- Bearing capacity of spatially random soil: the undrained clay Prandtl problem revisited. Griffiths D. V. & Fenton G. A., 351–359
- Characteristic values of ground parameters and probability of failure in design according to Eurocode 7. Cardoso A. S. & Fernandes M. M., 519–531
- Technical note: Seismic vertical uplift capacity of strip anchors. Kumar J., 275–279
- Upper bound load estimates on square and rectangular footings. Michalowski R. L., 787–798
- Liquefaction**
- Analysis of progressive liquefaction as a moving-boundary problem. Sassa S., Sekiguchi H. & Miyamoto J., 847–857
- Analysis of wave-induced liquefaction of sand beds. Sassa S. & Sekiguchi H., 115–126
- Case study of lateral spreading forces on a piled foundation. Berrill J. B., Christensen S. A., Keenan R. P., Okada W. & Pettinga J. R., 501–517
- Factors affecting rainfall-induced flowslides in laboratory flume tests. Wang G. & Sassa K., 587–599
- Partially saturated tailings sand below the phreatic surface. Fourie A. B., Hofmann B. A., Mikula R. J., Lord E. R. F. & Robertson P. K., 577–585
- Plane strain instability of saturated elasto-plastic soils. Iai S. & Bardet J. P., 389–398
- Pre-failure strain softening and pre-failure instability of sand: a comparative study. Chu J. & Leong W. K., 311–321
- Radiographic and microscopic observation of shear bands in granular materials. Nemat-Nasser S. & Okada N., 753–765
- Microscopy**
- Discussion: A probabilistic approach to sand particle crushing in the triaxial test. Nakata Y., Hyde A. F. L., Hyodo M. & Murata H., 285–287
- Macro—micro measurement of particle arrangement in sheared kaolinitic matrices. Dudoignon P., Pantet A., Carrara L. & Velde B., 493–499
- Partially saturated tailings sand below the phreatic surface. Fourie A. B., Hofmann B. A., Mikula R. J., Lord E. R. F. & Robertson P. K., 577–585
- Particle shape characterisation using Fourier descriptor analysis. Bowman E. T., Soga K. & Drummond W., 545–554
- Quantitative characterisation of the geometry of discrete particles. Sukumaran B. & Ashmawy A. K., 619–627
- Radiographic and microscopic observation of shear bands in granular materials. Nemat-Nasser S. & Okada N., 753–765
- Mineralogy**
- Discussion: A probabilistic approach to sand particle crushing in the triaxial test. Nakata Y., Hyde A. F. L., Hyodo M. & Murata H., 285–287
- Technical note: Consolidation behaviour of allophone clays. Wesley L. D., 901–904
- Model tests**
- Discussion: Group effects in stone column foundations: model tests. Muir-Wood D., Hu W. & Nash D. F. T., 649
- Monitoring**
- Technical note: Monitoring sedimentation of a clay slurry. Blewett J., McCarter W. J., Chrisp T. M. & Starrs G., 723–728
- Numerical modelling and analysis**
- Active and passive critical slip fields for cohesionless soils and calculation of lateral earth pressures. Zhu D.-Y., Qian Q.-H. & Lee C. F., 407–423
- Analysis of wave-induced liquefaction of sand beds. Sassa S. & Sekiguchi H., 115–126
- A parametric study of the pull-out capacity of bucket foundations in soft clay. Zdravković L., Potts D. M. & Jardine R. J., 55–67
- A random method for simulating loose packs of angular particles using tetrahedra. Latham J.-P., Lu Y. & Munjiza A., 871–879
- Bearing capacity of spatially random soil: the undrained clay Prandtl problem revisited. Griffiths D. V. & Fenton G. A., 351–359
- Combined loading of spudcan foundations on clay: numerical modelling. Martin C. M. & Houlsby G. T., 687–699
- Discussion: Dimensional analysis for geotechnical engineers. Butterfield R., 91–93
- Discussion: Further investigations at the Folkstone Warren landslide. Trenter N. A. & Warren C. D., 189–192
- Discussion: Rigorous plasticity solutions for the bearing capacity of two-layered clays. Merifield R. S., Sloan S. W. & Yu H. S., 179–183
- Discussion: Slope stability analysis by finite elements. Griffiths D. V. & Lane P. A., 653–654
- Evaluation of axial shear test using plane strain simulations. Molenkamp F., 37–49
- Full-height piled bridge abutments constructed on soft clay. Ellis E. A. & Springman S. M., 3–14
- Fuzzy partitioning algorithms applied to the interpretation of distinct element modelling results. Harrison J. P., Ferrero A. M. & Cravero S., 677–686
- Kinematic pile bending during earthquakes: analysis and field measurements. Nikolaou S., Mylonakis G., Gazetas G. & Tazoh T., 425–440
- Modelling consolidation accelerated by vertical drains in soils subject to creep. Nash D. F. T. & Ryde S. J., 257–273
- New descriptions of plane strain. Dean E. T. R., 15–36
- Piled raft foundations: design and applications. Poulos H. G., 95–113
- Plane strain instability of saturated elasto-plastic soils. Iai S. & Bardet J. P., 389–398
- Soil consolidation associated with grouting during shield tunnelling in soft clayey ground. Komiya K., Soga K., Akagi H., Jafari M. R. & Bolton M. D., 835–846
- Stability of plate anchors in undrained clay. Merifield R. S., Sloan S. W. & Yu H. S., 141–153
- Technical note: Revisiting Hvorslev's intake factors using the finite element method. Ratnam S., Soga K. & Whittle R. W., 641–645
- Technical note: Seismic vertical uplift capacity of strip anchors. Kumar J., 275–279
- Undrained cavity expansion in modified Cam clay I: Theoretical analysis. Cao L. F., Teh C. I. & Chang M. F., 323–334
- Offshore engineering**
- An investigation of the effect of soil state on the capacity of driven piles in sands. Klotz E. U. & Coop M. R., 733–751
- Combined loading of spudcan foundations on clay: numerical modelling. Martin C. M. & Houlsby G. T., 687–699
- Technical note: Observations of footing behaviour in loose carbonate sands. Byrne B. W. & Houlsby G. T., 463–466
- Partial saturation**
- A model for rockfill compressibility. Oldecop L. A. & Alonso E. E., 127–139
- Discussion: A unique relationship for  $\chi$  for the determination of the shear strength of unsaturated soils. Khalili N. & Khabbaz M. H., 477–478
- Discussion: Influence of soil structure and stress history on the soil—water characteristics of a compacted till. Vanapalli S. K., Fredlund D. G. & Pufahl D. E., 573–576
- Partially saturated tailings sand below the phreatic surface. Fourie A. B., Hofmann B. A., Mikula R. J., Lord E. R. F. & Robertson P. K., 577–585
- Technical note: Analytical study of saturation effects on seismic vertical amplification of a soil layer. Yang J. & Sato T., 161–165
- The strength of unsaturated bentonite-enhanced sand. Stewart D. I., Tay Y. Y. & Cousens T. W., 767–775
- Permeability**
- Discussion: The permeability of clay suspensions. Pane V. & Schiffman R. L., 375–376
- Prediction and interpretation of pore pressure dissipation for a tapered piezoprobe. Whittle A. J., Sutabutr T., Germaine J. T. & Varney A., 601–617
- Technical note: Consolidation behaviour of allophone clays. Wesley L. D., 901–904

- Technical note: Revisiting Hvorslev's intake factors using the finite element method. Ratnam S., Soga K. & Whittle R. W., 641–645
- Piles**
- An investigation of the effect of soil state on the capacity of driven piles in sands. Klotz E. U. & Coop M. R., 733–751
- Case study of lateral spreading forces on a piled foundation. Berrill J. B., Christensen S. A., Keenan R. P., Okada W. & Pettinga J. R., 501–517
- Discussion: Time-related increases in the shaft capacities of driven piles in sand. Chow F. C., Jardine R. J., Nauroy J. F. & Bruzy F., 475–476
- Full-height piled bridge abutments constructed on soft clay. Ellis E. A. & Springman S. M., 3–14
- Kinematic pile bending during earthquakes: analysis and field measurements. Nikolaou S., Mylonakis G., Gazetas G. & Tazoh T., 425–440
- Piled raft foundations: design and applications. Poulos H. G., 95–113
- Technical note: On the application of the Hiley formula in driving long piles. Triantafyllidis T., 891–895
- Winkler modulus for axially loaded piles. Mylonakis G., 455–461
- Plasticity**
- Analysis of wave-induced liquefaction of sand beds. Sassa S. & Sekiguchi H., 115–126
- Bearing capacity of spatially random soil: the undrained clay Prandtl problem revisited. Griffiths D. V. & Fenton G. A., 351–359
- Combined loading of spudcan foundations on clay: numerical modelling. Martin C. M. & Houlsby G. T., 687–699
- Development of stabilisation and solidification on lime–clay mixes. Boardman D. I., Glendinning S. & Rogers C. D. F., 533–543
- Discussion: Dilatancy for cohesionless soils. Li X. S. & Dafalias Y. F., 729–730
- Discussion: Fall-cone penetration and water content relationships of clays. Feng T. W., 819–821
- Discussion: Slope stability analysis by finite elements. Griffiths D. V. & Lane P. A., 653–654
- New descriptions of plane strain. Dean E. T. R., 15–36
- Stability of plate anchors in undrained clay. Merifield R. S., Sloan S. W. & Yu H. S., 141–153
- Strip loads on a non-linear heterogeneous half-space. Holzlöhner U., 655–664
- Technical note: Fractal compression of soil. McDowell G. R. & Daniell C. M., 173–176
- Technical note: Observations of footing behaviour in loose carbonate sands. Byrne B. W. & Houlsby G. T., 463–466
- Technical note: On the non-intersection dilemma in multiple surface plasticity. Puzrin A. M. & Houlsby G. T., 369–372
- Technical note: Strain-based plasticity models for soils and the BRICK model as an example of the hyperplasticity approach. Puzrin A. M. & Houlsby G. T., 169–172
- Theory and practice of the fall cone test. Koumoto T. & Houlsby G. T., 701–712
- Upper bound load estimates on square and rectangular footings. Michalowski R. L., 787–798
- Pore pressures**
- Consolidation equation valid for both Darcian and non-Darcian flow. Hansbo S., 51–54
- Consolidation of naturally gassy soft soil. Sills G. C. & Gonzalez R., 629–639
- Factors affecting rainfall-induced flowslides in laboratory flume tests. Wang G. & Sassa K., 587–599
- Failure mechanism of the Aznalcóllar Dam, Seville, Spain. Olalla C. & Cuéllar V., 399–406
- Natural slopes and cuts: movement and failure mechanisms. Leroueil S., 197–243
- Partially saturated tailings sand below the phreatic surface. Fourie A. B., Hofmann B. A., Mikula R. J., Lord E. R. F. & Robertson P. K., 577–585
- Plane strain instability of saturated elasto-plastic soils. Iai S. & Bardet J. P., 389–398
- Prediction and interpretation of pore pressure dissipation for a tapered piezoprobe. Whittle A. J., Sutabutr T., Germaine J. T. & Varney A., 601–617
- Pre-failure strain softening and pre-failure instability of sand: a comparative study. Chu J. & Leong W. K., 311–321
- Technical note: Undrained shear strength of soft clays from push cone penetration test. Mesri G., 167–168
- Undrained cavity expansion in modified Cam clay I: Theoretical analysis. Cao L. F., Teh C. I. & Chang M. F., 323–334
- Undrained cavity expansion in modified Cam clay II: Application to the interpretation of the piezocone test. Chang M. F., Teh C. I. & Cao L. F., 335–350
- Rafts**
- Piled raft foundations: design and applications. Poulos H. G., 95–113
- Reinforced soils**
- Discussion: Theoretical analysis of centrifugal model tests on reinforced earth structures. Sawicki A., 571–572
- Technical note: Horizontal slice method of analysis. Shahgholi M., Fakher A. & Jones C. J. F. P., 881–885
- Remediation**
- Technical note: Stabilisation of leaning structures: the Tower of Pisa case. Ranzini S. M. T., 647–648
- Repeated loading**
- Technical note: Shear modulus and damping ratio of a clay during undrained cyclic loading. Teachavorasinskun S., Thongchim P. & Lukkunaprasit P., 467–470
- Retaining walls**
- Active and passive critical slip fields for cohesionless soils and calculation of lateral earth pressures. Zhu D.-Y., Qian Q.-H. & Lee C. F., 407–423
- Discussion: Net pressure analysis of cantilever sheet pile walls. Day R. A., 185–187
- Discussion: Soil stiffness in stress paths relevant to diaphragm walls in clay. Powrie W., Pantelidou H. & Stallebrass S. E., 177–178
- Full-height piled bridge abutments constructed on soft clay. Ellis E. A. & Springman S. M., 3–14
- Rocks/rock mechanics**
- Fuzzy partitioning algorithms applied to the interpretation of distinct element modelling results. Harrison J. P., Ferrero A. M. & Cravero S., 677–686
- Technical note: Constitutive model for the continuous damage of brittle rock. Pan Y.-W. & Wen B.-H., 155–159
- Technical note: Strength variation in young reef limestones. Burton C. L., Waltham A. C. & McLaren S. J., 887–889
- Sampling**
- Discussion: Estimation of *in situ* stresses using anisotropic elasticity and suction measurements. Doran I. G., Sivakumar V., Graham J. & Johnson A., 383–384
- Technical note: Block sampling and test sample preparation of locked sands. Cresswell A., 567–570
- Sands**
- An investigation of the effect of soil state on the capacity of driven piles in sands. Klotz E. U. & Coop M. R., 733–751
- A random method for simulating loose packs of angular particles using tetrahedra. Latham J.-P., Lu Y. & Munjiza A., 871–879
- Discussion: A probabilistic approach to sand particle crushing in the triaxial test. Nakata Y., Hyde A. F. L., Hyodo M. & Murata H., 285–287
- Discussion: Dilatancy for cohesionless soils. Li X. S. & Dafalias Y. F., 729–730
- Discussion: Group effects in stone column foundations: model tests. Muir-Wood D., Hu W. & Nash D. F. T., 649
- Discussion: Observation of Biot compressional wave of the second kind in granular soils. Nakagawa K., Soga K. & Mitchell J. K., 85–89
- Discussion: Sand state from cone penetrometer tests: a framework considering grain crushing stress. Konrad J.-M., 651–652
- Discussion: Time-related increases in the shaft capacities of driven piles in sand. Chow F. C., Jardine R. J., Nauroy J. F. & Bruzy F., 475–476
- Partially saturated tailings sand below the phreatic surface. Fourie A. B., Hofmann B. A., Mikula R. J., Lord E. R. F. & Robertson P. K., 577–585
- Particle shape characterisation using Fourier descriptor analysis. Bowman E. T., Soga K. & Drummond W., 545–554
- Pre-failure strain softening and pre-failure instability of sand: a comparative study. Chu J. & Leong W. K., 311–321
- Quantitative characterisation of the geometry of discrete particles. Sukumaran B. & Ashmawy A. K., 619–627
- Radiographic and microscopic observation of shear bands in granular materials. Nemat-Nasser S. & Okada N., 753–765
- Technical note: A novel Bender/extender element for soil testing. Lings M. L. & Greening P. D., 713–717
- Technical note: Block sampling and test sample preparation of locked sands. Cresswell A., 567–570
- Technical note: Fractal compression of soil. McDowell G. R. & Daniell C. M., 173–176
- Technical note: Observations of footing behaviour in loose carbonate sands. Byrne B. W. & Houlsby G. T., 463–466
- Technical note: Seismic vertical uplift capacity of strip anchors. Kumar J., 275–279
- Sedimentation**
- Discussion: The permeability of clay suspensions. Pane V. & Schiffman R. L., 375–376

- Technical note: Monitoring sedimentation of a clay slurry. Blewett J., McCarter W. J., Chrisp T. M. & Starrs G., 723–728
- Settlement**
- Consolidation equation valid for both Darcian and non-Darcian flow. Hansbo S., 51–54
- Deformation of landfill from measurements of shear wave velocity and damping. Abbiss C. P., 483–492
- Discussion: A back-analysis of Beliche Dam. Naylor D. J., Maranha J. R., Maranha das Neves E. & Viegas Pinto A. A., 377–381
- Discussion: Precompression design for secondary settlement reduction. Alonso E. E., Gens A. & Lloret A., 822–826
- Field behaviour of very soft clays at the Athlone embankments. Long M. M. & O’Riordan N. J., 293–309
- Piled raft foundations: design and applications. Poulos H. G., 95–113
- Strip loads on a non-linear heterogeneous half-space. Holzöhner U., 655–664
- Technical note: Consolidation of soil with vertical and horizontal drainage under ramp load. Zhu G. & Yin J.-H., 361–367
- Technical note: Stabilisation of leaning structures: the Tower of Pisa case. Ranzini S. M. T., 647–648
- Winkler modulus for axially loaded piles. Mylonakis G., 455–461
- Shear strength**
- A laboratory study of post-rupture strength. Georgiannou V. N. & Burland J. B., 665–675
- Bearing capacity of spatially random soil: the undrained clay Prandtl problem revisited. Griffiths D. V. & Fenton G. A., 351–359
- Discussion: A probabilistic approach to sand particle crushing in the triaxial test. Nakata Y., Hyde A. F. L., Hyodo M. & Murata H., 285–287
- Discussion: A unique relationship for  $\chi$  for the determination of the shear strength of unsaturated soils. Khalili N. & Khabbaz M. H., 477–478
- Discussion: Fall-cone penetration and water content relationships of clays. Feng T. W., 819–821
- Discussion: Sand state from cone penetrometer tests: a framework considering grain crushing stress. Konrad J.-M., 651–652
- Failure mechanism of the Aznalcóllar Dam, Seville, Spain. Olalla C. & Cuéllar V., 399–406
- Failure modes of drilling fluid filter cake. Cerasi P. & Soga K., 777–785
- Field behaviour of very soft clays at the Athlone embankments. Long M. M. & O’Riordan N. J., 293–309
- Pre-failure strain softening and pre-failure instability of sand: a comparative study. Chu J. & Leong W. K., 311–321
- Structure degradation and changes in the mechanical behaviour of a stiff clay due to weathering. Cafaro F. & Cotecchia F., 441–453
- Technical note: Shear strength parameters from back-analysis of single slips. Wesley L. D. & Leelaratnam V., 373–374
- Technical note: Undrained shear strength of soft clays from push cone penetration test. Mesri G., 167–168
- Theory and practice of the fall cone test. Koumoto T. & Houlsby G. T., 701–712
- The strength of unsaturated bentonite-enhanced sand. Stewart D. I., Tay Y. Y. & Cousens T. W., 767–775
- Undrained cavity expansion in modified Cam clay II: Application to the interpretation of the piezocone test. Chang M. F., Teh C. I. & Cao L. F., 335–350
- Sheet piles and cofferdams**
- Discussion: Dimensional analysis for geotechnical engineers. Butterfield R., 91–93
- Discussion: Net pressure analysis of cantilever sheet pile walls. Day R. A., 185–187
- Silts**
- Factors affecting rainfall-induced flowslides in laboratory flume tests. Wang G. & Sassa K., 587–599
- Site investigation**
- Deformation of landfill from measurements of shear wave velocity and damping. Abbiss C. P., 483–492
- Failure mechanism of the Aznalcóllar Dam, Seville, Spain. Olalla C. & Cuéllar V., 399–406
- Field behaviour of very soft clays at the Athlone embankments. Long M. M. & O’Riordan N. J., 293–309
- Technical note: Revisiting Hvorslev’s intake factors using the finite element method. Ratnam S., Soga K. & Whittle R. W., 641–645
- Three-dimensional site characterisation: neural network approach. Juang C. H., Jiang T. & Christopher R. A., 799–809
- Slopes**
- Discussion: Earthquake destructiveness: potential factor and slope stability. Crespellani T., Madiari C. & Vannucchi G., 281–284
- Discussion: Slope stability analysis by finite elements. Griffiths D. V. & Lane P. A., 653–654
- Natural slopes and cuts: movement and failure mechanisms. Leroueil S., 197–243
- Technical note: Shear strength parameters from back-analysis of single slips. Wesley L. D. & Leelaratnam V., 373–374
- Soil classification**
- Particle shape characterisation using Fourier descriptor analysis. Bowman E. T., Soga K. & Drummond W., 545–554
- Technical note: Strength variation in young reef limestones. Burton C. L., Waltham A. C. & McLaren S. J., 887–889
- Theory and practice of the fall cone test. Koumoto T. & Houlsby G. T., 701–712
- Soil stabilisation**
- Development of stabilisation and solidification on lime–clay mixes. Boardman D. I., Glendinning S. & Rogers C. D. F., 533–543
- Soil/structure interaction**
- Combined loading of spudcan foundations on clay: numerical modelling. Martin C. M. & Houlsby G. T., 687–699
- Full-height piled bridge abutments constructed on soft clay. Ellis E. A. & Springman S. M., 3–14
- Kinematic pile bending during earthquakes: analysis and field measurements. Nikolaou S., Mylonakis G., Gazetas G. & Tazoh T., 425–440
- Piled raft foundations: design and applications. Poulos H. G., 95–113
- Winkler modulus for axially loaded piles. Mylonakis G., 455–461
- Standards**
- Theory and practice of the fall cone test. Koumoto T. & Houlsby G. T., 701–712
- Statistical analysis**
- Bearing capacity of spatially random soil: the undrained clay Prandtl problem revisited. Griffiths D. V. & Fenton G. A., 351–359
- Discussion: A probabilistic approach to sand particle crushing in the triaxial test. Nakata Y., Hyde A. F. L., Hyodo M. & Murata H., 285–287
- Particle shape characterisation using Fourier descriptor analysis. Bowman E. T., Soga K. & Drummond W., 545–554
- Technical note: Fractal compression of soil. McDowell G. R. & Daniell C. M., 173–176
- Technical note: Statistics of soil particle strength. McDowell G. R., 897–900
- Three-dimensional site characterisation: neural network approach. Juang C. H., Jiang T. & Christopher R. A., 799–809
- Stiffness**
- Discussion: Estimation of *in situ* stresses using anisotropic elasticity and suction measurements. Doran I. G., Sivakumar V., Graham J. & Johnson A., 383–384
- Discussion: Group effects in stone column foundations: model tests. Muir-Wood D., Hu W. & Nash D. F. T., 649
- Discussion: Observation of Biot compressional wave of the second kind in granular soils. Nakagawa K., Soga K. & Mitchell J. K., 85–89
- Discussion: Soil stiffness in stress paths relevant to danular soils. Nakagawa K., Soga K. & Mitchell J. K., 85–89
- Discussion: Soil stiffness in stress paths relevant to diaphragm walls in clay. Powrie W., Pantelidou H. & Stallebrass S. E., 177–178
- Drained and undrained anisotropic elastic stiffness parameters. Lings M. L., 555–565
- Stiffness of geomaterials at very small strains. Clayton C. R. I. & Heymann G., 245–255
- Structure degradation and changes in the mechanical behaviour of a stiff clay due to weathering. Cafaro F. & Cotecchia F., 441–453
- Technical note: A novel bender/extender element for soil testing. Lings M. L. & Greening P. D., 713–717
- Technical note: Constitutive model for the continuous damage of brittle rock. Pan Y.-W. & Wen B.-H., 155–159
- Technical note: Shear modulus and damping ratio of a clay during undrained cyclic loading. Teachavorasinskun S., Thongchim P. & Lukkunaprasit P., 467–470
- Winkler modulus for axially loaded piles. Mylonakis G., 455–461
- Stress analysis**
- Discussion: Further investigations at the Folkstone Warren landslide. Trenter N. A. & Warren C. D., 189–192
- Discussion: Theoretical analysis of centrifugal model tests on reinforced earth structures. Sawicki A., 571–572
- Failure modes of drilling fluid filter cake. Cerasi P. & Soga K., 777–785
- Technical note: Drained creep behaviour of soft Hong Kong marine deposits. Zhu J.-G. & Yin J.-H., 471–474
- Technical note: On the application of the Hiley formula in driving long piles. Triantafyllidis T., 891–895
- Technical note: On the non-intersection dilemma in multiple surface plasticity. Puzrin A. M. & Houlsby G. T., 369–372
- Technical note: Strain-based plasticity models for soils and the BRICK model as an example of the hyperplasticity approach. Puzrin A. M. & Houlsby G. T., 169–172

- Technical note: Stabilisation of leaning structures: the Tower of Pisa case. Ranzini S. M. T., 647–648
- Technical note: Uplift, friction, capillarity and effective stress: revisited via the porous media theory. de Boer R., 811–814
- Suction**
- A parametric study of the pull-out capacity of bucket foundations in soft clay. Zdravković L., Potts D. M. & Jardine R. J., 55–67
- Discussion: A unique relationship for  $\chi$  for the determination of the shear strength of unsaturated soils. Khalili N. & Khabbaz M. H., 477–478
- Discussion: Estimation of *in situ* stresses using anisotropic elasticity and suction measurements. Doran I. G., Sivakumar V., Graham J. & Johnson A., 383–384
- Stability of plate anchors in undrained clay. Merifield R. S., Sloan S. W. & Yu H. S., 141–153
- Structure degradation and changes in the mechanical behaviour of a stiff clay due to weathering. Cafaro F. & Cotecchia F., 441–453
- The strength of unsaturated bentonite-enhanced sand. Stewart D. I., Tay Y. Y. & Cousens T. W., 767–775
- Theoretical analysis**
- Analysis of progressive liquefaction as a moving-boundary problem. Sassa S., Sekiguchi H. & Miyamoto J., 847–857
- Consolidation equation valid for both Darcian and non-Darcian flow. Hansbo S., 51–54
- Deformation of landfill from measurements of shear wave velocity and damping. Abbiss C. P., 483–492
- Fuzzy partitioning algorithms applied to the interpretation of distinct element modelling results. Harrison J. P., Ferrero A. M. & Cravero S., 677–686
- Plane strain instability of saturated elasto-plastic soils. Iai S. & Bardet J. P., 389–398
- Prediction and interpretation of pore pressure dissipation for a tapered piezoprobe. Whittle A. J., Sutabutr T., Germaine J. T. & Varney A., 601–617
- Secondary compression of clays as a local dehydration process. Navarro V. & Alonso E. E., 859–869
- Technical note: Consolidation of soil with vertical and horizontal drainage under ramp load. Zhu G. & Yin J.-H., 361–367
- Technical note: Horizontal slice method of analysis. Shahgholi M., Fagher A. & Jones C. J. F. P., 881–885
- Technical note: Shear strength parameters from back-analysis of single slips. Wesley L. D. & Leelaratnam V., 373–374
- Undrained cavity expansion in modified Cam clay I: Theoretical analysis. Cao L. F., Teh C. I. & Chang M. F., 323–334
- Undrained cavity expansion in modified Cam clay II: Application to the interpretation of the piezocone test. Chang M. F., Teh C. I. & Cao L. F., 335–350
- Upper bound load estimates on square and rectangular footings. Michalowski R. L., 787–798
- Time dependence**
- Discussion: Time-related increases in the shaft capacities of driven piles in sand. Chow F. C., Jardine R. J., Nauroy J. F. & Brucy F., 475–476
- Secondary compression of clays as a local dehydration process. Navarro V. & Alonso E. E., 859–869
- Technical note: Consolidation of soil with vertical and horizontal drainage under ramp load. Zhu G. & Yin J.-H., 361–367
- Technical note: On the application of the Hiley formula in driving long piles. Triantafyllidis T., 891–895
- Tunnels**
- Fuzzy partitioning algorithms applied to the interpretation of distinct element modelling results. Harrison J. P., Ferrero A. M. & Cravero S., 677–686
- Soil consolidation associated with grouting during shield tunnelling in soft clayey ground. Komiya K., Soga K., Akagi H., Jafari M. R. & Bolton M. D., 835–846
- Vibration**
- Technical note: Analytical study of saturation effects on seismic vertical amplification of a soil layer. Yang J. & Sato T., 161–165
- Waves and wave loading**
- Analysis of progressive liquefaction as a moving-boundary problem. Sassa S., Sekiguchi H. & Miyamoto J., 847–857
- Analysis of wave-induced liquefaction of sand beds. Sassa S. & Sekiguchi H., 115–126