

INDEX TO GÉOTECHNIQUE VOLUME LV

February, March, April, May, June, August, September, October, November, December 2005

No. 1, 1–94; No. 2, 95–188; No. 3, 189–266; No. 4, 267–343; No. 5, 345–422; No. 6, 423–496; No. 7, 497–573; No. 8, 575–628;
No. 9, 629–705; No. 10, 707–782

AUTHOR INDEX

- Almeida M. S. S.** *see* Futai M. M. & Almeida M. S. S.
Alonso E. E., Olivella S. & Pinyol N. M.
 A review of Beliche Dam, 267–285
Amatya S. *see* Honjo Y. & Amatya S.
Amorosi A. *see* Houlsby G. T. *et al.*
Amundaray J. I. *see* Bourdeau P. L. & Amundaray J. I.
Au S. K. A. *see* Soga K. *et al.*
- Baldry A. S.** *see* Palmer A. C. *et al.*
Barefoot A. J. *see* Palmer A. C. *et al.*
Baumgard A. J. *see* Palmer A. C. *et al.*
Bergado D. T., Youwai S. & Rittirong A.
 Technical note. Strength and deformation characteristics of flat and cubical rubber tyre chip–sand mixtures, 603–606
Best A. I. *see* Clayton C. R. I. *et al.*
Bhattacharya S., Madabhushi S. P. G. & M. D. Bolton
 Discussion. An alternative mechanism of pile failure in liquefiable deposits during earthquakes, 259–263
Bolle A. *see* Collin F. *et al.*
Bolton M. D. *see* Bhattacharya S. *et al.*
See also Osman A. S. & Bolton M. D., Palmer A. C. *et al.* and Soga K. *et al.*
Borsic A., Comina C., Foti S., Lancellotta R. & Musso G.
 Imaging heterogeneities with electrical impedance tomography: laboratory results, 539–547
Boulbibane M. & Ponter A. R. S.
 Linear matching method for limit load problems using the Drucker–Prager yield condition, 731–739
Bourdeau P. L. & Amundaray J. I.
 Non-parametric simulation of geotechnical variability, 95–108
Breyse D., Niandou H., Elachachi S. & Houy L.
 A generic approach to soil–structure interaction considering the effects of soil heterogeneity, 143–150
Breyse D. *see* Houy L. *et al.*
Brown E. T. *see* Indraratna B. *et al.*
Burland J. B. *see* Franzius J. N. *et al.*
Byrne B. W. *see* Houlsby G. T. *et al.*
- Cassidy M. J.** *see* Houlsby G. T. *et al.*
Chen J., Yin J.-H. and Lee C. F.
 A three-dimensional upper-bound approach to slope stability analysis based on RFEM, 549–556
Cheng Y. M.
 Discussion. N_0 factor for pile foundations by Berezantzev, 493–494
Cheung R. W. M. & Tang W. H.
 Realistic assessment of slope reliability for effective landslide hazard management, 85–94
Cho G.-C. *see* Sung S.-G. *et al.*
Choudhury D. & Nimbalkar S.
 Technical note. Seismic passive resistance by pseudo-dynamic method, 699–702
Chow Y. K. *see* Purwana O. A. *et al.*
Christie D. *see* Indraratna B. *et al.*
Clayton C. R. I., Priest J. A. & Best A. I.
 The effects of disseminated methane hydrate on the dynamic stiffness and damping of a sand, 423–434
Clinton L. *see* Coop M. R. *et al.*
Collin F., Schroeder Ch., De Gennaro V. & Bolle A.
 A deterministic/stochastic model to predict the variation in bulk modulus of chalk, 135–141
Collins I. F.
 The concept of stored plastic work or frozen elastic energy in soil mechanics, 373–382
Comina C. *see* Borsic A. *et al.*
Coop M. R., Klotz E. U. & Clinton L.
 The influence of the *in situ* state of sands on the load-deflection behaviour of driven piles, 721–730
Cruden D. M. *see* El-Ramly H. *et al.*
Cui Y. J., Lu Y. F., Delage P. & Riffard M.
 Field simulation of *in situ* water content and temperature changes due to ground–atmospheric interactions, 557–567
- Dardzińska I.** *see* Przewłócki J. *et al.*
Dasari G. R. *see* Ni Q. *et al.*
Delage P. *see* Cui Y. J. *et al.*
Denis A. *see* Houy L. *et al.*
Deodatis G. *see* Popescu R. *et al.*
De Gennaro V. *see* Collin F. *et al.*
- Edwards D. H., Zdravkovic L. & Potts D. M.**
 Technical note. Depth factors for undrained bearing capacity, 755–758
Einav I.
 Energy and variational principles for piles in dissipative soil, 515–525
See also Houlsby G. T. *et al.*
El-Gonnouni M., Riou Y. & Hicher P. Y.
 Geostatistical method for analysing soil displacement from underground urban construction, 171–182
El-Ramly H., Morgenstern N. R. & Cruden D. M.
 Probabilistic assessment of stability of a cut slope in residual soil, 77–84
Elachachi S. *see* Breyse D. *et al.*
Eliadorani A. *see* Fannin R. J. *et al.*
Estévez M. *see* Hernández J. *et al.*
- Fannin R. J., Eliadorani A. & Wilkinson J. M. T.**
 Shear strength of cohesionless soils at low stress, 467–478
Faranski A. S. *see* Palmer A. C. *et al.*
Fenton G. A., Griffiths D. V. & Williams M. B.
 Reliability of traditional retaining wall design, 55–62
Fenton G. A. *see* Jaksa M. B. *et al.*
Finch M. *see* Palmer A. C. *et al.*
Foo K. S. *see* Purwana O. A. *et al.*
Foti S. *see* Borsic A. *et al.*
Franzius J. N., Potts D. M. & Burland J. B.
 The influence of soil anisotropy and K_0 on ground surface movements resulting from tunnel excavation, 189–199
Futai M. M. & Almeida M. S. S.
 An experimental investigation of the mechanical behaviour of an unsaturated gneiss residual soil, 201–213
- Gaudin C.** *see* Lehane B. M. *et al.*
Goldsworthy J. S. *see* Jaksa M. B. *et al.*
Griffiths D. V. *see* Fenton G. A. *et al.*
See also Jaksa M. B. *et al.*
- Harkness R. M.** *see* Powrie W. *et al.*
Hernández J., Vargas S., Estévez M., Vázquez G., Zepeda A. and Rodríguez R.
 Technical note. Hydrophobic modification of an expansive soil using polymers and organic compounds: a comparative study with lime, 613–616
Hicher P. Y. *see* El Gonnouni M. *et al.*
Hicks M. A. & Onisiphorou C.
 Stochastic evaluation of static liquefaction in a predominantly dilative sand fill, 123–133
Hight D. W. *see* Ni Q. *et al.*
Hird C. C. & Srisakthivel S.
 Laboratory investigation of permeability measurement in clay using outflow from unsupported cavities, 393–402
Hird C. C. *see* Sills G. C. & Hird C. C.
Honjo Y. & Amatya S.
 Partial factors calibration based on reliability analyses for square footings on granular soils, 479–491
Hossain M. S., Hu Y., Randolph M. F. & White D. J.
 Limiting cavity depth for spudcan foundations penetrating clay, 679–690
Houlsby G. T.
 Discussion. Editorial, 415–417
Houlsby G. T., Amorosi A. & Rojas E.
 Elastic moduli of soils dependent on pressure: a hyperelastic formulation, 383–392

- Houlsby G. T., Cassidy M. J. & Einav I.**
A generalised Winkler model for the behaviour of shallow foundations, 449–460
- Houlsby G. T., Kelly R. B., Huxtable J. & Byrne B. W.**
Field trials of suction caissons in clay for offshore wind turbine foundations, 287–296
- Houy L.** *see* Breyse D. *et al.*
- Houy L., Breyse D. & Denis A.**
Influence of soil heterogeneity on load redistribution and settlement of a hyperstatic three-support frame, 163–170
- Hsu H.-H.** *see* Huang A.-B. & Hsu H.-H.
- Hu Y.** *see* Hossain M. S. *et al.*
- Huang A.-B. & Hsu H.-H.**
Cone penetration tests under simulated field conditions, 345–354
- Huxtable J.** *see* Houlsby G. T. *et al.*
- Hyde A. F. L.** *see* Tarantino A. & Hyde A. F. L.
- Iai S., Tobita T. & Nakahara T.**
Generalised scaling relations for dynamic centrifuge tests, 355–362
- Indraratna B. & Jayanathan M.**
Technical note. Measurement of pore water pressure of clay-infilled rock joints during triaxial shearing, 759–764
- Indraratna B., Lackenby J. & Christie D.**
Technical note. Effect of confining pressure on the degradation of ballast under cyclic loading, 325–328
- Indraratna B., Welideniya H. S. & Brown E. T.**
A shear strength model for idealised infilled joints under constant normal stiffness, 215–226
- Ismail M. A. & Rammah K. I.**
Technical note. Shear-plate transducers as a possible alternative to bender elements for measuring G_{max}
- Jafari M. R.** *see* Soga K. *et al.*
- Jaksa M. B., Goldsworthy J. S., Fenton G. A., Kaggwa W. S., Griffiths D. V., Kuo Y. L. & Poulos H. G.**
Towards reliable and effective site investigations, 109–121
Discussion. Towards reliable and effective site investigations, 625–626
- Jayanathan M.** *see* Indraratna B. & Jayanathan M.
- Kaggwa W. S.** *see* Jaksa M. B. *et al.*
- Kelly R. B.** *see* Houlsby G. T. *et al.*
- Klar A., Vorster T. E. B., Soga K. & Mair R. J.**
Soil–pipe interaction due to tunnelling: comparison between Winkler and elastic continuum solutions, 461–466
- Klotz E. U.** *see* Coop M. R. *et al.*
- Kulhawy F. H.** *see* Phoon K.-K. & Kulhawy F. H.
- Kuo Y. L.** *see* Jaksa M. B. *et al.*
- Lackenby J.** *see* Indraratna B. *et al.*
- Lancellotta R.** *see* Borsic A. *et al.*
- Larsson S., Stille H. & Olsson L.**
On horizontal variability in lime-cement columns in deep mixing, 33–44
- Lee C. F.** *see* Chen J. *et al.*
- Lee I.-M.** *see* Sung S.-G. *et al.*
- Lehane B. M., Gaudin C. & Schneider J. A.**
Scale effects on tension capacity for rough piles buried in dense sand, 709–719
- Leung C. F.** *see* Purwana O. A. *et al.*
- Li W. P. & Li X. Q.**
Mechanism of rupture of shaft linings in coal mine areas buried by thick over-soils in East China, 237–244
- Li X. Q.** *see* Li W. P. & Li X. Q.
- Lobo-Guerrero S. & Vallejo L. E.**
Technical note. Crushing a weak granular material: experimental numerical analyses, 245–249
Technical note. DEM analysis of crushing around driven piles in granular materials, 617–23
- Low B. K.**
Reliability-based design applied to retaining walls, 63–75
- Lu Y. F.** *see* Cui Y. J. *et al.*
- Madabhushi S. P. G.** *see* Bhattacharya S. *et al.*
- Mair R. J.** *see* Klar A. *et al.*
- McDowell G. R.**
Technical note. A physical justification for $\log e - \log \sigma$ based on fractal crushing and particle kinematics, 697–698
- Morgenstern N. R.** *see* El-Ramly H. *et al.*
- Musso G.** *see* Borsic A. *et al.*
- Nader J. J.**
Technical note. Non-steady flow in the variable-head permeability test, 703
- Nakahara T.** *see* Iai S. *et al.*
- Ng A. M. Y.** *see* Zhang L. M. & Ng. A. M. Y.
- Ni Q.** *see* Powrie W. *et al.*
- Ni Q., Tan T. S., Dasari G. R. & Hight D. W.**
Discussion. Contribution of fines to the compressive strength of mixed soils, 627–628
- Niandou H.** *see* Breyse D. *et al.*
- Nimbalkar S.** *see* Choudhury D. & Nimbalkar S.
- Oda M., Takemura T. & Takahashi M.**
Discussion. Microstructure in shear band observed by microfocus X-ray computed tomography, 333–335
- O'Kelly B. C.**
Technical note. Method to compare water content values determined on the basis of different oven-drying temperatures, 329–332
- Olivella S.** *see* Alonso E. E. *et al.*
- Olsson L.** *see* Larsson H. *et al.*
- Onisiphorou C.** *see* Hicks M. A. & Onisiphorou C.
- Osman A. S. & Bolton M. D.**
Simple plasticity-based prediction of the undrained settlement of shallow circular foundations on clay, 435–447
- Palmer A. C., White D. J., Baumgard A. J., Bolton M. D., Barefoot A. J., Finch M., Powell T., Faranski A. S. & Baldry A. S.**
Discussion. Uplift resistance of buried submarine pipelines: comparison between centrifuge modelling and full-scale tests, 338–340
- Phoon K.-K.** *see* Uzielli M. *et al.*
- Phoon K.-K. & Kulhawy F. H.**
Characterisation of model uncertainties for laterally loaded rigid drilled shafts, 45–54
- Pinyol N. M.** *see* Alonso E. E. *et al.*
- Ponter A. R. S.** *see* Boulbibane M. & Ponter A. R. S.
- Popescu R., Prevost J. H. & Deodatis G.**
3D effects in seismic liquefaction of stochastically variable soil deposits, 21–31
- Potts D. M.** *see* Edwards D. H. *et al.*
See also Franzius J. N. *et al.* and Zdravkovic L. *et al.*
- Poulos H. G.** *see* Jaksa M. B. *et al.*
- Powell T.** *see* Palmer A. C. *et al.*
- Powrie W., Ni Q., Harkness R. M. & Zhang X.**
Numerical modelling of plane strain tests on sands using a particulate approach, 297–306
- Prevost J. H.** *see* Popescu R. *et al.*
- Priest J. A.** *see* Clayton C. R. I. *et al.*
- Przewłócki J., Dardzińska I. & Świniański J.**
Review of historical buildings' foundations, 363–372
- Purwana O. A., Leung C. F., Chow Y. K. & Foo K. S.**
Influence of base suction on extraction of jack-up spudcans, 741–753
- Puzrin A. M.** *see* Rammah K. I. *et al.*
- Rammah K. I.** *see* Ismail M. A. & Rammah K. I.
- Rammah K. I., Val D. V. & Puzrin A. M.**
Discussion. Effects of ageing on small-strain stiffness of overconsolidated clays, 336–337
- Randolph M. F.** *see* Hossain M. S. *et al.*
- Ratnam S., Soga K. & Whittle R. W.**
A field permeability measurement technique using a conventional self-boring pressuremeter, 527–537
- Reddi L. N.** *see* Sung S.-G. *et al.*
- Riffard M.** *see* Cui Y. J. *et al.*
- Riou Y.** *see* El Gonnouni M. *et al.*
- Rittirong A.** *see* Bergado D. T. *et al.*
- Rodríguez R.** *see* Hernández J. *et al.*
- Rojas E.** *see* Houlsby G. T. *et al.*
- Rowe R. K.**
Long-term performance of contaminant barrier systems, 631–678
- Schneider J. A.** *see* Lehane B. M. *et al.*
- Schroeder Ch.** *see* Collin F. *et al.*
- Sills G. C. & Hird C. C.**
Coefficient of consolidation from piezocone measurements, 597–602
- Smith C. C.**
Technical note. Complete limiting stress solutions for the bearing capacity of strip footings on a Mohr–Coulomb soil, 607–612
- Soga K., Au S. K. A., Jafari M. R. & M. D. Bolton**
Discussion. Laboratory investigation of multiple grout injections into clay, 257–258

- Soga K.** *see* Klar A. *et al.*
See also Ratnam S. *et al.*
- Srisakthivel S.** *see* Hird C. C. & Srisakthivel S.
- St John H. D.** *see* Zdravkovic L. *et al.*
- Stille H.** *see* Larsson H. *et al.*
- Sun D. A.** *see* Xu Y. F. & Sun D. A.
- Sung S.-G., Lee I.-M., Cho G.-C. & Reddi L. N.**
 Technical note. Estimation of soil-water characteristics using liquid limit state, 569–573
- Świniański J.** *see* Przewłócki J. *et al.*
- Takahashi M.** *see* Oda M. *et al.*
- Takemura T.** *see* Oda M. *et al.*
- Tan T.-S.** *see* Yang L.-A. & Tan T.-S.
- Tan T. S.** *see* Ni Q. *et al.*
- Tang W. H.** *see* Cheung R. W. M. and Tang W. H.
See also Zhang L. L. *et al.*
- Tarantino A. & Hyde A. F. L.**
 An experimental investigation of work dissipation in crushable materials, 575–584
- Tarantino A. & Tombolato S.**
 Coupling of hydraulic and mechanical behaviour in unsaturated compacted clay, 307–317
- Tobita T.** *see* Iai S. *et al.*
- Tombolato S.** *see* Tarantino A. & Tombolato S.
- Troncone A.**
 Numerical analysis of a landslide in soils with strain-softening behaviour, 585–596
- Uzielli M., Vannucchi G. & Phoon K.-K.**
 Random field characterisation of stress-normalised cone penetration testing parameters, 3–20
- Val D. V.** *see* Rammah K. I. *et al.*
- van Baars**
 Technical note. The horizontal failure mechanism of the Wilnis peat dyke, 319–323
- Vannucchi G.** *see* Uzielli M. *et al.*
- Vallejo L. E.** *see* Lobo-Guerrero S. & Vallejo L. E.
- Vargas S.** *see* Hernández J. *et al.*
- Vázquez G.** *see* Hernández J. *et al.*
- Vorster T. E. B.** *see* Klar A. *et al.*
- Welideniya H. S.** *see* Indraratna B. *et al.*
- White D. J.** *see* Hossain M. S. *et al.*
See also Palmer A. C. *et al.*
- Whittle R. W.** *see* Ratnam S. *et al.*
- Wilkinson J. M. T.** *see* Fannin R. J. *et al.*
- Williams M. B.** *see* Fenton G. A. *et al.*
- Xu Y. F. & Sun D. A.**
 Technical note. Correlation of surface fractal dimension with frictional angle at critical state of sands, 691–695
- Yang J.**
 Technical note. Pore pressure coefficient for soil and rock and its relation to compressional wave velocity, 251–256
 Technical note. Rayleigh surface waves in an idealised partially soil, 409–414
- Yang L.-A. & Tan T.-S.**
 One-dimensional consolidation of lumpy clay with non-linear properties, 227–235
- Yin J.-H.** *see* Chen J. *et al.*
- Youwai S.** *see* Bergado D. T. *et al.*
- Zdravkovic L., Potts D. M. & St John H. D.**
 Modelling of 3D excavation in finite element analysis, 497–513
- Zdravkovic L.** *see* Edwards D. H. *et al.*
- Zepeda A.** *see* Hernández J. *et al.*
- Zhang L. L., Zhang L. M. & Tang W. H.**
 Technical note. Rainfall-induced slope failure considering variability of soil properties, 183–188
- Zhang L. M. & Ng A. M. Y.**
 Probabilistic limiting tolerable displacements for serviceability limit state design of foundations, 151–161
- Zhang L. M.** *see* Zhang L. L. *et al.*
- Zhang X.** *see* Powrie W. *et al.*

SUBJECT INDEX

Anisotropy

Elastic moduli of soils dependent on pressure: a hyperelastic formulation. Housby G. T., Amorosi A. & Rojas E., 383–392

Bearing capacity

Field trials of suction caissons in clay for offshore wind turbine foundations. Housby G. T., Kelly R. B., Huxtable J. & Byrne B. W., 287–296

A generalised Winkler model for the behaviour of shallow foundations. Housby G. T., Cassidy M. J. & Einav I., 449–460

Technical note. Complete limiting stress solutions for the bearing capacity of strip footings on a Mohr–Coulomb soil. Smith C. C., 607–612

Linear matching method for limit load problems using the Drucker–Prager yield condition. Boulbibane M. & Ponter A. R. S., 731–740

Technical note. Depth factors for undrained bearing capacity Edwards D. H., Zdravkovic L. & Potts D. M., 755–758

Buried structures

Soil–pipe interaction due to tunnelling: comparison between Winkler and elastic continuum solutions. Klar A., Vorster T. E. B., Soga K. & Mair R. J., 461–466

Calcareous soils

The influence of the *in situ* state of sands on the load–deflection behaviour of driven piles. Coop M. R., Klotz E. U. & Clinton L., 721–730

Case history

Stochastic evaluation of static liquefaction in a predominantly dilative sand fill. Hicks M. A. & Onisiphorou C., 123–133

A review of Beliche Dam. Alonso E. E., Olivella S. & Pinyol N. M., 267–285

Long-term performance of contaminant barrier systems. Rowe R. K., 631–678

Centrifuge modelling

Generalised scaling relations for dynamic centrifuge tests. Iai S., Tobita T. & Nakahara T., 355–362

Scale effects on tension capacity for rough piles buried in dense sand. Lehane B. M., Gaudin C. & Schneider J. A., 709–719

The influence of the *in situ* state of sands on the load–deflection behaviour of driven piles. Coop M. R., Klotz E. U. & Clinton L., 721–730

Influence of base suction on extraction of jack-up spudcans. Purwana O. A., Leung C. F., Chow Y. K. and Foo K. S., 741–753

Chalk

A deterministic/stochastic model to predict the variation in bulk modulus of chalk. Collin F., Schroeder Ch., De Gennaro V. and Bolle A., 135–141

Chemical properties

Technical note. Hydrophobic modification of an expansive soil using polymers and organic compounds: a comparative study with lime. Hernández J., Vargas S., Estévez M., Vázquez G., Zepeda A. and Rodríguez R., 613–616

Clays

Field trials of suction caissons in clay for offshore wind turbine foundations. Housby G. T., Kelly R. B., Huxtable J. & Byrne B. W., 287–296

Coupling of hydraulic and mechanical behaviour in unsaturated compacted clay. Tarantino A. & Tombolato S., 307–317

Laboratory investigation of permeability measurement in clay using outflow from unsupported cavities. Hird C. C. & Srisakthivel S., 393–402

Technical note. Shear-plate transducers as a possible alternative to bender elements for measuring G_{max} . Ismail M. A. & Rammah K. I., 403–407

Simple plasticity-based prediction of the undrained settlement of shallow circular foundations on clay. Osman A. S. & Bolton M. D., 435–447

A field permeability measurement technique using a conventional self-boring pressuremeter. Ratnam S., Soga K. & Whittle R. W., 527–537

- Coefficient of consolidation from piezocone measurements. Sills G. C. & Hird C. C., 597–602
- Technical note. Hydrophobic modification of an expansive soil using polymers and organic compounds: a comparative study with lime. Hernández J., Vargas S., Estévez M., Vázquez G., Zepeda A. and Rodríguez R., 613–616
- Limiting cavity depth for spudcan foundations penetrating clay. Hossain M. S., Hu Y., Randolph M. F. & White D. J., 679–690
- Influence of base suction on extraction of jack-up spudcans. Purwana O. A., Leung C. F., Chow Y. K. and Foo K. S., 741–753
- Technical note. Measurement of pore water pressure of clay-infilled rock joints during triaxial shearing. Indraratna B. & Jayanathan M., 759–764
- Collapsed settlement**
A review of Beliche Dam. Alonso E. E., Olivella S. & Pinyol N. M., 267–285
- Compaction**
Technical note. Hydrophobic modification of an expansive soil using polymers and organic compounds: a comparative study with lime. Hernández J., Vargas S., Estévez M., Vázquez G., Zepeda A. and Rodríguez R., 613–616
- Compressibility**
An experimental investigation of the mechanical behaviour of an unsaturated gneiss soil. Futai M. M. & Almeida M. S. S., 201–213
Technical note. Pore pressure coefficient for soil and rock and its relation to compressional wave velocity. Yang J., 251–256
Technical note. A physical justification for $\log e - \log \sigma$ based on fractal crushing and particle kinematics. McDowell G. R., 697–698
- Consolidation**
One-dimensional consolidation of lumpy clay with non-linear properties. Yang L.-A. & Tan T. S., 227–235
Coefficient of consolidation from piezocone measurements. Sills G. C. & Hird C. C., 597–602
- Constitutive relations**
A review of Beliche Dam. Alonso E. E., Olivella S. & Pinyol N. M., 267–285
The concept of stored plastic work or frozen elastic energy in soil mechanics. Collins I. F., 373–382
An experimental investigation of work dissipation in crushable materials. Tarantino A. & Hyde A. F. L., 575–584
Technical note. A physical justification for $\log e - \log \sigma$ based on fractal crushing and particle kinematics. McDowell G. R., 697–698
- Dams**
A review of Beliche Dam. Alonso E. E., Olivella S. & Pinyol N. M., 267–285
- Deep excavation**
Modelling of 3D excavation in finite element analysis. Zdravkovic L., Potts D. M. and St John H. D., 497–513
- Deformation**
A shear strength model for idealised infilled joints under constant normal stiffness. Indraratna B., Welideniya H. S. & Brown E. T., 215–226
Technical note. Effect of confining pressure on the degradation of ballast under cyclic loading. Indraratna B., Lackenby J. & Christie D., 325–328
Generalised scaling relations for dynamic centrifuge tests. Iai S., Tobita T. & Nakahara T., 355–362
Simple plasticity-based prediction of the undrained settlement of shallow circular foundations on clay. Osman A. S. & Bolton M. D., 435–447
Soil–pipe interaction due to tunnelling: comparison between Winkler and elastic continuum solutions. Klar A., Vorster T. E. B., Soga K. & Mair R. J., 461–466
Energy and variational principles for piles in dissipative soil. Einav I., 515–525
Technical note. Strength and deformation characteristics of flat and cubical rubber tyre chip–sand mixtures. Bergado D. T., Youwai S. & Rittirong A., 603–606
- Design**
Reliability-based design applied to retaining walls. Low B. K., 63–75
Probabilistic limiting tolerable displacements for serviceability limit state design of foundations. Zhang L. M. & Ng A. M. Y., 151–161
- Partial factors calibration based on reliability analyses for square footings on granular soils. Honjo Y. & Amatya S., 479–491
- Dewatering**
Mechanism of rupture of shaft linings in coal mine areas buried by thick over-soils in East China. Li W. P. & Li X. Q., 237–244
- Dynamics**
Technical note. Pore pressure coefficient for soil and rock and its relation to compressional wave velocity. Yang J., 251–256
Field trials of suction caissons in clay for offshore wind turbine foundations. Houlsby G. T., Kelly R. B., Huxtable J. & Byrne B. W., 287–296
Generalised scaling relations for dynamic centrifuge tests. Iai S., Tobita T. & Nakahara T., 355–362
Technical note. Rayleigh surface waves in an idealised partially saturated soil. Yang J., 409–414
The effects of disseminated methane hydrate on the dynamic stiffness and damping of sand. Clayton C. R. I., Priest J. A. & Best A. I., 423–434
Technical note. Seismic passive resistance by pseudo-dynamic method. Choudhury D. & Nimbalkar S., 699–702
- Earth pressure**
Reliability of traditional retaining wall design. Fenton G. A., Griffiths D. V. & Williams M. B., 55–62
Mechanism of rupture of shaft linings in coal mine areas buried by thick over-soils in East China. Li W. P. & Li X. Q., 237–244
Technical note. Seismic passive resistance by pseudo-dynamic method. Choudhury D. & Nimbalkar S., 699–702
- Earthquakes**
3D effects in seismic liquefaction of stochastically variable soil deposits. Popescu R., Prevost J. H. & Deodatis G., 21–31
Generalised scaling relations for dynamic centrifuge tests. Iai S., Tobita T. & Nakahara T., 355–362
Technical note. Seismic passive resistance by pseudo-dynamic method. Choudhury D. & Nimbalkar S., 699–702
- Elasticity**
The concept of stored plastic work or frozen elastic energy in soil mechanics. Collins I. F., 373–382
Elastic moduli of soils dependent on pressure: a hyperelastic formulation. Houlsby G. T., Amorosi A. & Rojas E., 383–392
Technical note. Rayleigh surface waves in an idealised partially saturated soil. Yang J., 409–414
A generalised Winkler model for the behaviour of shallow foundations. Houlsby G. T., Cassidy M. J. & Einav I., 449–460
Soil–pipe interaction due to tunnelling: comparison between Winkler and elastic continuum solutions. Klar A., Vorster T. E. B., Soga K. & Mair R. J., 461–466
- Embankments**
Technical note. The horizontal failure mechanism of the Wilnis peat dyke. Van Baars S., 319–323
- Environmental engineering**
Long-term performance of contaminant barrier systems. Rowe R. K., 631–678
- Erosion**
Imaging heterogeneities with electrical impedance tomography: laboratory results. Borsic A., Comina C., Foti S., Lancellotta R. & Musso G., 539–547
- Expansive soils**
Technical note. Hydrophobic modification of an expansive soil using polymers and organic compounds: a comparative study with lime. Hernández J., Vargas S., Estévez M., Vázquez G., Zepeda A. and Rodríguez R., 613–616
- Fabric/structure of soils**
Coupling of hydraulic and mechanical behaviour in unsaturated compacted clay. Tarantino A. & Tombolato S., 307–317
Imaging heterogeneities with electrical impedance tomography: laboratory results. Borsic A., Comina C., Foti S., Lancellotta R. & Musso G., 539–547
Technical note. Correlation of surface fractal dimension with frictional angle at critical state of sands. Xu Y. F. & Sun D. A., 691–695

Failure

- Realistic assessment of slope reliability for effective landslide hazard management. Cheung R. W. M. & Tang W. H., 85–94
- Technical note: The horizontal failure mechanism of the Wilnis peat dyke. Van Baars S., 319–323
- Numerical analysis of a landslide in soils with strain-softening behaviour. Troncone A., 585–596

Field instrumentation

- Field simulation of *in situ* water content and temperature changes due to ground–atmospheric interactions. Cui Y. J., Lu Y. F., Delage P. & Riffard M., 557–567

Footings/foundations

- Towards reliable and effective site investigations. Jaksa M. B., Goldsworthy J. S., Fenton G. A., Kaggwa W. S., Griffiths D. V., Kuo Y. L. & Poulos H. G., 109–121
- Probabilistic limiting tolerable displacements for serviceability limit state design of foundations. Zhang L. M. & Ng A. M. Y., 151–161
- Field trials of suction caissons in clay for offshore wind turbine foundations. Houlby G. T., Kelly R. B., Huxtable J. & Byrne B. W., 287–296
- Review of historical buildings' foundations. Przewłócki, I. Dardzińska & J. Świniański, 363–372
- Simple plasticity-based prediction of the undrained settlement of shallow circular foundations on clay. Osman A. S. & Bolton M. D., 435–447
- A generalised Winkler model for the behaviour of shallow foundations. Houlby G. T., Cassidy M. J. & Einav I., 449–460
- Partial factors calibration based on reliability analyses for square footings on granular soils. Honjo Y. & Amatya S., 479–491
- Technical note. Complete limiting stress solutions for the bearing capacity of strip footings on a Mohr–Coulomb soil. Smith C. C., 607–612
- Limiting cavity depth for spudcan foundations penetrating clay. Hossain M. S., Hu Y., Randolph M. F. & White D. J., 679–690
- Linear matching method for limit load problems using the Drucker–Prager yield condition. Boulbibane M. & Ponter A. R. S., 731–740
- Influence of base suction on extraction of jack-up spudcans. Purwana O. A., Leung C. F., Chow Y. K. and Foo K. S., 741–753
- Technical note. Depth factors for undrained bearing capacity Edwards D. H., Zdravkovic L. & Potts D. M., 755–758

Fractals

- An experimental investigation of work dissipation in crushable materials. Tarantino A. & Hyde A. F. L., 575–584

Friction

- A shear strength model for idealised infilled joints under constant normal stiffness. Indraratna B., Welideniya H. S. & Brown E. T., 215–226
- Technical note. Correlation of surface fractal dimension with frictional angle at critical state of sands. Xu Y. F. & Sun D. A., 691–695
- Scale effects on tension capacity for rough piles buried in dense sand. Lehane B. M., Gaudin C. & Schneider J. A., 709–719

Full-scale tests

- Characterisation of model uncertainties for laterally loaded rigid drilled shafts. Phoon K.-K. & Kulhawey F. H., 54–54

Geophysics

- Imaging heterogeneities with electrical impedance tomography: laboratory results. Borsic A., Comina C., Foti S., Lancellotta R. & Musso G., 539–547

Geosynthetics

- Long-term performance of contaminant barrier systems. Rowe R. K., 631–678

Geotechnical risk

- Non-parametric simulation of geotechnical variability. Bourdeau P. L. & Amundaray J. I., 95–108

Glacial soils

- Shear strength of cohesionless soils at low stress. Fannin R. J., Eliadorani A. & Wilkinson J. M. T., 467–478

Gravels

- Technical note: Effect of confining pressure on the degradation of ballast under cyclic loading. Indraratna B., Lackenby J. & Christie D., 325–328

Ground improvement

- On horizontal variability in lime-cement columns in deep mixing. Larsson S., Stille H. & Olsson L., 33–44

Ground movements

- The influence of soil anisotropy and K_0 on ground surface movements resulting from tunnel excavation. Franzius J. N., Pots D. M. & Burland J. B., 189–199

Groundwater

- Mechanism of rupture of shaft linings in coal mine areas buried by thick over-soils in East China. Li W. P. & Li X. Q., 237–244

Historical review

- Review of historical buildings' foundations. Przewłócki, I. Dardzińska & J. Świniański, 363–372

Hyperstaticity

- Influence of soil heterogeneity on load redistribution and settlement of a hyperstatic three-support frame. Houy L., Breysse D. & Denis A., 163–170

In situ testing

- Random field characterisation of stress-normalised cone penetration testing parameters. Uzielli M., Vannucchi G. & Phoon K.-K., 3–20
- Cone penetration tests under simulated field conditions. Huang A.-B. & Hsu H.-H., 345–354
- A field permeability measurement technique using a conventional self-boring pressuremeter. Ratnam S., Soga K. & Whittle R. W., 527–537
- Coefficient of consolidation from piezocone measurements. Sills G. C. & Hird C. C., 597–602

Industrial waste

- Long-term performance of contaminant barrier systems. Rowe R. K., 631–678

Laboratory tests

- Probabilistic assessment of stability of a cut slope in residual soil. El-Ramly H., Morgenstern N. R. & Cruden D. M., 77–84
- An experimental investigation of the mechanical behaviour of an unsaturated gneiss soil. Futai M. M. & Almeida M. S. S., 201–213
- A shear strength model for idealised infilled joints under constant normal stiffness. Indraratna B., Welideniya H. S. & Brown E. T., 215–226
- Technical note: Pore pressure coefficient for soil and rock and its relation to compressional wave velocity. Yang J., 251–256
- A review of Beliche Dam. Alonso E. E., Olivella S. & Pinyol N. M., 267–285
- Coupling of hydraulic and mechanical behaviour in unsaturated compacted clay. Tarantino A. & Tombolato S., 307–317
- Technical note: Effect of confining pressure on the degradation of ballast under cyclic loading. Indraratna B., Lackenby J. & Christie D., 325–328
- Technical note: Method to compare water content values determined on the basis of different oven-drying temperatures. O'Kelly B. C., 329–332
- Cone penetration tests under simulated field conditions. Huang A.-B. & Hsu H.-H., 345–354
- Technical note. Shear-plate transducers as a possible alternative to bender elements for measuring G_{max} . Ismail M. A. & Rammah K. I., 403–407
- The effects of disseminated methane hydrate on the dynamic stiffness and damping of sand. Clayton C. R. I., Priest J. A. & Best A. I., 423–434
- Imaging heterogeneities with electrical impedance tomography: laboratory results. Borsic A., Comina C., Foti S., Lancellotta R. & Musso G., 539–547
- An experimental investigation of work dissipation in crushable materials. Tarantino A. & Hyde A. F. L., 575–584
- Long-term performance of contaminant barrier systems. Rowe R. K., 631–678
- Technical note. Correlation of surface fractal dimension with frictional angle at critical state of sands. Xu Y. F. & Sun D. A., 691–695
- Technical note. Measurement of pore water pressure of clay-filled rock joints during triaxial shearing. Indraratna B. & Jayanathan M., 759–764

Landfills

- Long-term performance of contaminant barrier systems. Rowe R. K., 631–678

Landslides

- Probabilistic assessment of stability of a cut slope in residual soil. El-Ramly H., Morgenstern N. R. & Cruden D. M., 77–84
- Realistic assessment of slope reliability for effective landslide hazard management. Cheung R. W. M. & Tang W. H., 85–94

Limit state design/analysis

- Characterisation of model uncertainties for laterally loaded rigid drilled shafts. Phoon K.-K. & Kulhawy F. H., 54–54
- Probabilistic limiting tolerable displacements for serviceability limit state design of foundations. Zhang L. M. & Ng A. M. Y., 151–161
- Chen J., Yin J.-H. and Lee C. F.
- A three-dimensional upper-bound approach to slope stability analysis based on RFEM. Chen J., Yin J.-H. and Lee C. F., 549–556
- Technical note. Complete limiting stress solutions for the bearing capacity of strip footings on a Mohr–Coulomb soil. Smith C. C., 607–612
- Linear matching method for limit load problems using the Drucker–Prager yield condition. Boulbibane M. & Ponter A. R. S., 731–740

Liquefaction

- 3D effects in seismic liquefaction of stochastically variable soil deposits. Popescu R., Prevost J. H. & Deodatis G., 21–31
- Stochastic evaluation of static liquefaction in a predominantly dilative sand fill. Hicks M. A. & Onisiphorou C., 123–133

Load redistribution

- Influence of soil heterogeneity on load redistribution and settlement of a hyperstatic three-support frame. Houy L., Breyse D. & Denis A., 163–170

Mineralogy

- Shear strength of cohesionless soils at low stress. Fannin R. J., Eliadorani A. & Wilkinson J. M. T., 467–478

Model tests

- Characterisation of model uncertainties for laterally loaded rigid drilled shafts. Phoon K.-K. & Kulhawy F. H., 54–54
- Cone penetration tests under simulated field conditions. Huang A.-B. & Hsu H.-H., 345–354
- Generalised scaling relations for dynamic centrifuge tests. Iai S., Tobita T. & Nakahara T., 355–362
- Limiting cavity depth for spudcan foundations penetrating clay. Hossain M. S., Hu Y., Randolph M. F. & White D. J., 679–690

Monitoring

- Field simulation of *in situ* water content and temperature changes due to ground–atmospheric interactions. Cui Y. J., Lu Y. F., Delage P. & Riffard M., 557–567

Numerical modelling and analysis

- Random field characterisation of stress-normalised cone penetration testing parameters. Uzielli M., Vannucchi G. & Phoon K.-K., 3–20
- 3D effects in seismic liquefaction of stochastically variable soil deposits. Popescu R., Prevost J. H. & Deodatis G., 21–31
- Towards reliable and effective site investigations. Jaksa M. B., Goldsworthy J. S., Fenton G. A., Kaggwa W. S., Griffiths D. V., Kuo Y. L. & Poulos H. G., 109–121
- Stochastic evaluation of static liquefaction in a predominantly dilative sand fill. Hicks M. A. & Onisiphorou C., 123–133
- A deterministic/stochastic model to predict the variation in bulk modulus of chalk. Collin F., Schroeder Ch., De Gennaro V. and Bolle A., 135–141
- Geostatistical method for analysing soil displacement from underground urban construction. El Gonnouni M., Riou Y. & Hicher P. Y., 171–182
- The influence of soil anisotropy and K_0 on ground surface movements resulting from tunnel excavation. Franzius J. N., Pots D. M. & Burland J. B., 189–199
- One-dimensional consolidation of lumpy clay with non-linear properties. Yang L.-A. & Tan T. S., 227–235
- Technical note. Crushing a weak granular material: experimental numerical analyses. Lobo-Guerrero S. & Vallejo L. E., 245–249
- A review of Beliche Dam. Alonso E. E., Olivella S. & Pinyol N. M., 267–285
- Numerical modelling of plane strain tests on sands using a particulate approach. Powrie W., Ni Q., Harkness R. M. & Zhang X., 297–306
- Soil–pipe interaction due to tunnelling: comparison between Winkler and elastic continuum solutions. Klar A., Vorster T. E. B., Soga K. & Mair R. J., 461–466

- Modelling of 3D excavation in finite element analysis. Zdravkovic K., Potts D. M. and St John H. D., 497–513
- Field simulation of *in situ* water content and temperature changes due to ground–atmospheric interactions. Cui Y. J., Lu Y. F., Delage P. & Riffard M., 557–567
- Numerical analysis of a landslide in soils with strain-softening behaviour. Troncone A., 585–596
- Technical note. DEM analysis of crushing around driven piles in granular materials. Lobo-Guerrero S. & Vallejo L. E., 617–23
- Long-term performance of contaminant barrier systems. Rowe R. K., 631–678
- Limiting cavity depth for spudcan foundations penetrating clay. Hossain M. S., Hu Y., Randolph M. F. & White D. J., 679–690
- Technical note. Depth factors for undrained bearing capacity. Edwards D. H., Zdravkovic L. & Potts D. M., 755–758

Offshore engineering

- The effects of disseminated methane hydrate on the dynamic stiffness and damping of sand. Clayton C. R. I., Priest J. A. & Best A. I., 423–434
- Limiting cavity depth for spudcan foundations penetrating clay. Hossain M. S., Hu Y., Randolph M. F. & White D. J., 679–690
- Influence of base suction on extraction of jack-up spudcans. Purwana O. A., Leung C. F., Chow Y. K. and Foo K. S., 741–753

Partial saturation

- Technical note: Pore pressure coefficient for soil and rock and its relation to compressional wave velocity. Yang J., 251–256
- Coupling of hydraulic and mechanical behaviour in unsaturated compacted clay. Tarantino A. & Tombolato S., 307–317
- Technical note. Rayleigh surface waves in an idealised partially saturated soil. Yang J., 409–414

Particle crushing

- An experimental investigation of work dissipation in crushable materials. Tarantino A. & Hyde A. F. L., 575–584
- Technical note. DEM analysis of crushing around driven piles in granular materials. Lobo-Guerrero S. & Vallejo L. E., 617–23
- Technical note. A physical justification for $\log e - \log \sigma$ based on fractal crushing and particle kinematics. McDowell G. R., 697–698

Permeability

- Laboratory investigation of permeability measurement in clay using outflow from unsupported cavities. Hird C. C. & Srisakthivel S., 393–402
- A field permeability measurement technique using a conventional self-boring pressuremeter. Ratnam S., Soga K. & Whittle R. W., 527–537
- Technical note. Non-steady flow in the variable-head permeability test. Nader J. J., 703

Piles

- Characterisation of model uncertainties for laterally loaded rigid drilled shafts. Phoon K.-K. & Kulhawy F. H., 54–54
- Energy and variational principles for piles in dissipative soil. Einav I., 515–525
- Technical note. DEM analysis of crushing around driven piles in granular materials. Lobo-Guerrero S. & Vallejo L. E., 617–23
- Scale effects on tension capacity for rough piles buried in dense sand. Lehan B. M., Gaudin C. & Schneider J. A., 709–719
- The influence of the *in situ* state of sands on the load–deflection behaviour of driven piles. Coop M. R., Klotz E. U. & Clinton L., 721–730

Plasticity

- The concept of stored plastic work or frozen elastic energy in soil mechanics. Collins I. F., 373–382
- Simple plasticity-based prediction of the undrained settlement of shallow circular foundations on clay. Osman A. S. & Bolton M. D., 435–447
- A generalised Winkler model for the behaviour of shallow foundations. Houlsby G. T., Cassidy M. J. & Einav I., 449–460
- Energy and variational principles for piles in dissipative soil. Einav I., 515–525
- A three-dimensional upper-bound approach to slope stability analysis based on RFEM. Chen J., Yin J.-H. and Lee C. F., 549–556
- Technical note. Complete limiting stress solutions for the bearing capacity of strip footings on a Mohr–Coulomb soil. Smith C. C., 607–612
- Limiting cavity depth for spudcan foundations penetrating clay. Hossain M. S., Hu Y., Randolph M. F. & White D. J., 679–690

Pollution migration/control

Long-term performance of contaminant barrier systems. Rowe R. K., 631–678

Pore pressures

One-dimensional consolidation of lumpy clay with non-linear properties. Yang L.-A. & Tan T. S., 227–235

Technical note: Pore pressure coefficient for soil and rock and its relation to compressional wave velocity. Yang J., 251–256

Influence of base suction on extraction of jack-up spudcans. Purwana O. A., Leung C. F., Chow Y. K. and Foo K. S., 741–753

Technical note. Measurement of pore water pressure of clay-infilled rock joints during triaxial shearing. Indraratna B. & Jayanathan M., 759–764

Reclamation

One-dimensional consolidation of lumpy clay with non-linear properties. Yang L.-A. & Tan T. S., 227–235

Repeated loading

Technical note: Effect of confining pressure on the degradation of ballast under cyclic loading. Indraratna B., Lackenby J. & Christie D., 325–328

Residual soils

Probabilistic assessment of stability of a cut slope in residual soil. El-Ramly H., Morgenstern N. R. & Cruden D. M., 77–84

An experimental investigation of the mechanical behaviour of an unsaturated gneiss soil. Futai M. M. & Almeida M. S. S., 201–213

Retaining walls

Reliability of traditional retaining wall design. Fenton G. A., Griffiths D. V. & Williams M. B., 55–62

Reliability-based design applied to retaining walls. Low B. K., 63–75

Modelling of 3D excavation in finite element analysis. Zdravkovic K., Potts D. M. and St John H. D., 497–513

Technical note. Seismic passive resistance by pseudo-dynamic method. Choudhury D. & Nimbalkar S., 699–702

Rocks/rock mechanics

Technical note. Measurement of pore water pressure of clay-infilled rock joints during triaxial shearing. Indraratna B. & Jayanathan M., 759–764

Sands

Numerical modelling of plane strain tests on sands using a particulate approach. Powrie W., Ni Q., Harkness R. M. & Zhang X., 297–306

Cone penetration tests under simulated field conditions. Huang A.-B. & Hsu H.-H., 345–354

Technical note. Shear-plate transducers as a possible alternative to bender elements for measuring G_{max} . Ismail M. A. & Rammah K. I., 403–407

Imaging heterogeneities with electrical impedance tomography: laboratory results. Borsic A., Comina C., Foti S., Lancellotta R. & Musso G., 539–547

Technical note. DEM analysis of crushing around driven piles in granular materials. Lobo-Guerrero S. & Vallejo L. E., 617–23

Technical note. Correlation of surface fractal dimension with frictional angle at critical state of sands. Xu Y. F. & Sun D. A., 691–695

Technical note. A physical justification for $\log e - \log \sigma$ based on fractal crushing and particle kinematics. McDowell G. R., 697–698

Scale effects on tension capacity for rough piles buried in dense sand. Lehane B. M., Gaudin C. & Schneider J. A., 709–719

The influence of the in situ state of sands on the load–deflection behaviour of driven piles. Coop M. R., Klotz E. U. & Clinton L., 721–730

Settlement

Influence of soil heterogeneity on load redistribution and settlement of a hyperstatic three-support frame. Houy L., Breyse D. & Denis A., 163–170

Geostatistical method for analysing soil displacement from underground urban construction. El Gonnouni M., Riou Y. & Hicher P. Y., 171–182

The influence of soil anisotropy and K_0 on ground surface movements resulting from tunnel excavation. Franzius J. N., Pots D. M. & Burland J. B., 189–199

Shear strength

An experimental investigation of the mechanical behaviour of an unsaturated gneiss soil. Futai M. M. & Almeida M. S. S., 201–213

A shear strength model for idealised infilled joints under constant normal stiffness. Indraratna B., Welideniya H. S. & Brown E. T., 215–226

Coupling of hydraulic and mechanical behaviour in unsaturated compacted clay. Tarantino A. & Tombolato S., 307–317

Cone penetration tests under simulated field conditions. Huang A.-B. & Hsu H.-H., 345–354

Shear strength of cohesionless soils at low stress. Fannin R. J., Eliadorani A. & Wilkinson J. M. T., 467–478

An experimental investigation of work dissipation in crushable materials. Tarantino A. & Hyde A. F. L., 575–584

Technical note. Correlation of surface fractal dimension with frictional angle at critical state of sands. Xu Y. F. & Sun D. A., 691–695

Technical note. Measurement of pore water pressure of clay-infilled rock joints during triaxial shearing. Indraratna B. & Jayanathan M., 759–764

Site investigation

Random field characterisation of stress-normalised cone penetration testing parameters. Uzielli M., Vannucchi G. & Phoon K.-K., 3–20

Towards reliable and effective site investigations. Jaksa M. B., Goldsworthy J. S., Fenton G. A., Kaggwa W. S., Griffiths D. V., Kuo Y. L. & Poulos H. G., 109–121

Laboratory investigation of permeability measurement in clay using outflow from unsupported cavities. Hird C. C. & Srisakthivel S., 393–402

A field permeability measurement technique using a conventional self-boring pressuremeter. Ratnam S., Soga K. & Whittle R. W., 527–537

Coefficient of consolidation from piezocone measurements. Sills G. C. & Hird C. C., 597–602

Slopes

Probabilistic assessment of stability of a cut slope in residual soil. El-Ramly H., Morgenstern N. R. & Cruden D. M., 77–84

Realistic assessment of slope reliability for effective landslide hazard management. Cheung R. W. M. & Tang W. H., 85–94

Stochastic evaluation of static liquefaction in a predominantly dilative sand fill. Hicks M. A. & Onisiphorou C., 123–133

Technical note. Rainfall-induced slope failure considering variability of soil properties. Zhang L. L., Zhang L. M. & Tang W. H., 183–188

Shear strength of cohesionless soils at low stress. Fannin R. J., Eliadorani A. & Wilkinson J. M. T., 467–478

A three-dimensional upper-bound approach to slope stability analysis based on RFEM. Chen J., Yin J.-H. and Lee C. F., 549–556

Numerical analysis of a landslide in soils with strain-softening behaviour. Troncone A., 585–596

Soft rocks

A shear strength model for idealised infilled joints under constant normal stiffness. Indraratna B., Welideniya H. S. & Brown E. T., 215–226

Soil classification

Random field characterisation of stress-normalised cone penetration testing parameters. Uzielli M., Vannucchi G. & Phoon K.-K., 3–20

Soil stabilisation

On horizontal variability in lime-cement columns in deep mixing. Larsson S., Stille H. & Olsson L., 33–44

Technical note. Hydrophobic modification of an expansive soil using polymers and organic compounds: a comparative study with lime. Hernández J., Vargas S., Estévez M., Vázquez G., Zepeda A. and Rodríguez R., 613–616

Soil–structure interaction

A generic approach to soil–structure interaction considering the effects of soil heterogeneity. Breyse D., Niandou H., Elachachi S. & Houy L., 143–150

Influence of soil heterogeneity on load redistribution and settlement of a hyperstatic three-support frame. Houy L., Breyse D. & Denis A., 163–170

Geostatistical method for analysing soil displacement from underground urban construction. El Gonnouni M., Riou Y. & Hicher P. Y., 171–182

Mechanism of rupture of shaft linings in coal mine areas buried by thick over-soils in East China. Li W. P. & Li X. Q., 237–244

Generalised scaling relations for dynamic centrifuge tests. Iai S., Tobita T. & Nakahara T., 355–362

Energy and variational principles for piles in dissipative soil. Einav I., 515–525

Technical note. Estimation of soil–water characteristics using liquid limit state. Sung S.-G., Lee I.-M., Cho G.-C. & Reddi L. N., 569–573

- Technical note. Seismic passive resistance by pseudo-dynamic method. Choudhury D. & Nimbalkar S., 699–702
- Spatial variability**
Stochastic evaluation of static liquefaction in a predominantly dilative sand fill. Hicks M. A. & Onisiphorou C., 123–133
Influence of soil heterogeneity on load redistribution and settlement of a hyperstatic three-support frame. Houy L., Breyse D. & Denis A., 163–170
- Standards**
Technical note: Method to compare water content values determined on the basis of different oven-drying temperatures. O’Kelly B. C., 329–332
- Statistical analysis**
Random field characterisation of stress-normalised cone penetration testing parameters. Uzielli M., Vannucchi G. & Phoon K.-K., 3–20
On horizontal variability in lime-cement columns in deep mixing. Larsson S., Stille H. & Olsson L., 33–44
Characterisation of model uncertainties for laterally loaded rigid drilled shafts. Phoon K.-K. & Kulhawy F. H., 54–54
Reliability of traditional retaining wall design. Fenton G. A., Griffiths D. V. & Williams M. B., 55–62
Reliability-based design applied to retaining walls. Low B. K., 63–75
Probabilistic assessment of stability of a cut slope in residual soil. El-Ramly H., Morgenstern N. R. & Cruden D. M., 77–84
Realistic assessment of slope reliability for effective landslide hazard management. Cheung R. W. M. & Tang W. H., 85–94
Towards reliable and effective site investigations. Jaksa M. B., Goldsworthy J. S., Fenton G. A., Kaggwa W. S., Griffiths D. V., Kuo Y. L. & Poulos H. G., 109–121
Stochastic evaluation of static liquefaction in a predominantly dilative sand fill. Hicks M. A. & Onisiphorou C., 123–133
Geostatistical method for analysing soil displacement from underground urban construction. El Gonnouni M., Riou Y. & Hicher P. Y., 171–182
Partial factors calibration based on reliability analyses for square footings on granular soils. Honjo Y. & Amatyia S., 479–491
Technical note. Correlation of surface fractal dimension with frictional angle at critical state of sands. Xu Y. F. & Sun D. A., 691–695
- Stiffness**
A generic approach to soil–structure interaction considering the effects of soil heterogeneity. Breyse D., Niandou H., Elachachi S. & Houy L., 143–150
A shear strength model for idealised infilled joints under constant normal stiffness. Indraratna B., Welideniya H. S. & Brown E. T., 215–226
Field trials of suction caissons in clay for offshore wind turbine foundations. Houlsby G. T., Kelly R. B., Huxtable J. & Byrne B. W., 287–296
Elastic moduli of soils dependent on pressure: a hyperelastic formulation. Houlsby G. T., Amorosi A. & Rojas E., 383–392
Technical note. Shear-plate transducers as a possible alternative to bender elements for measuring G_{max} . Ismail M. A. & Rammah K. I., 403–407
Technical note. Rayleigh surface waves in an idealised partially saturated soil. Yang J., 409–414
- Strain localisation**
Numerical analysis of a landslide in soils with strain-softening behaviour. Troncone A., 585–596
- Strength**
Technical note. Strength and deformation characteristics of flat and cubical rubber tyre chip–sand mixtures. Bergado D. T., Youwai S. & Rittirong A., 603–606
- Stress analysis**
Mechanism of rupture of shaft linings in coal mine areas buried by thick over-soils in East China. Li W. P. & Li X. Q., 237–244
Elastic moduli of soils dependent on pressure: a hyperelastic formulation. Houlsby G. T., Amorosi A. & Rojas E., 383–392
- Suction**
An experimental investigation of the mechanical behaviour of an unsaturated gneiss soil. Futai M. M. & Almeida M. S. S., 201–213
Coupling of hydraulic and mechanical behaviour in unsaturated compacted clay. Tarantino A. & Tombolato S., 307–317
Field simulation of *in situ* water content and temperature changes due to ground–atmospheric interactions. Cui Y. J., Lu Y. F., Delage P. & Riffard M., 557–567
Technical note. Estimation of soil-water characteristics using liquid limit state. Sung S.-G., Lee I.-M., Cho G.-C. & Reddi L. N., 569–573
Influence of base suction on extraction of jack-up spudcans. Purwana O. A., Leung C. F., Chow Y. K. & Foo K. S., 741–753
- Temperature effects**
Technical note: Method to compare water content values determined on the basis of different oven-drying temperatures. O’Kelly B. C., 329–332
Long-term performance of contaminant barrier systems. Rowe R. K., 631–678
- Theoretical analysis**
Random field characterisation of stress-normalised cone penetration testing parameters. Uzielli M., Vannucchi G. & Phoon K.-K., 3–20
Mechanism of rupture of shaft linings in coal mine areas buried by thick over-soils in East China. Li W. P. & Li X. Q., 237–244
The concept of stored plastic work or frozen elastic energy in soil mechanics. Collins I. F., 373–382
Simple plasticity-based prediction of the undrained settlement of shallow circular foundations on clay. Osman A. S. & Bolton M. D., 435–447
A generalised Winkler model for the behaviour of shallow foundations. Houlsby G. T., Cassidy M. J. & Einav I., 449–460
Energy and variational principles for piles in dissipative soil. Einav I., 515–525
- Time dependence**
Realistic assessment of slope reliability for effective landslide hazard management. Cheung R. W. M. & Tang W. H., 85–94
Long-term performance of contaminant barrier systems. Rowe R. K., 631–678
Technical note. Seismic passive resistance by pseudo-dynamic method. Choudhury D. & Nimbalkar S., 699–702
- Triaxial tests**
Technical note. Strength and deformation characteristics of flat and cubical rubber tyre chip–sand mixtures. Bergado D. T., Youwai S. & Rittirong A., 603–606
- Tunnels**
Geostatistical method for analysing soil displacement from underground urban construction. El Gonnouni M., Riou Y. & Hicher P. Y., 171–182
The influence of soil anisotropy and K_0 on ground surface movements resulting from tunnel excavation. Franzius J. N., Pots D. M. & Burland J. B., 189–199
Soil–pipe interaction due to tunnelling: comparison between Winkler and elastic continuum solutions. Klar A., Vorster T. E. B., Soga K. & Mair R. J., 461–466
- Unsaturated soils**
Technical note. Rainfall-induced slope failure considering variability of soil properties. Zhang L. L., Zhang L. M. & Tang W. H., 183–188
- Vibration**
Technical note. Rayleigh surface waves in an idealised partially saturated soil. Yang J., 409–414
- Water flow**
Field simulation of *in situ* water content and temperature changes due to ground–atmospheric interactions. Cui Y. J., Lu Y. F., Delage P. & Riffard M., 557–567
Technical note. Non-steady flow in the variable-head permeability test. Nader J. J., 703
- Waves & wave loading**
Technical note. Shear-plate transducers as a possible alternative to bender elements for measuring G_{max} . Ismail M. A. & Rammah K. I., 403–407