

INDEX TO GÉOTECHNIQUE VOLUME LIX

February, March, April, May, June, August, September, October, November, December 2009

No. 1, 1–78; No. 2, 79–156; No. 3, 157–290; No. 4, 291–413; No. 5, 415–492; No. 6, 493–570; No. 7, 571–467; No. 8, 649–726; No. 9, 727–799; No. 10; 801–878

AUTHOR INDEX

- Abbireddy C. O. R.** *see* Clayton C. R. I. *et al.*, 493–501
- Abbireddy C. O. R., Clayton C. R. I. & Huvenne V. A. I.**
A method of estimating the form of fine particulates, 503–511
- Abuel-Naga H. M., Bergado D. T., Bouazza A. & Pender M.**
Technical note. Thermomechanical model for saturated clays, 273–278
- Acosta-Martinez H. E.** *see* Gourvenec S. *et al.*
- Adam D. & Markiewicz R.**
Energy from earth-coupled structures, foundations, tunnels and sewers, 229–236
- Ahmad K.** *see* Shukla S. K. *et al.*
- Åkesson M., Jacinto A. C., Gatabin C., Sanchez M. & Ledesma A.**
Bentonite THM behaviour at high temperatures: experimental and numerical analysis, 307–318
- Alonso E. E.** *see* Muñoz J. J. *et al.*
See also Gens A. *et al.*
- Amatya B.** *see* Bourne-Webb P. J. *et al.*
- Amis T.** *see* Bourne-Webb P. J. *et al.*
- Andrade J. E.**
A predictive framework for liquefaction instability, 673–682
- Aoyama S.** *see* Fujisawa K. *et al.*
- Augarde C. E.** *see* Jaquin P. A. *et al.*
- Basu D., Salgado R. & Prezzi M.**
A continuum-based model for analysis of laterally loaded piles in layered soils, 127–140
- Baziar M. H., Salemi Sh. & Merrifield C. M.**
Dynamic centrifuge model tests on asphalt-concrete core dams, 763–771
- Bergado D. T.** *see* Abuel-Naga H. M. *et al.*
- Bezuijen A., Sanders M. P. M. & Den Hamer D.**
Technical note. Parameters that influence the pressure filtration characteristics of bentonite grouts, 717–721
- Black J. A.** *see* Sivakumar V. *et al.*, 813–823
- Blight G.**
Solar heating of the soil and evaporation from a soil surface, 355–363
- Bouazza A.** *see* Abuel-Naga H. M. *et al.*
- Bouazza A., Gates W. P. & Ranjith P. G.**
Technical note. Hydraulic conductivity of biopolymer-treated silty sand, 71–72
- Bourne-Webb P. J., Amatya B., Soga K., Amis T., Davidson C. & Payne P.**
Energy pile test at Lambeth College, London: geotechnical and thermodynamic aspects of pile response to heat cycles, 237–248
- Bransby M. F. & Yun G.-J.**
The undrained capacity of skirted strip foundations under combined loading, 115–125
- Brown J. L., Sivakumar V., McKinley J. D., Harmon N. & McDonald K.**
Technical note. The miniature wireless data-logger for pressure measurements in geotechnical applications, 141–146
- Budhu M.** *see* Mahajan S. P. & Budhu M.
- Bui M.** *see* Clayton C. R. I. *et al.*, 429–437
- Buik N.** *see* Dickinson J. S. *et al.*
- Burland J. B.**
Discussion. The founders of *Géotechnique*, 785–788
- Cairns P.** *see* Sivakumar V. *et al.*, 813–823
- Casagrande M. D. T.** *see* Consoli N. C. *et al.*
- Chai J.-C., Matsunaga K., Sakai A. & Hayashi S.**
Technical note. Comparison of vacuum consolidation with surcharge load induced consolidation of a two-layer system, 637–641
- Chandler H. W. & Sands C. M.**
A graphical method for producing yield surfaces for soils, 683–690
- Cheung R. W. M.** *see* Yin J.-H. *et al.*
- Chow Y. K.** *see* Zhou X. X. *et al.*
- Clarke B. G.**
Editorial, 157
Editorial, 291
- Clarke B. G., Hughes D. B. & Hashemi S.**
Discussion. Physical characteristics of subglacial tills, 153–155
- Clayton C. R. I.**
Editorial: Géotechnique—moving on, 1
See also Abbireddy C. O. R. *et al.*
- Clayton C. R. I., Abbireddy C. O. R. & Schiebel R.**
A method of estimating the form of coarse particulates, 493–501
- Clayton C. R. I., Priest J. A., Bui M., Zervos A. & Kim S. G.**
The Stokoe resonant column apparatus: effects of stiffness, mass and specimen fixity, 429–437
- Cleall P.** *see* Thomas H. R. *et al.*, 173–184
- Cleall P. J.** *see* Thomas H. R. *et al.*, 401–413
- Consoli N. C., Casagrande M. D. T., Thomé A., Dalla Rosa F. & Fahey M.**
Technical note. Effect of relative density on plate loading tests on fibre-reinforced sand, 471–476
- Coop M.** *see* Jotisankasa A. *et al.*
- Coop M. R.** *see* Ventouras K. & Coop M. R.
- Cui Y.-J.** *see* Tang A.-M. & Cui Y.-J.
- Cui Y.-J., Le T. T., Tang A. M., Delage P. & Li X. L.**
Investigating the time-dependent behaviour of Boom clay under thermomechanical loading, 319–329
- Dalla Rosa F.** *see* Consoli N. C. *et al.*
- Darve F.** *see* Lignon S. *et al.*
- Davidson C.** *see* Bourne-Webb P. J. *et al.*
- De Col E.** *see* Tarantino A. & De Col E.
- Delage P.** *see* Cui Y.-J. *et al.*
- Den Hamer D.** *see* Bezuijen A. *et al.*
- Di Benedetto H.** *see* Ezaoui A. & Di Benedetto H.
- Dickinson J. S., Buik N., Matthews M. C. & Snijders A.**
Aquifer thermal energy storage: theoretical and operational analysis, 249–260
- Dixon D.** *see* Thomas H. R. *et al.*, 401–413
- Donohue S., O’Sullivan C. & Long M.**
Technical note. Particle breakage during cyclic triaxial loading of a carbonate sand, 477–482
- Drescher A.** *see* Michalowski R. L. & Drescher A.
- Ezaoui A. & Di Benedetto H.**
Experimental measurements of the global anisotropic elastic behaviour of dry Hostun sand during triaxial tests, and effect of sample preparation, 621–635
- Fahey M.** *see* Consoli N. C. *et al.*
- François B.** *see* Hueckel T. *et al.*
- Fenton C. H.** *see* Nishimura S. *et al.*, 213–227
- Fujisawa K., Kobayashi A. & Aoyama S.**
Theoretical description of embankment erosion owing to overflow, 661–671
- Galavi V.** *see* Schweiger H. F. *et al.*
- Gallagher G.** *see* Sivakumar V. *et al.*, 825–838
- Gallipoli D.** *see* Jaquin P. A. *et al.*
- Gandhi M.** *see* Shukla S. K. *et al.*
- Garcia X., Latham J.-P., Xiang J. & Harrison J. P.**
Technical note. A clustered overlapping sphere algorithm to represent real particles in discrete element modeling, 779–784
- Gareau L. F.** *see* Rohe A. *et al.*
- Gatabin C.** *see* Åkesson M. *et al.*
- Gates W. P.** *see* Bouazza A. *et al.*
- Gaudin C.** *see* Lehane B. M. *et al.*
- Gavin K. & Xue J.**
Technical note. Use of a genetic algorithm to perform reliability analysis of unsaturated soil slopes, 545–549
- Gens A.** *see* Nishimura S. *et al.*, 159–171
- Gens A., Sánchez M., Guimarães L. Do N., Alonso E. E., Lloret A., Olivella S., Villar M. V. & Huertas F.**
A full-scale in situ heating test for high-level nuclear waste disposal: observations, analysis and interpretation, 377–399
- Glynn D.** *see* Sivakumar V. *et al.*, 813–823
- Gourvenec S., Acosta-Martinez H. E. & Randolph M. F.**

- Experimental study of uplift resistance of shallow skirted foundations in clay under transient and sustained concentric loading, 525–537
- Gudehus G. & Mašin D.**
Technical note. Graphical representation of constitutive equations, 147–151
- Guimarães L. Do N.** *see* Gens A. *et al.*
- Haldar S. & Sivakumar Babu G. L.**
Design of laterally loaded piles in clays based on cone penetration test data: a reliability-based approach, 593–607
- Harmon N.** *see* Brown J. L. *et al.*
- Harris C.** *see* Thomas H. R. *et al.*, 173–184
- Harrison J. P.** *see* Garcia X. *et al.*
- Hashemi S.** *see* Clarke B. G. *et al.*
- Hayashi S.** *see* Chai J.-C. *et al.*
- Hou W.** *see* Yao Y.-P. *et al.*
- Hueckel T., François B. & Laloui L.**
Explaining thermal failure in saturated clays, 197–212
- Huertas F.** *see* Gens A. *et al.*
- Hughes D.** *see* Sivakumar V. *et al.*, 825–838
- Hughes D. B.** *see* Clarke B. G. *et al.*
- Huvenne V. A. I.** *see* Abbireddy C. O. R. *et al.*
- Indraratna B.** *see* Walker R. & Indraratna B.
- Indraratna B., Vinod J. S. & Lackenby J.**
Technical note. Influence of particle breakage on the resilient modulus of railway ballast, 643–646
- Ishihara K.** *see* Tsukamoto Y. *et al.*
- Jacinto A. C.** *see* Åkesson M. *et al.*
- Jaquin P. A., Augarde C. E., Gallipoli D. & Toll D. G.**
Technical note. The strength of unstabilised rammed earth materials, 487–490
- Jardine R. J.** *see* Nishimura S. *et al.*, 159–171, 213–227
- Jotisankasa A., Coop M. & Ridley A.**
The mechanical behaviour of an unsaturated compacted silty clay, 415–428
- Kamata T.** *see* Tsukamoto Y. *et al.*
- Kern-Leutschg M.** *see* Thomas H. R. *et al.*, 173–184
- Khalili N.** *see* Uchaipichat A. & Khalili N.
- Khoa H. D. V.** *see* Lignon S. *et al.*
- Kikkawa N.** *see* Pender M. J. *et al.*
- Kim S. G.** *see* Clayton C. R. I. *et al.*, 429–437
- Knappett J. A. & Madabhushi S. P. G.**
Influence of axial load on lateral pile response in liquefiable soils. Part I: physical modeling, 571–581
Influence of axial load on lateral pile response in liquefiable soils. Part II: numerical modeling, 583–592
- Kobayashi A.** *see* Fujisawa K. *et al.*
- Lackenby J.** *see* Indraratna B. *et al.*
- Laloui L.** *see* Hueckel T. *et al.*
- Lancellota R. & Pappin J. W.**
Discussion. Contributions to *Géotechnique* 1948–2008: Dynamics, 789–791
- Laouafa F.** *see* Lignon S. *et al.*
- Latham J.-P.** *see* Garcia X. *et al.*
- Le T. T.** *see* Cui Y.-J. *et al.*
- Ledesma A.** *see* Åkesson M. *et al.*
- Lee H. F.** *see* Zhang X. Y. *et al.*
- Lehane B. M., O’Loughlin C. D., Gaudin C. & Randolph M. F.**
Rate effects on penetrometer resistance in kaolin, 41–52
- Leong W. H.** *see* Tarnawski V. R. *et al.*
- Leung C. F.** *see* Zhang X. Y. *et al.*
See also Zhou X. X. *et al.*
- Li X. L.** *see* Cui Y.-J. *et al.*
- Li Y.-C.** *see* Thomas H. R. *et al.*, 173–184
- Lignon S., Laouafa F., Prunier F., Khoa H. D. V. & Darve F.**
Hydro-mechanical modelling of landslides with a material instability criterion, 513–524
- Liu H.** *see* Wood C. J. *et al.*
- Liu P.** *see* Pender M. J. *et al.*
- Lloret A.** *see* Muñoz J. J. *et al.*
See also Gens A. *et al.*
- Long M.** *see* Donohue S. *et al.*
- Madabhushi S. P. G.** *see* Knappett J. A. & Madabhushi S. P. G.
- Mahajan S. P. & Budhu M.**
Technical note. Shear viscosity of clays using the fall cone test, 539–543
- Markiewicz R.** *see* Adam D. & Markiewicz R.
- Martin C. J.** *see* Nishimura S. *et al.*, 213–227
- Martin C. M.**
Technical note. Undrained collapse of a shallow plane-strain trapdoor, 855–863
- Mašin D.** *see* Gudehus G. & Mašin D.
- Massinas S. A. & Sakellariou M. G.**
Closed-form solution for plastic zone formation around a circular tunnel in half-space obeying Mohr–Coulomb criterion, 691–701
- Matsunaga K.** *see* Chai J.-C. *et al.*
- Matthews M. C.** *see* Dickinson J. S. *et al.*
- McDonald K.** *see* Brown J. L. *et al.*
- McKinley J. D.** *see* Brown J. L. *et al.*
- McKinley J. D. & Sivakumar V.**
Technical note. Coefficient of consolidation by plotting velocity against displacement, 553–557
- Merrifield C. M.** *see* Baziar M. H. *et al.*
- Michalowski R. L. & Drescher A.**
Three-dimensional stability of slopes and excavations, 839–849
- Misra A. & Roberts L. A.**
Service limit state resistance factors for drilled shafts, 53–61
- Mitchell H. P.** *see* Thomas H. R. *et al.*, 401–413
- Molenkamp F.** *see* Rohe A. *et al.*
- Momose T.** *see* Tarnawski V. R. *et al.*
- Mooney M. A.** *see* Rinehart R. V. & Mooney M. A.
- Muñoz J. J., Alonso E. E. & Lloret A.**
Thermo-hydraulic characterisation of soft rock by means of heating pulse tests, 293–306
- Nader J. J.**
Technical note. Darcy’s law and the differential equation of motion, 551–552
- Nakamura K.** *see* Toyota H. *et al.*
- Navaneethan T.** *see* Sivakumar V. *et al.*, 825–838
- Nishimura S., Gens A., Olivella S. & Jardine R. J.**
THM-coupled finite element analysis of frozen soil: formulation and application, 159–171
- Nishimura S., Martin C. J., Jardine R. J. & Fenton C. H.**
A new approach for assessing geothermal response to climate change in permafrost regions, 213–227
- O’Loughlin C. D.** *see* Lehane B. M. *et al.*
- Olivella S.** *see* Nishimura S. *et al.*, 159–171
See also Gens A. *et al.*
- O’Sullivan C.** *see* Donohue S. *et al.*
- Pappin J. W.** *see* Lancellota R. & Pappin J. W.
- Payne P.** *see* Bourne-Webb P. J. *et al.*
- Pender M.** *see* Abuel-Naga H. M. *et al.*
- Pender M. J., Kikkawa N. & Liu P.**
Technical note. Macro-void structure and permeability of Auckland residual clay, 773–778
- Powrie W.** *see* Preen M. & Powrie W.
- Preen M. & Powrie W.**
Ground energy systems: from analysis to geotechnical design, 261–271
- Prezzi M.** *see* Basu D. *et al.*
- Priest J. A.** *see* Clayton C. R. I. *et al.*, 429–437
- Prunier F.** *see* Lignon S. *et al.*
- Randolph M. F.** *see* Gourvenec S. *et al.*
See also Lehane B. M. *et al.*
See also Tran M. N. & Randolph M. F.
See also Zhou H. & Randolph M. F., 79–86, 801–812
- Ranjith P. G.** *see* Bouazza A. *et al.*
- Ravishankar B. V.** *see* Sitharam T. G. *et al.*
- Rees S. W.** *see* Thomas H. R. & Rees S. W.
- Ridley A.** *see* Jotisankasa A. *et al.*
- Riffat S. B.** *see* Wood C. J. *et al.*
- Rinehart R. V. & Mooney M. A.**
Measurement depth of vibratory roller-measured soil stiffness, 609–619
- Roberts L. A.** *see* Misra A. & Roberts L. A.
- Rohe A., Gareau L. F. & Molenkamp F.**
Lateral oedometer testing of anisotropic clay as affected by surface roughness, 703–715
- Sakai A.** *see* Chai J.-C. *et al.*
- Sakai N.** *see* Toyota H. *et al.*
- Sakellariou M. G.** *see* Massinas S. A. & Sakellariou M. G.
- Salemi Sh.** *see* Baziar M. H. *et al.*
- Salgado R.** *see* Basu D. *et al.*

- Sanchez M.** *see* Åkesson M. *et al.*
Sánchez M. *see* Gens A. *et al.*
Sands C. M. *see* Chandler H. W. & Sands C. M.
Sanders M. P. M. *see* Bezuijen A. *et al.*
Scharinger F. *see* Schweiger H. F. *et al.*
Schiebel R. *see* Clayton C. R. I. *et al.*, 493–501
Schweiger H. F., Wiltafsky C., Scharinger F. & Galavi V.
 A multilaminate framework for modelling induced and inherent anisotropy of soils, 87–101
Seetharam S. C. *see* Thomas H. R. *et al.*, 279–282
Shiu Y.-K. *see* Yin J.-H. *et al.*
Shukla S. K., Sivakugan N., Gandhi M. & M. Ahmad K.
 Technical note. Improved expressions for field values of compaction test parameters, 851–853
Siddiqua S. *see* Thomas H. R. *et al.*, 279–282
Simpson B. & Tatsuoka F.
 Discussion. Geotechnics: The next 60 years, 723–724
Sitharam T. G., Vinod J. S. & Ravishankar B. V.
 Post-liquefaction undrained monotonic behaviour of sands: experiments and DEM simulations, 739–749
Sivakugan N. *see* Shukla S. K. *et al.*
Sivakumar V. *see* Brown J. L. *et al.*
See also McKinley J. D. & Sivakumar V.
Sivakumar V., Glynn D., Cairns P. & Black J. A.
 A new method of measuring plastic limit of fine materials, 813–823
Sivakumar V., Navaneethan T., Hughes D. & Gallagher G.
 An assessment of earth pressure coefficient in overconsolidated clays, 825–838
Sivakumar Babu G. L. *see* Haldar S. & Sivakumar Babu G. L.
Snijders A. *see* Dickinson J. S. *et al.*
Soga K. *see* Bourne-Webb P. J. *et al.*
Su L.-J. *see* Yin J.-H. *et al.*
Sugimoto M. *see* Toyota H. *et al.*
- Tang A. M.** *see* Cui Y.-J. *et al.*
Tang A.-M. & Cui Y.-J.
 Modelling the thermomechanical volume change behaviour of compacted expansive clays, 185–195
Tang C. *see* Yin J.-H. *et al.*
Tarantino A.
 A water retention model for deformable soils, 751–762
Tarantino A. & De Col E.
 Discussion. Compaction behaviour of clay, 75–77
Tarnawski V. R., Momose T. & Leong W. H.
 Assessing the impact of quartz content on the prediction of soil thermal conductivity, 331–338
Tatsuoka F. *see* Simpson B. & Tatsuoka F.
Thomas H. R. & Rees S. W.
 Measured and simulated heat transfer to foundation soils, 365–375
Thomas H. R., Cleall P., Li Y.-C., Harris C. & Kern-Luetsch M.
 Modelling of cryogenic processes in permafrost and seasonally frozen soils, 173–184
Thomas H. R., Cleall P. J., Dixon D. & Mitchell H. P.
 The coupled thermal-hydraulic-mechanical behaviour of a large-scale in situ heating experiment, 401–413
Thomas H. R., Siddiqua S. & Seetharam S. C.
 Technical note. Inclusion of higher-temperature effects in a soil behaviour model, 279–282
Thomé A. *see* Consoli N. C. *et al.*
Toll D. G. *see* Jaquin P. A. *et al.*
- Toyota H., Nakamura K., Sugimoto M. & Sakai N.**
 Ring shear tests to evaluate strength parameters in various remoulded soils, 649–659
Tran M. N. & Randolph M. F.
 Discussion. Variation of suction pressure during caisson installation in sand, 73–74
Tsukamoto Y., Ishihara K. & Kamata T.
 Technical note. Undrained shear strength of soils under flow deformation, 483–486
- Uchaipichat A. & Khalili N.**
 Experimental investigation of thermo-hydro-mechanical behaviour of an unsaturated silt, 339–353
- Vallejo L. E.**
 Technical note. Fractal analysis of temperature-induced cracking in clays and rocks, 283–286
Ventouras K. & Coop M. R.
 On the behaviour of Thanet Sand: an example of an uncemented natural sand, 727–738
Villar M. V. *see* Gens A. *et al.*
Vinod J. S. *see* Indraratna B. *et al.*
See also Sitharam T. G. *et al.*
- Walker R. & Indraratna B.**
 Consolidation analysis of a stratified soil with vertical and horizontal drainage using the spectral method, 439–449
Wang H. *see* Zhang L. M. & Wang H.
Wiltafsky C. *see* Schweiger H. F. *et al.*
Wood C. J., Liu H. & Riffat S. B.
 Technical note. Use of energy piles in a residential building, and effects on ground temperature and heat pump efficiency, 287–190
- Xiang J.** *see* Garcia X. *et al.*
Xue J. *see* Gavin K. & Xue J.
- Yao Y.-P., Hou W. & Zhou A.-N.**
 UH model: three-dimensional unified hardening model for overconsolidated clays, 451–469
Yin J.-H., Su L.-J., Cheung R. W. M., Shiu Y.-K. & Tang C.
 The influence of grouting pressure on the pullout resistance of soil nails in compacted completely decomposed granite fill, 103–113
Yun G.-J. *see* Bransby M. F. & Yun G.-J.
- Zhang L. M. & Wang H.**
 Technical note. Field study of construction effects in jacked and driven steel H-piles, 63–69
Zhang X. Y., Lee F. H. & Leung C. F.
 Response of caisson breakwater subjected to repeated impulsive loading, 3–16
 Tilt displacement of caisson breakwater due to wave loading, 17–27
Zervos A. *see* Clayton C. R. I. *et al.*, 429–437
Zhou A.-N. *see* Yao Y.-P. *et al.*
Zhou H. & Randolph M. F.
 Resistance of full-flow penetrometers in rate-dependent and strain-softening clay, 79–86
 Numerical investigations into cycling of full-flow penetrometers in soft clay, 801–812
Zhou X. X., Chow Y. K. & Leung C. F.
 Numerical modelling of extraction of spudcans, 29–39

SUBJECT INDEX

Anchors

- Energy from earth-coupled structures, foundations, tunnels and sewers. Adam D. & Markiewicz R., 229–236
 Technical note. Undrained collapse of a shallow plane-strain trapdoor. Martin C. M., 855–863

Anisotropy

- A multilaminate framework for modelling induced and inherent anisotropy of soils. Schweiger H. F., Wiltafsky C., Scharinger F. & Galavi V., 87–101
 Experimental measurements of the global anisotropic elastic behaviour of dry Hostun sand during triaxial tests, and effect of sample preparation. Ezaoui A. & Di Benedetto H., 621–635
 A graphical method for producing yield surfaces for soils. Chandler H. W. & Sands C. M., 683–690

- Lateral oedometer testing of anisotropic clay as affected by surface roughness. Rohe A., Gareau L. F. & Molenkamp F., 703–715
 On the behaviour of Thanet Sand: an example of an uncemented natural sand. Ventouras K. & Coop M. R., 727–738
 An assessment of earth pressure coefficient in overconsolidated clays. Sivakumar V., Navaneethan T., Hughes D. & Gallagher G., 825–838

Bearing capacity

- Energy pile test at Lambeth College, London: geotechnical and thermodynamic aspects of pile response to heat cycles. Bourne-Webb P. J., Amatya B., Soga K., Amis T., Davidson C. & Payne P., 237–248
 Technical note. Effect of relative density on plate loading tests on fibre-reinforced sand. Consoli N. C., Casagrande M. D. T., Thomé A., Dalla Rosa F. & Fahey M., 471–476
 Experimental study of uplift resistance of shallow skirted foundations in

- clay under transient and sustained concentric loading. Gourvenec S., Acosta-Martinez H. E. & Randolph M. F., 525–537
- Buried structures**
 Numerical modelling of extraction of spudcans. Zhou X. X., Chow Y. K. & Leung C. F., 29–39
 Technical note. Undrained collapse of a shallow plane-strain trapdoor. Martin C. M., 855–863
- Calcareous soils**
 Technical note. Particle breakage during cyclic triaxial loading of a carbonate sand. Donohue S., O'Sullivan C. & Long M., 477–482
- Centrifuge modelling**
 Response of caisson breakwater subjected to repeated impulsive loading. Zhang X. Y., Lee F. H. & Leung C. F., 3–16
 Tilt displacement of caisson breakwater due to wave loading. Zhang X. Y., Lee F. H. & Leung C. F., 17–27
 Technical note. The miniature wireless data-logger for pressure measurements in geotechnical applications. Brown J. L., Sivakumar V., McKinley J. D., Harmon N. & McDonald K., 141–146
 Influence of axial load on lateral pile response in liquefiable soils. Part I: physical modeling. Knappett J. A. & Madabhushi S. P. G., 571–581
 Dynamic centrifuge model tests on asphalt-concrete core dams. Baziar M. H., Salemi Sh. & Merrifield C. M., 763–771
- Clays**
 Numerical modelling of extraction of spudcans. Zhou X. X., Chow Y. K. & Leung C. F., 29–39
 Rate effects on penetrometer resistance in kaolin. Lehane B. M., O'Loughlin C. D., Gaudin C. & Randolph M. F., 41–52
 Resistance of full-flow penetrometers in rate-dependent and strain-softening clay. Zhou H. & Randolph M. F., 79–86
 Explaining thermal failure in saturated clays. Hueckel T., François B. & Laloui L., 197–212
 Technical note. Thermomechanical model for saturated clays. Abuel-Naga H. M., Bergado D. T., Bouazza A. & Pender M., 273–278
 Technical note. Fractal analysis of temperature-induced cracking in clays and rocks. Vallejo L. E., 283–286
 Bentonite THM behaviour at high temperatures: experimental and numerical analysis. Åkesson M., Jacinto A. C., Gatabin C., Sanchez M. & Ledesma A., 307–318
 Investigating the time-dependent behaviour of Boom clay under thermomechanical loading. Cui Y.-J., Le T. T., Tang A. M., Delage P. & Li X. L., 319–329
 Consolidation analysis of a stratified soil with vertical and horizontal drainage using the spectral method. Walker R. & Indraratna B., 439–449
 UH model: three-dimensional unified hardening model for overconsolidated clays. Yao Y.-P., Hou W. & Zhou A.-N., 451–469
 Technical note. Shear viscosity of clays using the fall cone test. Mahajan S. P. & Budhu M., 539–543
 Technical note. Coefficient of consolidation by plotting velocity against displacement. McKinley J. D. & Sivakumar V., 553–557
 Design of laterally loaded piles in clays based on cone penetration test data: a reliability-based approach. Haldar S. & Sivakumar Babu G. L., 593–607
 Ring shear tests to evaluate strength parameters in various remoulded soils. Toyota H., Nakamura K., Sugimoto M. & Sakai N., 649–659
 Lateral oedometer testing of anisotropic clay as affected by surface roughness. Rohe A., Gareau L. F. & Molenkamp F., 703–715
 Numerical investigations into cycling of full-flow penetrometers in soft clay. Zhou H. & Randolph M. F., 801–812
 A new method of measuring plastic limit of fine materials. Sivakumar V., Glynn D., Cairns P. & Black J. A., 813–823
 Technical note. Undrained collapse of a shallow plane-strain trapdoor. Martin C. M., 855–863
- Collapsed settlement**
 The mechanical behaviour of an unsaturated compacted silty clay. Jotiskansa A., Coop M. & Ridley A., 415–428
- Compaction**
 The mechanical behaviour of an unsaturated compacted silty clay. Jotiskansa A., Coop M. & Ridley A., 415–428
 Technical note. The strength of unstabilised rammed earth materials. Jaquin P. A., Augarde C. E., Gallipoli D. & Toll D. G., 487–490
 Measurement depth of vibratory roller-measured soil stiffness. Rinehart R. V. & Mooney M. A., 609–619
 Technical note. Improved expressions for field values of compaction test parameters. Shukla S. K., Sivakugan N., Gandhi M. & M. Ahmad K., 851–853
- Compressibility**
 Modelling the thermomechanical volume change behaviour of compacted expansive clays. Tang A.-M. & Cui Y.-J., 185–195
- Consolidation**
 Rate effects on penetrometer resistance in kaolin. Lehane B. M., O'Loughlin C. D., Gaudin C. & Randolph M. F., 41–52
 Consolidation analysis of a stratified soil with vertical and horizontal drainage using the spectral method. Walker R. & Indraratna B., 439–449
 Technical note. Coefficient of consolidation by plotting velocity against displacement. McKinley J. D. & Sivakumar V., 553–557
 Technical note. Comparison of vacuum consolidation with surcharge load induced consolidation of a two-layer system. Chai J.-C., Matsunaga K., Sakai A. & Hayashi S., 637–641
 Technical note. Macro-void structure and permeability of Auckland residual clay. Pender M. J., Kikkawa N. & Liu P., 773–778
- Constitutive relations**
 A multilaminate framework for modelling induced and inherent anisotropy of soils. Schweiger H. F., Wiltafsky C., Scharinger F. & Galavi V., 87–101
 Technical note. Graphical representation of constitutive equations. Gudehus G. & Mašin D., 147–151
 Technical note. Thermomechanical model for saturated clays. Abuel-Naga H. M., Bergado D. T., Bouazza A. & Pender M., 273–278
 UH model: three-dimensional unified hardening model for overconsolidated clays. Yao Y.-P., Hou W. & Zhou A.-N., 451–469
 A graphical method for producing yield surfaces for soils. Chandler H. W. & Sands C. M., 683–690
 A water retention model for deformable soils. Tarantino A., 751–762
- Dams**
 Dynamic centrifuge model tests on asphalt-concrete core dams. Baziar M. H., Salemi Sh. & Merrifield C. M., 763–771
- Deformation**
 Modelling of cryogenic processes in permafrost and seasonally frozen soils. Thomas H. R., Cleall P., Li Y.-C., Harris C. & Kern-Luetschig M., 173–184
 Experimental investigation of thermo-hydro-mechanical behaviour of an unsaturated silt. Uchaipichat A. & Khalili N., 339–353
 UH model: three-dimensional unified hardening model for overconsolidated clays. Yao Y.-P., Hou W. & Zhou A.-N., 451–469
 Influence of axial load on lateral pile response in liquefiable soils. Part I: physical modeling. Knappett J. A. & Madabhushi S. P. G., 571–581
 Influence of axial load on lateral pile response in liquefiable soils. Part II: numerical modeling. Knappett J. A. & Madabhushi S. P. G., 583–592
 Technical note. Influence of particle breakage on the resilient modulus of railway ballast. Indraratna B., Vinod J. S. & Lackenby J., 643–646
- Design**
 Aquifer thermal energy storage: theoretical and operational analysis. Dickinson J. S., Buik N., Matthews M. C. & Snijders A., 249–260
 Design of laterally loaded piles in clays based on cone penetration test data: a reliability-based approach. Haldar S. & Sivakumar Babu G. L., 593–607
 Closed-form solution for plastic zone formation around a circular tunnel in half-space obeying Mohr–Coulomb criterion. Massinas S. A. & Sakellariou M. G., 691–701
- Dewatering**
 Technical note. Parameters that influence the pressure filtration characteristics of bentonite grouts. Bezuijen A., Sanders M. P. M. & Den Hamer D., 717–721
- Drainage**
 Consolidation analysis of a stratified soil with vertical and horizontal drainage using the spectral method. Walker R. & Indraratna B., 439–449
- Dynamics**
 The Stokoe resonant column apparatus: effects of stiffness, mass and specimen fixity. Clayton C. R. I., Priest J. A., Bui M., Zervos A. & Kim S. G., 429–437
 Dynamic centrifuge model tests on asphalt-concrete core dams. Baziar M. H., Salemi Sh. & Merrifield C. M., 763–771

Earth pressure

Technical note. Undrained collapse of a shallow plane-strain trapdoor. Martin C. M., 855–863

Earthquakes

Influence of axial load on lateral pile response in liquefiable soils. Part I: physical modeling. Knappett J. A. & Madabhushi S. P. G., 571–581
 Influence of axial load on lateral pile response in liquefiable soils. Part II: numerical modeling. Knappett J. A. & Madabhushi S. P. G., 583–592

Elasticity

Tilt displacement of caisson breakwater due to wave loading. Zhang X. Y., Lee F. H. & Leung C. F., 17–27
 A continuum-based model for analysis of laterally loaded piles in layered soils. Basu D., Salgado R. & Prezzi M., 127–140
 Technical note. Graphical representation of constitutive equations. Gudehus G. & Mašin D., 147–151
 Technical note. Thermomechanical model for saturated clays. Abuel-Naga H. M., Bergado D. T., Bouazza A. & Pender M., 273–278
 Experimental measurements of the global anisotropic elastic behaviour of dry Hostun sand during triaxial tests, and effect of sample preparation. Ezaoui A. & Di Benedetto H., 621–635
 Lateral oedometer testing of anisotropic clay as affected by surface roughness. Rohe A., Gareau L. F. & Molenkamp F., 703–715

Embankments

Theoretical description of embankment erosion owing to overflow. Fujisawa K., Kobayashi A. & Aoyama S., 661–671

Environmental engineering

Energy from earth-coupled structures, foundations, tunnels and sewers. Adam D. & Markiewicz R., 229–236
 Aquifer thermal energy storage: theoretical and operational analysis. Dickinson J. S., Buik N., Matthews M. C. & Snijders A., 249–260

Erosion

Theoretical description of embankment erosion owing to overflow. Fujisawa K., Kobayashi A. & Aoyama S., 661–671

Excavation

Closed-form solution for plastic zone formation around a circular tunnel in half-space obeying Mohr–Coulomb criterion. Massinas S. A. & Sakellariou M. G., 691–701
 Three-dimensional stability of slopes and excavations. Michalowski R. L. & Drescher A., 839–849

Expansive soils

Modelling the thermomechanical volume change behaviour of compacted expansive clays. Tang A.-M. & Cui Y.-J., 185–195
 Bentonite THM behaviour at high temperatures: experimental and numerical analysis. Åkesson M., Jacinto A. C., Gatabin C., Sanchez M. & Ledesma A., 307–318
 A full-scale in situ heating test for high-level nuclear waste disposal: observations, analysis and interpretation. Gens A., Sánchez M., Guimarães L. Do N., Alonso E. E., Lloret A., Olivella S., Villar M. V. & Huertas F., 377–399
 The coupled thermal-hydraulic-mechanical behaviour of a large-scale in situ heating experiment. Thomas H. R., Cleall P. J., Dixon D. & Mitchell H. P., 401–413

Fabric/structure of soils

A graphical method for producing yield surfaces for soils. Chandler H. W. & Sands C. M., 683–690

Failure

Explaining thermal failure in saturated clays. Hueckel T., François B. & Laloui L., 197–212
 Technical note. Effect of relative density on plate loading tests on fibre-reinforced sand. Consoli N. C., Casagrande M. D. T., Thomé A., Dalla Rosa F. & Fahey M., 471–476
 Hydro-mechanical modelling of landslides with a material instability criterion. Lignon S., Laouafa F., Prunier F., Khoa H. D. V. & Darve F., 513–524
 Technical note. Use of a genetic algorithm to perform reliability analysis of unsaturated soil slopes. Gavin K. & Xue J., 545–549
 Influence of axial load on lateral pile response in liquefiable soils. Part I: physical modeling. Knappett J. A. & Madabhushi S. P. G., 571–581
 Influence of axial load on lateral pile response in liquefiable soils. Part II: numerical modeling. Knappett J. A. & Madabhushi S. P. G., 583–592

Theoretical description of embankment erosion owing to overflow. Fujisawa K., Kobayashi A. & Aoyama S., 661–671

A predictive framework for liquefaction instability. Andrade J. E., 673–682

A graphical method for producing yield surfaces for soils. Chandler H. W. & Sands C. M., 683–690

Three-dimensional stability of slopes and excavations. Michalowski R. L. & Drescher A., 839–849

Field instrumentation

Energy pile test at Lambeth College, London: geotechnical and thermodynamic aspects of pile response to heat cycles. Bourne-Webb P. J., Amaty B., Soga K., Amis T., Davidson C. & Payne P., 237–248
 Measurement depth of vibratory roller-measured soil stiffness. Rinehart R. V. & Mooney M. A., 609–619

Footings/foundations

Technical note. Field study of construction effects in jacked and driven steel H-piles. Zhang L. M. & Wang H., 63–69
 The undrained capacity of skirted strip foundations under combined loading. Bransby M. F. & Yun G.-J., 115–125
 Energy from earth-coupled structures, foundations, tunnels and sewers. Adam D. & Markiewicz R., 229–236
 Energy pile test at Lambeth College, London: geotechnical and thermodynamic aspects of pile response to heat cycles. Bourne-Webb P. J., Amaty B., Soga K., Amis T., Davidson C. & Payne P., 237–248
 Technical note. Effect of relative density on plate loading tests on fibre-reinforced sand. Consoli N. C., Casagrande M. D. T., Thomé A., Dalla Rosa F. & Fahey M., 471–476
 Experimental study of uplift resistance of shallow skirted foundations in clay under transient and sustained concentric loading. Gourvenec S., Acosta-Martinez H. E. & Randolph M. F., 525–537

Fractals

Technical note. Fractal analysis of temperature-induced cracking in clays and rocks. Vallejo L. E., 283–286

Friction

A graphical method for producing yield surfaces for soils. Chandler H. W. & Sands C. M., 683–690

Full-scale tests

Energy pile test at Lambeth College, London: geotechnical and thermodynamic aspects of pile response to heat cycles. Bourne-Webb P. J., Amaty B., Soga K., Amis T., Davidson C. & Payne P., 237–248
 A full-scale in situ heating test for high-level nuclear waste disposal: observations, analysis and interpretation. Gens A., Sánchez M., Guimarães L. Do N., Alonso E. E., Lloret A., Olivella S., Villar M. V. & Huertas F., 377–399
 The coupled thermal-hydraulic-mechanical behaviour of a large-scale in situ heating experiment. Thomas H. R., Cleall P. J., Dixon D. & Mitchell H. P., 401–413

Geology

A new approach for assessing geothermal response to climate change in permafrost regions. Nishimura S., Martin C. J., Jardine R. J. & Fenton C. H., 213–227

Geophysics

Technical note. Use of energy piles in a residential building, and effects on ground temperature and heat pump efficiency. Wood C. J., Liu H. & Riffat S. B., 287–190

Geotextiles

Energy from earth-coupled structures, foundations, tunnels and sewers. Adam D. & Markiewicz R., 229–236

Glacial soils

Lateral oedometer testing of anisotropic clay as affected by surface roughness. Rohe A., Gareau L. F. & Molenkamp F., 703–715

Gravels

A method of estimating the form of coarse particulates. Clayton C. R. I., Abbireddy C. O. R. & Schiebel R., 493–501
 Technical note. Influence of particle breakage on the resilient modulus of railway ballast. Indraratna B., Vinod J. S. & Lackenby J., 643–646

Ground freezing

THM-coupled finite element analysis of frozen soil: formulation and

- application. Nishimura S., Gens A., Olivella S. & Jardine R. J., 159–171
- Modelling of cryogenic processes in permafrost and seasonally frozen soils. Thomas H. R., Cleall P., Li Y.-C., Harris C. & Kern-Luetsch M., 173–184
- A new approach for assessing geothermal response to climate change in permafrost regions. Nishimura S., Martin C. J., Jardine R. J. & Fenton C. H., 213–227
- Ground improvement**
- Technical note. Parameters that influence the pressure filtration characteristics of bentonite grouts. Bezuijen A., Sanders M. P. M. & Den Hamer D., 717–721
- Groundwater**
- Aquifer thermal energy storage: theoretical and operational analysis. Dickinson J. S., Buik N., Matthews M. C. & Snijders A., 249–260
- Ground energy systems: from analysis to geotechnical design. Preene M. & Powrie W., 261–271
- Grouting**
- The influence of grouting pressure on the pullout resistance of soil nails in compacted completely decomposed granite fill. Yin J.-H., Su L.-J., Cheung R. W. M., Shiu Y.-K. & Tang C., 103–113
- Technical note. Parameters that influence the pressure filtration characteristics of bentonite grouts. Bezuijen A., Sanders M. P. M. & Den Hamer D., 717–721
- In situ testing**
- Rate effects on penetrometer resistance in kaolin. Lehané B. M., O'Loughlin C. D., Gaudin C. & Randolph M. F., 41–52
- Technical note. Field study of construction effects in jacked and driven steel H-piles. Zhang L. M. & Wang H., 63–69
- Resistance of full-flow penetrometers in rate-dependent and strain-softening clay. Zhou H. & Randolph M. F., 79–86
- Design of laterally loaded piles in clays based on cone penetration test data: a reliability-based approach. Haldar S. & Sivakumar Babu G. L., 593–607
- Measurement depth of vibratory roller-measured soil stiffness. Rinehart R. V. & Mooney M. A., 609–619
- An assessment of earth pressure coefficient in overconsolidated clays. Sivakumar V., Navaneethan T., Hughes D. & Gallagher G., 825–838
- Laboratory equipment**
- Technical note. The miniature wireless data-logger for pressure measurements in geotechnical applications. Brown J. L., Sivakumar V., McKinley J. D., Harmon N. & McDonald K., 141–146
- The Stokoe resonant column apparatus: effects of stiffness, mass and specimen fixity. Clayton C. R. I., Priest J. A., Bui M., Zervos A. & Kim S. G., 429–437
- Laboratory tests**
- Technical note. Hydraulic conductivity of biopolymer-treated silty sand. Bouazza A., Gates W. P. & Ranjith P. G., 71–72
- Technical note. The miniature wireless data-logger for pressure measurements in geotechnical applications. Brown J. L., Sivakumar V., McKinley J. D., Harmon N. & McDonald K., 141–146
- Technical note. Fractal analysis of temperature-induced cracking in clays and rocks. Vallejo L. E., 283–286
- Bentonite THM behaviour at high temperatures: experimental and numerical analysis. Åkesson M., Jacinto A. C., Gatabin C., Sanchez M. & Ledesma A., 307–318
- Investigating the time-dependent behaviour of Boom clay under thermomechanical loading. Cui Y.-J., Le T. T., Tang A. M., Delage P. & Li X. L., 319–329
- Experimental investigation of thermo-hydro-mechanical behaviour of an unsaturated silt. Uchaipichat A. & Khalili N., 339–353
- The mechanical behaviour of an unsaturated compacted silty clay. Jotisankasa A., Coop M. & Ridley A., 415–428
- The Stokoe resonant column apparatus: effects of stiffness, mass and specimen fixity. Clayton C. R. I., Priest J. A., Bui M., Zervos A. & Kim S. G., 429–437
- Technical note. Particle breakage during cyclic triaxial loading of a carbonate sand. Donohue S., O'Sullivan C. & Long M., 477–482
- Technical note. Undrained shear strength of soils under flow deformation. Tsukamoto Y., Ishihara K. & Kamata T., 483–486
- Technical note. The strength of unstabilised rammed earth materials. Jaquin P. A., Augarde C. E., Gallipoli D. & Toll D. G., 487–490
- A method of estimating the form of coarse particulates. Clayton C. R. I., Abbireddy C. O. R. & Schiebel R., 493–501
- A method of estimating the form of fine particulates. Abbireddy C. O. R., Clayton C. R. I. & Huvenne V. A. I., 503–511
- Technical note. Shear viscosity of clays using the fall cone test. Mahajan S. P. & Budhu M., 539–543
- Technical note. Coefficient of consolidation by plotting velocity against displacement. McKinley J. D. & Sivakumar V., 553–557
- Technical note. Comparison of vacuum consolidation with surcharge load induced consolidation of a two-layer system. Chai J.-C., Matsunaga K., Sakai A. & Hayashi S., 637–641
- Technical note. Influence of particle breakage on the resilient modulus of railway ballast. Indraratna B., Vinod J. S. & Lackenby J., 643–646
- Ring shear tests to evaluate strength parameters in various remoulded soils. Toyota H., Nakamura K., Sugimoto M. & Sakai N., 649–659
- Lateral oedometer testing of anisotropic clay as affected by surface roughness. Rohe A., Gareau L. F. & Molenkamp F., 703–715
- Technical note. Parameters that influence the pressure filtration characteristics of bentonite grouts. Bezuijen A., Sanders M. P. M. & Den Hamer D., 717–721
- Post-liquefaction undrained monotonic behaviour of sands: experiments and DEM simulations. Sitharam T. G., Vinod J. S. & Ravishanker B. V., 739–749
- A water retention model for deformable soils. Tarantino A., 751–762
- A new method of measuring plastic limit of fine materials. Sivakumar V., Glynn D., Cairns P. & Black J. A., 813–823
- Technical note. Improved expressions for field values of compaction test parameters. Shukla S. K., Sivakugan N., Gandhi M. & M. Ahmad K., 851–853
- Landslides**
- Hydro-mechanical modelling of landslides with a material instability criterion. Lignon S., Laouafa F., Prunier F., Khoa H. D. V. & Darve F., 513–524
- Three-dimensional stability of slopes and excavations. Michalowski R. L. & Drescher A., 839–849
- Limit state design/analysis**
- Service limit state resistance factors for drilled shafts. Misra A. & Roberts L. A., 53–61
- Three-dimensional stability of slopes and excavations. Michalowski R. L. & Drescher A., 839–849
- Liquefaction**
- Response of caisson breakwater subjected to repeated impulsive loading. Zhang X. Y., Lee F. H. & Leung C. F., 3–16
- Influence of axial load on lateral pile response in liquefiable soils. Part I: physical modeling. Knappett J. A. & Madabhushi S. P. G., 571–581
- Influence of axial load on lateral pile response in liquefiable soils. Part II: numerical modeling. Knappett J. A. & Madabhushi S. P. G., 583–592
- A predictive framework for liquefaction instability. Andrade J. E., 673–682
- Mineralogy**
- A new method of measuring plastic limit of fine materials. Sivakumar V., Glynn D., Cairns P. & Black J. A., 813–823
- Model tests**
- Technical note. Inclusion of higher-temperature effects in a soil behaviour model. Thomas H. R., Siddiqua S. & Seetharam S. C., 279–282
- Experimental study of uplift resistance of shallow skirted foundations in clay under transient and sustained concentric loading. Gourvenec S., Acosta-Martinez H. E. & Randolph M. F., 525–537
- Monitoring**
- Aquifer thermal energy storage: theoretical and operational analysis. Dickinson J. S., Buik N., Matthews M. C. & Snijders A., 249–260
- Measured and simulated heat transfer to foundation soils. Thomas H. R. & Rees S. W., 365–375
- Numerical modelling**
- Numerical modelling of extraction of spudcans. Zhou X. X., Chow Y. K. & Leung C. F., 29–39
- Service limit state resistance factors for drilled shafts. Misra A. & Roberts L. A., 53–61
- Resistance of full-flow penetrometers in rate-dependent and strain-softening clay. Zhou H. & Randolph M. F., 79–86
- The undrained capacity of skirted strip foundations under combined loading. Bransby M. F. & Yun G.-J., 115–125
- THM-coupled finite element analysis of frozen soil: formulation and

- application. Nishimura S., Gens A., Olivella S. & Jardine R. J., 159–171
- Modelling of cryogenic processes in permafrost and seasonally frozen soils. Thomas H. R., Cleall P., Li Y.-C., Harris C. & Kern-Luetsch M., 173–184
- Modelling the thermomechanical volume change behaviour of compacted expansive clays. Tang A.-M. & Cui Y.-J., 185–195
- A new approach for assessing geothermal response to climate change in permafrost regions. Nishimura S., Martin C. J., Jardine R. J. & Fenton C. H., 213–227
- Energy from earth-coupled structures, foundations, tunnels and sewers. Adam D. & Markiewicz R., 229–236
- Aquifer thermal energy storage: theoretical and operational analysis. Dickinson J. S., Buik N., Matthews M. C. & Sniijders A., 249–260
- Thermo-hydraulic characterisation of soft rock by means of heating pulse tests. Muñoz J. J., Alonso E. E. & Lloret A., 293–306
- Bentonite THM behaviour at high temperatures: experimental and numerical analysis. Åkesson M., Jacinto A. C., Gatabin C., Sanchez M. & Ledesma A., 307–318
- Measured and simulated heat transfer to foundation soils. Thomas H. R. & Rees S. W., 365–375
- A full-scale in situ heating test for high-level nuclear waste disposal: observations, analysis and interpretation. Gens A., Sánchez M., Guimarães L. Do N., Alonso E. E., Lloret A., Olivella S., Villar M. V. & Huertas F., 377–399
- The coupled thermal-hydraulic-mechanical behaviour of a large-scale in situ heating experiment. Thomas H. R., Cleall P. J., Dixon D. & Mitchell H. P., 401–413
- Hydro-mechanical modelling of landslides with a material instability criterion. Lignon S., Laouafa F., Prunier F., Khoa H. D. V. & Darve F., 513–524
- Influence of axial load on lateral pile response in liquefiable soils. Part II: numerical modeling. Knappett J. A. & Madabhushi S. P. G., 583–592
- Theoretical description of embankment erosion owing to overflow. Fujisawa K., Kobayashi A. & Aoyama S., 661–671
- A predictive framework for liquefaction instability. Andrade J. E., 673–682
- Post-liquefaction undrained monotonic behaviour of sands: experiments and DEM simulations. Sitharam T. G., Vinod J. S. & Ravishankar B. V., 739–749
- Dynamic centrifuge model tests on asphalt-concrete core dams. Baziari M. H., Salemi Sh. & Merrifield C. M., 763–771
- Technical note. A clustered overlapping sphere algorithm to represent real particles in discrete element modeling. Garcia X., Latham J.-P., Xiang J. & Harrison J. P., 779–784
- Numerical investigations into cycling of full-flow penetrometers in soft clay. Zhou H. & Randolph M. F., 801–812
- Offshore engineering**
- Numerical modelling of extraction of spudcans. Zhou X. X., Chow Y. K. & Leung C. F., 29–39
- Resistance of full-flow penetrometers in rate-dependent and strain-softening clay. Zhou H. & Randolph M. F., 79–86
- The undrained capacity of skirted strip foundations under combined loading. Bransby M. F. & Yun G.-J., 115–125
- Experimental study of uplift resistance of shallow skirted foundations in clay under transient and sustained concentric loading. Gourvenec S., Acosta-Martinez H. E. & Randolph M. F., 525–537
- Partial saturation**
- Experimental investigation of thermo-hydro-mechanical behaviour of an unsaturated silt. Uchaipichat A. & Khalili N., 339–353
- A full-scale in situ heating test for high-level nuclear waste disposal: observations, analysis and interpretation. Gens A., Sánchez M., Guimarães L. Do N., Alonso E. E., Lloret A., Olivella S., Villar M. V. & Huertas F., 377–399
- The coupled thermal-hydraulic-mechanical behaviour of a large-scale in situ heating experiment. Thomas H. R., Cleall P. J., Dixon D. & Mitchell H. P., 401–413
- The mechanical behaviour of an unsaturated compacted silty clay. Jotisankasa A., Coop M. & Ridley A., 415–428
- Technical note. The strength of unstabilised rammed earth materials. Jaquin P. A., Augarde C. E., Gallipoli D. & Toll D. G., 487–490
- Technical note. Use of a genetic algorithm to perform reliability analysis of unsaturated soil slopes. Gavin K. & Xue J., 545–549
- A water retention model for deformable soils. Tarantino A., 751–762
- Particle crushing/crushability**
- Technical note. Influence of particle breakage on the resilient modulus of railway ballast. Indraratna B., Vinod J. S. & Lackenby J., 643–646
- Permeability**
- Technical note. Hydraulic conductivity of biopolymer-treated silty sand. Bouazza A., Gates W. P. & Ranjith P. G., 71–72
- Thermo-hydraulic characterisation of soft rock by means of heating pulse tests. Muñoz J. J., Alonso E. E. & Lloret A., 293–306
- Technical note. Macro-void structure and permeability of Auckland residual clay. Pender M. J., Kikkawa N. & Liu P., 773–778
- Pore pressures**
- Thermo-hydraulic characterisation of soft rock by means of heating pulse tests. Muñoz J. J., Alonso E. E. & Lloret A., 293–306
- Investigating the time-dependent behaviour of Boom clay under thermomechanical loading. Cui Y.-J., Le T. T., Tang A. M., Delage P. & Li X. L., 319–329
- Piles**
- Service limit state resistance factors for drilled shafts. Misra A. & Roberts L. A., 53–61
- Technical note. Field study of construction effects in jacked and driven steel H-piles. Zhang L. M. & Wang H., 63–69
- A continuum-based model for analysis of laterally loaded piles in layered soils. Basu D., Salgado R. & Prezzi M., 127–140
- Technical note. Use of energy piles in a residential building, and effects on ground temperature and heat pump efficiency. Wood C. J., Liu H. & Riffat S. B., 287–190
- Influence of axial load on lateral pile response in liquefiable soils. Part I: physical modeling. Knappett J. A. & Madabhushi S. P. G., 571–581
- Influence of axial load on lateral pile response in liquefiable soils. Part II: numerical modeling. Knappett J. A. & Madabhushi S. P. G., 583–592
- Design of laterally loaded piles in clays based on cone penetration test data: a reliability-based approach. Haldar S. & Sivakumar Babu G. L., 593–607
- Plasticity**
- Tilt displacement of caisson breakwater due to wave loading. Zhang X. Y., Lee F. H. & Leung C. F., 17–27
- A multilaminate framework for modelling induced and inherent anisotropy of soils. Schweiger H. F., Wiltafsky C., Scharinger F. & Galavi V., 87–101
- The undrained capacity of skirted strip foundations under combined loading. Bransby M. F. & Yun G.-J., 115–125
- Technical note. Graphical representation of constitutive equations. Gudehus G. & Mašin D., 147–151
- Technical note. Thermomechanical model for saturated clays. Abuel-Naga H. M., Bergado D. T., Bouazza A. & Pender M., 273–278
- UH model: three-dimensional unified hardening model for overconsolidated clays. Yao Y.-P., Hou W. & Zhou A.-N., 451–469
- Ring shear tests to evaluate strength parameters in various remoulded soils. Toyota H., Nakamura K., Sugimoto M. & Sakai N., 649–659
- A predictive framework for liquefaction instability. Andrade J. E., 673–682
- A graphical method for producing yield surfaces for soils. Chandler H. W. & Sands C. M., 683–690
- Closed-form solution for plastic zone formation around a circular tunnel in half-space obeying Mohr–Coulomb criterion. Massinas S. A. & Sakellariou M. G., 691–701
- Technical note. Undrained collapse of a shallow plane-strain trapdoor. Martin C. M., 855–863
- Radioactive waste disposal**
- Modelling the thermomechanical volume change behaviour of compacted expansive clays. Tang A.-M. & Cui Y.-J., 185–195
- Thermo-hydraulic characterisation of soft rock by means of heating pulse tests. Muñoz J. J., Alonso E. E. & Lloret A., 293–306
- Bentonite THM behaviour at high temperatures: experimental and numerical analysis. Åkesson M., Jacinto A. C., Gatabin C., Sanchez M. & Ledesma A., 307–318
- The coupled thermal-hydraulic-mechanical behaviour of a large-scale in situ heating experiment. Thomas H. R., Cleall P. J., Dixon D. & Mitchell H. P., 401–413
- Reinforced soils**
- Technical note. Effect of relative density on plate loading tests on fibre-reinforced sand. Consoli N. C., Casagrande M. D. T., Thomé A., Dalla Rosa F. & Fahey M., 471–476
- Repeated loading**
- Technical note. Influence of particle breakage on the resilient modulus of railway ballast. Indraratna B., Vinod J. S. & Lackenby J., 643–646

Residual soils

Technical note. Macro-void structure and permeability of Auckland residual clay. Pender M. J., Kikkawa N. & Liu P., 773–778

Rocks/rock mechanics

Technical note. Fractal analysis of temperature-induced cracking in clays and rocks. Vallejo L. E., 283–286

Sampling

An assessment of earth pressure coefficient in overconsolidated clays. Sivakumar V., Navaneethan T., Hughes D. & Gallagher G., 825–838

Sands

Tilt displacement of caisson breakwater due to wave loading. Zhang X. Y., Lee F. H. & Leung C. F., 17–27

Aquifer thermal energy storage: theoretical and operational analysis. Dickinson J. S., Buik N., Matthews M. C. & Snijders A., 249–260

Technical note. Effect of relative density on plate loading tests on fibre-reinforced sand. Consoli N. C., Casagrande M. D. T., Thomé A., Dalla Rosa F. & Fahey M., 471–476

Technical note. Particle breakage during cyclic triaxial loading of a carbonate sand. Donohue S., O'Sullivan C. & Long M., 477–482

Technical note. Undrained shear strength of soils under flow deformation. Tsukamoto Y., Ishihara K. & Kamata T., 483–486

A method of estimating the form of coarse particulates. Clayton C. R. I., Abbireddy C. O. R. & Schiebel R., 493–501

Experimental measurements of the global anisotropic elastic behaviour of dry Hostun sand during triaxial tests, and effect of sample preparation. Ezaoui A. & Di Benedetto H., 621–635

A predictive framework for liquefaction instability. Andrade J. E., 673–682

On the behaviour of Thanet Sand: an example of an uncemented natural sand. Ventouras K. & Coop M. R., 727–738

Post-liquefaction undrained monotonic behaviour of sands: experiments and DEM simulations. Sitharam T. G., Vinod J. S. & Ravishanker B. V., 739–749

Seepage

Technical note. Darcy's law and the differential equation of motion. Nader J. J., 551–552

Settlement

Service limit state resistance factors for drilled shafts. Misra A. & Roberts L. A., 53–61

Technical note. Comparison of vacuum consolidation with surcharge load induced consolidation of a two-layer system. Chai J.-C., Matsunaga K., Sakai A. & Hayashi S., 637–641

Shear strength

Rate effects on penetrometer resistance in kaolin. Lehane B. M., O'Loughlin C. D., Gaudin C. & Randolph M. F., 41–52

Resistance of full-flow penetrometers in rate-dependent and strain-softening clay. Zhou H. & Randolph M. F., 79–86

Technical note. Graphical representation of constitutive equations. Gudehus G. & Mašin D., 147–151

Technical note. Thermomechanical model for saturated clays. Abuel-Naga H. M., Bergado D. T., Bouazza A. & Pender M., 273–278

Experimental investigation of thermo-hydro-mechanical behaviour of an unsaturated silt. Uchaipichat A. & Khalili N., 339–353

The mechanical behaviour of an unsaturated compacted silty clay. Jotisankasa A., Coop M. & Ridley A., 415–428

Technical note. Undrained shear strength of soils under flow deformation. Tsukamoto Y., Ishihara K. & Kamata T., 483–486

Technical note. Shear viscosity of clays using the fall cone test. Mahajan S. P. & Budhu M., 539–543

Ring shear tests to evaluate strength parameters in various remoulded soils. Toyota H., Nakamura K., Sugimoto M. & Sakai N., 649–659

Post-liquefaction undrained monotonic behaviour of sands: experiments and DEM simulations. Sitharam T. G., Vinod J. S. & Ravishanker B. V., 739–749

Slopes

A multilaminate framework for modelling induced and inherent anisotropy of soils. Schweiger H. F., Wiltafsky C., Scharinger F. & Galavi V., 87–101

The influence of grouting pressure on the pullout resistance of soil nails in compacted completely decomposed granite fill. Yin J.-H., Su L.-J., Cheung R. W. M., Shiu Y.-K. & Tang C., 103–113

Technical note. Use of a genetic algorithm to perform reliability analysis of unsaturated soil slopes. Gavin K. & Xue J., 545–549

Three-dimensional stability of slopes and excavations. Michalowski R. L. & Drescher A., 839–849

Soft rocks

Thermo-hydraulic characterisation of soft rock by means of heating pulse tests. Muñoz J. J., Alonso E. E. & Lloret A., 293–306

Closed-form solution for plastic zone formation around a circular tunnel in half-space obeying Mohr–Coulomb criterion. Massinas S. A. & Sakellariou M. G., 691–701

Soil classification

A method of estimating the form of coarse particulates. Clayton C. R. I., Abbireddy C. O. R. & Schiebel R., 493–501

A new method of measuring plastic limit of fine materials. Sivakumar V., Glynn D., Cairns P. & Black J. A., 813–823

Soil nailing

The influence of grouting pressure on the pullout resistance of soil nails in compacted completely decomposed granite fill. Yin J.-H., Su L.-J., Cheung R. W. M., Shiu Y.-K. & Tang C., 103–113

Soil stabilisation

Consolidation analysis of a stratified soil with vertical and horizontal drainage using the spectral method. Walker R. & Indraratna B., 439–449

Soil/structure interaction

Numerical modelling of extraction of spudcans. Zhou X. X., Chow Y. K. & Leung C. F., 29–39

Service limit state resistance factors for drilled shafts. Misra A. & Roberts L. A., 53–61

Measurement depth of vibratory roller-measured soil stiffness. Rinehart R. V. & Mooney M. A., 609–619

Standards

Technical note. Improved expressions for field values of compaction test parameters. Shukla S. K., Sivakugan N., Gandhi M. & M. Ahmad K., 851–853

Statistical analysis

Design of laterally loaded piles in clays based on cone penetration test data: a reliability-based approach. Haldar S. & Sivakumar Babu G. L., 593–607

Stiffness

Technical note. Graphical representation of constitutive equations. Gudehus G. & Mašin D., 147–151

The Stokoe resonant column apparatus: effects of stiffness, mass and specimen fixity. Clayton C. R. I., Priest J. A., Bui M., Zervos A. & Kim S. G., 429–437

Measurement depth of vibratory roller-measured soil stiffness. Rinehart R. V. & Mooney M. A., 609–619

An assessment of earth pressure coefficient in overconsolidated clays. Sivakumar V., Navaneethan T., Hughes D. & Gallagher G., 825–838

Stress analysis

Closed-form solution for plastic zone formation around a circular tunnel in half-space obeying Mohr–Coulomb criterion. Massinas S. A. & Sakellariou M. G., 691–701

On the behaviour of Thanet Sand: an example of an uncemented natural sand. Ventouras K. & Coop M. R., 727–738

Stress path

UH model: three-dimensional unified hardening model for overconsolidated clays. Yao Y.-P., Hou W. & Zhou A.-N., 451–469

An assessment of earth pressure coefficient in unsaturated clays. Sivakumar V., Navaneethan T., Hughes D. & Gallagher G., 825–838

Suction

Modelling the thermomechanical volume change behaviour of compacted expansive clays. Tang A.-M. & Cui Y.-J., 185–195

Experimental investigation of thermo-hydro-mechanical behaviour of an unsaturated silt. Uchaipichat A. & Khalili N., 339–353

The mechanical behaviour of an unsaturated compacted silty clay. Jotisankasa A., Coop M. & Ridley A., 415–428

Technical note. The strength of unstabilised rammed earth materials. Jaquin P. A., Augarde C. E., Gallipoli D. & Toll D. G., 487–490

Technical note. Use of a genetic algorithm to perform reliability analysis of unsaturated soil slopes. Gavin K. & Xue J., 545–549

A water retention model for deformable soils. Tarantino A., 751–762

- An assessment of earth pressure coefficient in overconsolidated clays. Sivakumar V., Navaneethan T., Hughes D. & Gallagher G., 825–838
- Temperature effects**
- THM-coupled finite element analysis of frozen soil: formulation and application. Nishimura S., Gens A., Olivella S. & Jardine R. J., 159–171
- Modelling of cryogenic processes in permafrost and seasonally frozen soils. Thomas H. R., Cleall P., Li Y.-C., Harris C. & Kern-Luetsch M., 173–184
- Modelling the thermomechanical volume change behaviour of compacted expansive clays. Tang A.-M. & Cui Y.-J., 185–195
- Explaining thermal failure in saturated clays. Hueckel T., François B. & Laloui L., 197–212
- A new approach for assessing geothermal response to climate change in permafrost regions. Nishimura S., Martin C. J., Jardine R. J. & Fenton C. H., 213–227
- Energy pile test at Lambeth College, London: geotechnical and thermodynamic aspects of pile response to heat cycles. Bourne-Webb P. J., Amatya B., Soga K., Amis T., Davidson C. & Payne P., 237–248
- Aquifer thermal energy storage: theoretical and operational analysis. Dickinson J. S., Buik N., Matthews M. C. & Snijders A., 249–260
- Technical note. Thermomechanical model for saturated clays. Abuel-Naga H. M., Bergado D. T., Bouazza A. & Pender M., 273–278
- Technical note. Inclusion of higher-temperature effects in a soil behaviour model. Thomas H. R., Siddiqua S. & Seetharam S. C., 279–282
- Technical note. Use of energy piles in a residential building, and effects on ground temperature and heat pump efficiency. Wood C. J., Liu H. & Riffat S. B., 287–190
- Thermo-hydraulic characterisation of soft rock by means of heating pulse tests. Muñoz J. J., Alonso E. E. & Lloret A., 293–306
- Bentonite THM behaviour at high temperatures: experimental and numerical analysis. Åkesson M., Jacinto A. C., Gatabin C., Sanchez M. & Ledesma A., 307–318
- Investigating the time-dependent behaviour of Boom clay under thermomechanical loading. Cui Y.-J., Le T. T., Tang A. M., Delage P. & Li X. L., 319–329
- Experimental investigation of thermo-hydro-mechanical behaviour of an unsaturated silt. Uchaipichat A. & Khalili N., 339–353
- Measured and simulated heat transfer to foundation soils. Thomas H. R. & Rees S. W., 365–375
- A full-scale in situ heating test for high-level nuclear waste disposal: observations, analysis and interpretation. Gens A., Sánchez M., Guimarães L. Do N., Alonso E. E., Lloret A., Olivella S., Villar M. V. & Huertas F., 377–399
- The coupled thermal-hydraulic-mechanical behaviour of a large-scale in situ heating experiment. Thomas H. R., Cleall P. J., Dixon D. & Mitchell H. P., 401–413
- Theoretical analysis**
- A continuum-based model for analysis of laterally loaded piles in layered soils. Basu D., Salgado R. & Prezzi M., 127–140
- Consolidation analysis of a stratified soil with vertical and horizontal drainage using the spectral method. Walker R. & Indraratna B., 439–449
- Theoretical description of embankment erosion owing to overflow. Fujisawa K., Kobayashi A. & Aoyama S., 661–671
- A predictive framework for liquefaction instability. Andrade J. E., 673–682
- Lateral oedometer testing of anisotropic clay as affected by surface roughness. Rohe A., Gareau L. F. & Molenkamp F., 703–715
- Technical note. Undrained collapse of a shallow plane-strain trapdoor. Martin C. M., 855–863
- Time dependence**
- Investigating the time-dependent behaviour of Boom clay under thermomechanical loading. Cui Y.-J., Le T. T., Tang A. M., Delage P. & Li X. L., 319–329
- Tunnels**
- Energy from earth-coupled structures, foundations, tunnels and sewers. Adam D. & Markiewicz R., 229–236
- Closed-form solution for plastic zone formation around a circular tunnel in half-space obeying Mohr–Coulomb criterion. Massinas S. A. & Sakellariou M. G., 691–701
- Water flow**
- THM-coupled finite element analysis of frozen soil: formulation and application. Nishimura S., Gens A., Olivella S. & Jardine R. J., 159–171
- Technical note. Darcy's law and the differential equation of motion. Nader J. J., 551–552
- Theoretical description of embankment erosion owing to overflow. Fujisawa K., Kobayashi A. & Aoyama S., 661–671